

ISO/IEC JTC 1/SC 29/WG 1
(ITU-T SG8)

Coding of Still Pictures

JBIG	JPEG
Joint Bi-level Image	Joint Photographic
Experts Group	Experts Group

TITLE: 14492 FCD

SOURCE: JBIG Committee

PROJECT: JTC 1.29.10

STATUS: Final Committee Draft

REQUESTED ACTION: For ballot

DISTRIBUTION: WG1 mailing list

Contact:
ISO/IEC JTC 1/SC 29/WG 1 Convenor – Dr. Daniel T. Lee
Hewlett-Packard Company, 11000 Wolfe Road, MS42U0, Cupertino CA 95014, USA
Telephone: +1 408 447 4160, Fax: +1 408 447 2842, Email: Daniel.Lee@hp.com

14492 FCD
**INFORMATION TECHNOLOGY — CODED REPRESENTATION OF
PICTURE AND AUDIO INFORMATION — LOSSY/LOSSLESS
CODING OF BI-LEVEL IMAGES**

JBIG committee

1999 July 16

Contents

0	Introduction	11
0.1	Interpretation and use of the requirements	11
0.1.1	Subject matter for JBIG2 coding	11
0.1.2	Relationship between segments and documents	12
0.1.3	Structure and use of segments	12
0.1.4	Internal representations	13
0.1.5	Decoding results	13
0.1.6	Decoding procedures	13
0.2	Lossy coding	15
0.2.1	Symbol coding	16
0.2.2	Generic coding	16
0.2.3	Halftone coding	16
0.2.4	Consequences of inadequate segmentation	16
1	Scope	18
2	Normative References	19
3	Terms and Definitions	20
4	Symbols and Abbreviations	25
4.1	Abbreviations	25
4.2	Symbol definitions	25
4.3	Operator definitions	32
5	Conventions	34
5.1	Typographic conventions	34
5.2	Binary notation	34
5.3	Hexadecimal notation	34
5.4	Integer value syntax	34
5.4.1	Bit packing	34
5.4.2	Multi-byte values	34
5.4.3	Bit numbering	34
5.4.4	Signedness	34
5.5	Array notation and conventions	34
5.6	Image and bitmap conventions	35
6	Decoding Procedures	36
6.1	Introduction to decoding procedures	36
6.2	Generic Region Decoding Procedure	36
6.2.1	General description	36
6.2.2	Input parameters	37
6.2.3	Return value	37
6.2.4	Variables used in decoding	37
6.2.5	Decoding using a template and arithmetic coding	37
6.2.5.1	General description	37
6.2.5.2	Coding order and edge conventions	37
6.2.5.3	Fixed templates	38
6.2.5.4	Adaptive template pixels	39
6.2.5.5	Typical prediction for generic direct coding (TPGD)	41
6.2.5.6	Skipped pixels	41
6.2.5.7	Decoding the bitmap	41

6.2.6	Decoding using MMR coding	42
6.3	Generic Refinement Region Decoding Procedure	43
6.3.1	General description	43
6.3.2	Input parameters	43
6.3.3	Return value	43
6.3.4	Variables used in decoding	43
6.3.5	Decoding using a template and arithmetic coding	45
6.3.5.1	General description	45
6.3.5.2	Coding order and edge conventions	45
6.3.5.3	Fixed templates and adaptive templates	45
6.3.5.4	Adaptive template pixels	46
6.3.5.5	Typical prediction for generic refinement (TPGR)	46
6.3.5.6	Decoding the refinement bitmap	46
6.4	Text Region Decoding Procedure	47
6.4.1	General description	47
6.4.2	Input parameters	49
6.4.3	Return value	49
6.4.4	Variables used in decoding	49
6.4.5	Decoding the text region	51
6.4.6	Strip delta T	54
6.4.7	First symbol instance S coordinate	54
6.4.8	Subsequent symbol instance S coordinate	54
6.4.9	Symbol instance T coordinate	54
6.4.10	Symbol instance symbol ID	54
6.4.11	Symbol instance bitmap	54
6.4.11.1	Symbol instance refinement delta width	55
6.4.11.2	Symbol instance refinement delta height	55
6.4.11.3	Symbol instance refinement X offset	55
6.4.11.4	Symbol instance refinement Y offset	55
6.4.11.5	Symbol instance refinement bitmap data size	55
6.5	Symbol Dictionary Decoding Procedure	56
6.5.1	General description	56
6.5.2	Input parameters	56
6.5.3	Return value	56
6.5.4	Variables used in decoding	56
6.5.5	Decoding the symbol dictionary	56
6.5.6	Height class delta height	60
6.5.7	Delta width	60
6.5.8	Symbol bitmap	60
6.5.8.1	Direct-coded symbol bitmap	60
6.5.8.2	Refinement/aggregate-coded symbol bitmap	60
6.5.8.2.1	Number of symbol instances in aggregation	61
6.5.8.2.2	Decoding a bitmap when REFAGGNINST = 1	61
6.5.8.2.3	Setting SBSYMCODES and SBSYMCODELEN	63
6.5.8.2.4	Setting SBSYMS	63
6.5.9	Height class collective bitmap	63
6.5.10	Exported symbols	64
6.6	Halftone Region Decoding Procedure	65
6.6.1	General description	65
6.6.2	Input parameters	65
6.6.3	Return value	65
6.6.4	Variables used in decoding	65
6.6.5	Decoding the halftone region	66
6.6.5.1	Computing HSKIP	68

6.6.5.2	Rendering the patterns	68
6.7	Pattern Dictionary Decoding Procedure	69
6.7.1	General description	69
6.7.2	Input parameters	69
6.7.3	Return value	69
6.7.4	Variables used in decoding	69
6.7.5	Decoding the pattern dictionary	70
7	Control Decoding Procedure	71
7.1	General description	71
7.2	Segment header syntax	72
7.2.1	Segment header fields	72
7.2.2	Segment number	72
7.2.3	Segment header flags	72
7.2.4	Referred-to segment count and retention flags	73
7.2.5	Referred-to segment numbers	74
7.2.6	Segment page association	74
7.2.7	Segment data length	74
7.2.8	Segment header example	75
7.3	Segment types	75
7.3.1	Rules for segment references	77
7.3.2	Rules for page associations	78
7.4	Segment syntaxes	78
7.4.1	Region segment information field	78
7.4.1.1	Region segment bitmap width	78
7.4.1.2	Region segment bitmap height	79
7.4.1.3	Region segment bitmap X location	79
7.4.1.4	Region segment bitmap Y location	79
7.4.1.5	Region segment flags	79
7.4.2	Symbol dictionary segment syntax	80
7.4.2.1	Symbol dictionary segmentdata header	80
7.4.2.1.1	Symbol dictionary flags	80
7.4.2.1.2	Symbol dictionary AT flags	81
7.4.2.1.3	Symbol dictionary refinement AT flags	82
7.4.2.1.4	Number of exported symbols (SDNUMEXSYMS)	82
7.4.2.1.5	Number of new symbols (SDNUMNEWSYMS)	82
7.4.2.1.6	Symbol dictionary segment Huffman table selection	83
7.4.2.2	Decoding a symbol dictionary segment	83
7.4.3	Text region segment syntax	85
7.4.3.1	Text region segment data header	85
7.4.3.1.1	Text region segment flags	85
7.4.3.1.2	Text region segment Huffman flags	86
7.4.3.1.3	Text region refinement AT flags	88
7.4.3.1.4	Number of symbol instances (SBNUMINSTANCES)	88
7.4.3.1.5	Text region segment symbol ID Huffman decoding table	88
7.4.3.1.6	Text region segment Huffman table selection	88
7.4.3.1.7	Symbol ID Huffman table decoding	89
7.4.3.2	Decoding a text region segment	94
7.4.4	Pattern dictionary segment syntax	94
7.4.4.1	Pattern dictionary segment data header	94
7.4.4.1.1	Pattern dictionary flags	94
7.4.4.1.2	Width of the patterns in the pattern dictionary (HDPW)	96
7.4.4.1.3	Height of the patterns in the pattern dictionary (HDPH)	96
7.4.4.1.4	Largest gray-scale value (GRAYMAX)	96

7.4.4.2	Decoding a pattern dictionary segment	96
7.4.5	Halftone region segment syntax	96
7.4.5.1	Halftone region segment data header	96
7.4.5.1.1	Halftone region segment flags	97
7.4.5.1.2	Halftone grid position and size	97
7.4.5.1.2.1	Width of the gray-scale image (HGW)	98
7.4.5.1.2.2	Height of the gray-scale image (HGH)	98
7.4.5.1.2.3	Horizontal offset of the grid (HGX)	98
7.4.5.1.2.4	Vertical offset of the grid (HGY)	98
7.4.5.1.3	Halftone grid vector	98
7.4.5.1.3.1	Horizontal coordinate of the halftone grid vector (HRX)	98
7.4.5.1.3.2	Vertical coordinate of the halftone grid vector (HRY)	98
7.4.5.2	Decoding a halftone region segment	98
7.4.6	Generic region segment syntax	98
7.4.6.1	Generic region segment data header	100
7.4.6.2	Generic region segment flags	100
7.4.6.3	Generic region segment AT flags	100
7.4.6.4	Decoding a generic region segment	101
7.4.7	Generic refinement region syntax	102
7.4.7.1	Generic refinement region segment data header	102
7.4.7.2	Generic refinement region segment flags	102
7.4.7.3	Generic refinement region segment AT flags	103
7.4.7.4	Reference bitmap selection	103
7.4.7.5	Decoding a generic refinement region segment	103
7.4.8	Page information segment syntax	103
7.4.8.1	Page bitmap width	104
7.4.8.2	Page bitmap height	104
7.4.8.3	Page X resolution	104
7.4.8.4	Page Y resolution	104
7.4.8.5	Page segment flags	104
7.4.8.6	Page striping information	105
7.4.9	End of page segment syntax	106
7.4.10	End of stripe segment syntax	106
7.4.11	End of file segment syntax	106
7.4.12	Profiles segment syntax	106
7.4.13	Code table segment syntax	107
7.4.14	Extension segment syntax	107
7.4.15	Defined extension types	107
7.4.15.1	Comment	107
7.4.15.2	Unicode comment	108
8	Page Make-up	109
8.1	Decoder model	109
8.2	Page image composition	109
A	(normative) Arithmetic Integer Decoding Procedure	113
A.1	General description	113
A.2	Procedure for decoding values (except IAID)	113
A.3	The IAID decoding procedure	116

B	(normative) Huffman Table Decoding Procedure	117
B.1	General description	117
B.2	Code table structure	117
B.2.1	Code table flags	118
B.2.2	Code table lowest value	118
B.2.3	Code table highest value	118
B.3	Assigning the prefix codes	119
B.4	Using a Huffman table	119
B.5	Standard Huffman tables	120
C	(normative) Gray-scale Image Decoding Procedure	128
C.1	General description	128
C.2	Input parameters	128
C.3	Return value	128
C.4	Variables used in decoding	128
C.5	Decoding the gray-scale image	129
D	(normative) File Formats	130
D.1	Sequential organisation	130
D.2	Random-access organisation	130
D.3	Embedded organisation	130
D.4	File header syntax	131
D.4.1	ID string	131
D.4.2	File header flags	131
D.4.3	Number of pages	131
E	(normative) Arithmetic Coding	132
E.1	Binary encoding	132
E.1.1	Recursive interval subdivision	132
E.1.2	Coding conventions and approximations	132
E.2	Description of the arithmetic encoder	133
E.2.1	Encoder code register conventions	133
E.2.2	Encoding a decision (ENCODE)	133
E.2.3	Encoding a 1 or 0 (CODE1 and CODE0)	133
E.2.4	Encoding an MPS or LPS (CODEMPS and CODELPS)	136
E.2.5	Probability estimation	138
E.2.6	Renormalisation in the encoder (RENORME)	138
E.2.7	Compressed data output (BYTEOUT)	138
E.2.8	Initialisation of the encoder (INITENC)	138
E.2.9	Termination of encoding (FLUSH)	138
E.2.10	Minimisation of the compressed data	142
E.3	Arithmetic decoding procedure	142
E.3.1	Decoder code register conventions	142
E.3.2	Decoding a decision (DECODE)	146
E.3.3	Renormalisation in the decoder (RENORMD)	146
E.3.4	Compressed data input (BYTEIN)	146
E.3.5	Initialisation of the decoder (INITDEC)	151
E.3.6	Resynchronisation of the decoder	151
E.3.7	Resetting arithmetic coding statistics	151
E.3.8	Saving arithmetic coding statistics	151
F	(informative) Arithmetic Decoding Procedure (Software Conventions)	153
G	(informative) Profiles	155

H (informative) Datastream Example and Test Sequence	157
H.1 Datastream example	157
H.2 Test sequence for arithmetic coder	180
I (informative) List of Patents	185
I.1 List of patents	185
I.2 Contact addresses for patent information	186
J (informative) References	187

List of Tables

1	Entities in the decoding process	15
2	Parameters for the generic region decoding procedure.	37
3	Return value from the generic region decoding procedure.	37
4	Variables used in the generic region decoding procedure.	38
5	The nominal values of the AT pixel locations.	40
6	Parameters for the generic refinement region decoding procedure.	44
7	Return value from the generic refinement region decoding procedure.	44
8	Variables used in the generic refinement region decoding procedure.	44
9	Parameters for the text region decoding procedure.	48
10	Return value from the text region decoding procedure.	49
11	Variables used in the text region decoding procedure.	50
12	Parameters used to decode a symbol instance's bitmap using refinement.	55
13	Parameters for the symbol dictionary decoding procedure.	57
14	Return value from the symbol dictionary decoding procedure.	58
15	Variables used in the symbol dictionary decoding procedure.	58
16	Parameters used to decode a symbol's bitmap using generic bitmap decoding.	61
17	Parameters used to decode a symbol's bitmap using refinement/aggregate decoding.	62
18	Parameters used to decode a symbol's bitmap when REFAGGNINST = 1	62
19	Parameters used to decode a height class collective bitmap.	63
20	Parameters for the halftone region decoding procedure.	65
21	Return value from the halftone region decoding procedure.	65
22	Variables used in the halftone region decoding procedure.	66
23	Parameters used to decode a halftone region's gray-scale value array.	68
24	Parameters for the pattern dictionary decoding procedure.	69
25	Return value from the pattern dictionary decoding procedure.	69
26	Variables used in the pattern dictionary decoding procedure.	70
27	Parameters used to decode a pattern dictionary's collective bitmap.	70
28	Parameters used to decode a symbol dictionary segment.	84
29	Meaning of the run codes	90
30	Example of symbol ID Huffman table encoding	92
31	Parameters used to decode a text region segment.	95
32	Parameters used to decode a pattern dictionary segment.	96
33	Parameters used to decode a halftone region segment.	99
34	Parameters used to decode a generic region segment.	101
35	Parameters used to decode a generic refinement region segment.	104
A.1	Arithmetic integer decoding procedure table	115
B.1	Standard Huffman table A	121
B.2	Standard Huffman table B	121
B.3	Standard Huffman table C	121
B.4	Standard Huffman table D	121
B.5	Standard Huffman table E	122
B.6	Standard Huffman table F	122
B.7	Standard Huffman table G	123
B.8	Standard Huffman table H	123
B.9	Standard Huffman table I	124
B.10	Standard Huffman table J	125
B.11	Standard Huffman table K	125
B.12	Standard Huffman table L	126
B.13	Standard Huffman table M	126
B.14	Standard Huffman table N	126
B.15	Standard Huffman table O	127
C.1	Parameters for the gray-scale image decoding procedure.	128

C.2	Return value from the gray-scale image decoding procedure.	128
C.3	Variables used in the gray-scale image decoding procedure.	128
C.4	Parameters used to decode a bitplane of the gray-scale image.	129
E.1	Qe values and probability estimation process	139
G.1	Profile description for profile 0x00000001	155
G.2	Profile description for profile 0x00000002	155
G.3	Profile description for profile 0x00000003	155
G.4	Profile description for profile 0x00000004	156
G.5	Profile description for profile 0x00000005	156
H.1	Encoder and decoder trace data	181

List of Figures

1	Block diagram of major decoder components.	14
2	The four edges of a bitmap	35
3	Template when GBTEMPLATE =0, showing the AT pixels at their nominal locations.	38
4	Template when GBTEMPLATE =1, showing the AT pixel at its nominal location.	38
5	Template when GBTEMPLATE =2, showing the AT pixel at its nominal location.	39
6	Template when GBTEMPLATE =3, showing the AT pixel at its nominal location.	39
7	Field to which AT pixel locations are restricted.	40
8	Reused context for coding the SLTP pseudo-pixel when GBTEMPLATE is 0.	42
9	Reused context for coding the SLTP pseudo-pixel when GBTEMPLATE is 1.	42
10	Reused context for coding the SLTP pseudo-pixel when GBTEMPLATE is 2.	42
11	Reused context for coding the SLTP pseudo-pixel when GBTEMPLATE is 3.	43
12	13-pixel refinement template showing the AT pixels at their nominal locations.	45
13	10-pixel refinement template	45
14	Reused context for coding the SLTP pseudo-pixel when GRTEMPLATE is 0.	47
15	Reused context for coding the SLTP pseudo-pixel when GRTEMPLATE is 1.	49
16	TPGR template.	49
17	Coded structure of a text region.	51
18	Structure of a strip.	51
19	Structure of a symbol instance when SBREFINE is 0.	52
20	Structure of a symbol instance when SBREFINE is 1.	52
21	The structure of a symbol dictionary.	56
22	Height class coding when SDHUFF is 1 and SDREFAGG is 0.	56
23	Height class coding when SDHUFF is 0 or SDREFAGG is 1.	59
24	Specification of coordinate systems and grid parameters.	67
25	Segment header structure	72
26	Segment header flags	72
27	Referred-to segment count and retention flags — short form	73
28	Region segment data header structure	78
29	Region segment flags field structure	79
30	Symbol dictionary segment data header structure	80
31	Symbol dictionary flags field structure	80
32	Symbol dictionary AT flags field structure when SDTEMPLATE is 0	81
33	Symbol dictionary AT flags field structure when SDTEMPLATE is not 0	82
34	Symbol dictionary refinement AT flags field structure	82
35	Text region segment data header structure	85
36	Text region flags field structure	85
37	Text region Huffman flags field structure	86
38	Text region refinement AT flags field structure	88
39	Pattern dictionary header structure	94
40	Pattern dictionary flags field structure	95
41	Halftone region segment data header structure	96
42	Halftone region segment flags field structure	97
43	Halftone grid position and size field structure	97
44	Halftone grid vector field structure	98
45	Generic region segment data header structure	99
46	Generic region segment flags field structure	100
47	Generic region AT flags field structure when GBTEMPLATE is 0	100
48	Generic region AT flags field structure when GBTEMPLATE is not 0	101
49	Generic refinement region segment data header structure	102
50	Generic refinement region segment flags field structure	102
51	Generic refinement region AT flags field structure	103
52	Page information segment structure	104

53	Page segment flags field structure	105
54	Page striping information field structure	106
A.1	Flowchart for the integer arithmetic decoding procedures (except IAID)	114
B.1	Coded structure of a Huffman table.	117
D.1	Sequential organisation	130
D.2	Random-access organisation	131
E.1	Arithmetic encoder inputs and outputs.	132
E.2	Encoder for the MQ-coder.	134
E.3	ENCODE procedure.	134
E.4	CODE1 procedure.	135
E.5	CODE0 procedure.	135
E.6	CODELPS procedure with conditional MPS/LPS exchange.	136
E.7	CODEMPS procedure with conditional MPS/LPS exchange.	137
E.8	Encoder renormalisation procedure.	140
E.9	BYTEOUT procedure for encoder.	141
E.10	Initialisation of the encoder.	142
E.11	FLUSH procedure.	143
E.12	Setting the final bits in the C register.	144
E.13	Arithmetic decoder inputs and outputs.	144
E.14	Decoder for the MQ-coder.	145
E.15	Decoding an MPS or an LPS.	147
E.16	Decoder MPS path conditional exchange procedure.	148
E.17	Decoder LPS path conditional exchange procedure.	149
E.18	Decoder renormalisation procedure.	150
E.19	BYTEIN procedure for decoder	151
E.20	Initialisation of the decoder.	152
F.1	Initialisation of the software-conventions decoder.	153
F.2	Decoding an MPS or an LPS in the software-conventions decoder.	154
F.3	Inserting a new byte into the C register in the software-conventions decoder.	154
H.1	Test datastream page bitmap	159
H.2	The first symbol in the first symbol dictionary	160
H.3	The height class collective bitmap in the second symbol dictionary	162
H.4	The symbols in the second symbol dictionary	163
H.5	The text region bitmap	165
H.6	The generic region bitmap	166
H.7	The pattern dictionary collective bitmap	167
H.8	The patterns defined in the pattern dictionary	167
H.9	The raw bitplanes for the halftone region	169
H.10	The bitplanes for the halftone region	169
H.11	The halftone region bitmap	170
H.12	The symbols in the symbol dictionaries on the third page	175

0 Introduction

This Recommendation | International Standard, informally called JBIG2, defines a coding method for bi-level images (e.g., black and white printed matter). These are images consisting of a single rectangular bit plane, with each pixel taking on one of just two possible colours. Multiple colours are to be handled using an appropriate higher level standard such as ITU-T Recommendation T.44. It is being drafted by the Joint Bi-level Image Experts Group (JBIG), a “Collaborative Team”, established in 1988, that reports both to ISO/IEC JTC 1/SC29/WG1 and to ITU-T/SG8.

Compression of this type of image is also addressed by existing facsimile standards, for example by the compression algorithms in ITU-T Recommendations T.4 (MH, MR), T.6 (MMR), T.82 (JBIG1), and T.85 (Application profile of JBIG1 for facsimile). Besides the obvious facsimile application, JBIG2 will be useful for document storage and archiving, coding images on the World Wide Web, wireless data transmission, print spooling, and even teleconferencing.

As the result of a process that ended in 1993, JBIG produced a first coding standard formally designated ITU-T Recommendation T.82 | International Standard ISO/IEC 11544, which is informally known as JBIG or JBIG1. JBIG1 is intended to behave as lossless and progressive (lossy-to-lossless) coding. Though it has the capability of lossy coding, the lossy images produced by JBIG1 have significantly lower quality than the original images because the number of pixels in the lossy image cannot exceed one quarter of those in the original image.

On the contrary, JBIG2 was explicitly prepared for lossy, lossless, and lossy-to-lossless image compression. The design goal for JBIG2 was to allow for lossless compression performance better than that of the existing standards, and to allow for lossy compression at much higher compression ratios than the lossless ratios of the existing standards, with almost no visible degradation of quality. In addition, JBIG2 allows both quality-progressive coding, with the progression going from lower to higher (or lossless) quality, and content-progressive coding, successively adding different types of image data (for example, first text, then halftones). A typical JBIG2 encoder decomposes the input bi-level image into several regions and codes each of the regions separately using a different coding method. Such content-based decomposition is very desirable especially in interactive multimedia applications. JBIG2 can also handle a set of images (multiple page document) in an explicit manner.

As is typical with image compression standards, JBIG2 explicitly defines the requirements of a compliant bitstream, and thus defines decoder behavior. JBIG2 does not explicitly define a standard encoder, but instead is flexible enough to allow sophisticated encoder design. In fact, encoder design will be a major differentiator among competing JBIG2 implementations.

Although this document is phrased in terms of actions to be taken by decoders to interpret a bitstream, any decoder that produces the correct result (as defined by those actions) is compliant, regardless of the actions it actually takes.

Annexes A, B, C, D, E are normative, and thus form an integral part of this Specification. Annexes F, G, H, I and J are informative, and thus do not form an integral part of this Specification.

0.1 Interpretation and use of the requirements

This section is informative and designed to aid in interpreting the requirements of this Recommendation | International Standard. The requirements are written to be as general as possible to allow a large amount of implementation flexibility. Hence the language of the requirements is not specific about applications or implementations. In this section a correspondence is drawn between the general wording of the requirements and the intended use of this Recommendation | International Standard in typical applications.

0.1.1 Subject matter for JBIG2 coding

JBIG2 is used to code bi-level documents. A bi-level document contains one or more pages. A typical page contains some text data, that is, some characters of a small size arranged in horizontal or vertical rows. The characters in the text part of a page are called *symbols* in JBIG2. A page may also contain “halftone data”, that is, gray-scale or colour multi-level images (e.g., photographs) that have been dithered to produce bi-level images. The periodic bitmap cells in the halftone part of the page are called *patterns* in JBIG2. In addition, a page may contain other data, such as line art and noise. Such non-text, non-halftone data is called *generic* data in JBIG2.

The JBIG2 image model treats text data and halftone data as special cases. It is expected that a JBIG2 encoder will divide the content of a page into a text region containing digitised text, a halftone region containing digitised halftones, and a generic region containing the remaining digitised image data, such as line-art. In some

circumstances, it is better (in image quality or compressed data size) to consider text or halftones as generic data; conversely, in some circumstances it is better to consider generic data using one of the special cases.

An encoder is permitted to divide a single page into any number of regions, but often three regions will be sufficient, one for textual symbols, one for halftone patterns, and the third for the generic remainder. In some cases, not all types of data may be present, and the page may consist of fewer than three regions.

The various regions may overlap on the physical page. JBIG2 provides means to specify how the overlapping regions are re-combined to form the final page image.

A text region consists of a number of symbols placed at specified locations on a background. The symbols usually correspond to individual text characters. JBIG2 obtains much of its effectiveness by using individual symbols more than once. To reuse a symbol, an encoder or decoder must have a succinct way of referring to it. In JBIG2, the symbols are collected into one or more symbol dictionaries. A symbol dictionary is a set of bitmaps of text symbols, indexed so that a symbol bitmap may be referred to by an index number.

A halftone region consists of a number of patterns placed along a regular grid. The patterns usually correspond to gray-scale values. Indeed, the coding method of the pattern indices is designed as a gray-scale coder. Compression can be realised by representing the binary pixels of one grid cell by a single integer, the halftone index (which is usually a rendered gray-scale value). This many-to-one mapping (the pattern in a cell into a gray-scale value) may have the effect that edge information present in the original bitmap is lost by halftone coding. For this reason, lossless or near-lossless coding of halftones will often be better in image quality (though larger in size) if the halftone is coded with generic coding rather than halftone coding.

0.1.2 Relationship between segments and documents

A JBIG2 file contains the information needed to decode a bi-level document. A JBIG2 file is composed of *segments*. A typical page is coded using several segments. In a simple case, there will be a page information segment, a symbol dictionary segment, a text region segment, a pattern dictionary segment, a halftone region segment, and an end-of-page segment. The page information segment provides general information about the page, such as its size and resolution. The dictionary segments collect bitmaps referred to in the region segments. The region segments describe the appearance of the text and halftone regions by referencing bitmaps from a dictionary and specifying where they should appear on the page. The end-of-page segment marks the end of the page.

0.1.3 Structure and use of segments

Each segment contains a segment header, a data header, and data. The segment header is used to convey segment reference information and, in the case of multi-page documents, page association information. A data header gives information used for decoding the data in the segment. The data describes an image region or a dictionary, or provides other information.

Segments are numbered sequentially. A segment may refer to a lower-numbered, or *earlier*, segment. A region segment is always associated with one specific page of the document. A dictionary segment may be associated with one page of the document, or it may be associated with the document as a whole.

A region segment may refer to one or more earlier dictionary segments. The purpose of such a reference is to allow the decoder to identify symbols in a dictionary segment that are present into the image.

A region segment may refer to an earlier region segment. The purpose of such a reference is to combine the image described by the earlier segment with the current representation of the page.

A dictionary segment may refer to earlier dictionary segments. The symbols added to a dictionary segment may be described directly, or may be described as refinements of symbols described previously, either in the same dictionary segment or in earlier dictionary segments.

A JBIG2 file may be organised in two ways, sequential or random access. In the sequential organisation, each segment's segment header immediately precedes that segment's data header and data, all in sequential order. In the random access organisation, all the segment headers are collected together at the beginning of the file, followed by the data (including data headers) for all the segments, in the same order. This second organisation permits a decoder to determine all segment dependencies without reading the entire file.

A third way of encapsulating of JBIG2-encoded data is to embed it in a non-JBIG2 file — this is sometimes called the *embedded organisation*. In this case a different file format carries JBIG2 segments. The segment header, data header, and data of each segment are stored together, but the embedding file format may store the segments in any order, at any set of locations within its own structure.

0.1.4 Internal representations

Decoded data must be stored before printing or display. While this Recommendation | International Standard does not specify how to store it, its decoding model presumes certain data structures, specifically buffers and dictionaries. Figure 1 illustrates major decoder components and associated buffers. In this figure, decoding procedures are outlined in bold lines, and memory components are outlined in non-bold lines. Also, bold arrows indicate that one decoding procedure invokes another decoding procedure; for example, the symbol dictionary decoding procedure invokes the generic region decoding procedure to decode the bitmaps for the symbols that it defines. Non-bold arrows indicate flow of data: the text region decoding procedure reads symbols from the symbol memory and draws them into the page buffer or an auxiliary buffer. Although it is not shown in Figure 1, the encoded data stream flows to the decoding procedures, and the block labeled "Page and auxiliary buffers" produces the final decoded page images.

The resources required to decode any given JBIG2 bitstream depend on the complexity of that bitstream. Some techniques such as striping can be used to reduce decoder memory requirements. It is estimated that a full-featured decoder may need two full-page buffers, plus about the same amount of dictionary memory, plus about 100 kilobytes of arithmetic coding context memory, to decode most bitstreams.

A buffer is a representation of a bitmap. A buffer is intended to hold a large amount of data, typically the size of a page. A buffer may contain the description of a region or of an entire page. Even if the buffer describes only a region, it has information associated with it that specifies its placement on the page. Decoding a region segment modifies the contents of a buffer.

There is one special buffer, the *page buffer*. It is intended that the decoder accumulate region data directly in the page buffer until the page has been completely decoded; then the data can be sent to an output device or file. Decoding an *immediate* region segment modifies the contents of the page buffer. The usual way of preparing a page is to decode one or more immediate region segments, each one modifying the page buffer. The decoder may output an incomplete page buffer, either as part of progressive transmission or in response to user input. Such output is optional, and its content is not specified by this Recommendation | International Standard.

All other buffers are auxiliary buffers. It is intended that the decoder fill an auxiliary buffer, then later use it to refine the page buffer. In an application, it will often be unnecessary to have any auxiliary buffers. Decoding an *intermediate* region segment modifies the contents of an auxiliary buffer. The decoder may use auxiliary buffers to output pages other than those found in a complete page buffer, either as part of progressive transmission or in response to user input. Such output is optional, and its content is not specified by this Recommendation | International Standard.

A symbol dictionary consists of an indexed set of bitmaps. The bitmaps in a dictionary are typically small, approximately the size of text characters. Unlike a buffer, a bitmap in a dictionary does not have page location information associated with it.

0.1.5 Decoding results

Decoding a segment involves invocation of one or more decoding procedures. The decoding procedures to be invoked are determined by the segment type.

The result of decoding a region segment is a bitmap stored in a buffer, possibly the page buffer. Decoding a region segment may fill a new buffer, or may modify an existing buffer. In typical applications, placing the data into a buffer involves changing pixels from the background colour to the foreground colour, but this Recommendation | International Standard specifies other permissible ways of changing a buffer's pixels.

A typical page will be described by a number of one or more immediate region segments, each one resulting in modification of the page buffer.

Just as it is possible to specify a new symbol in a dictionary by refining a previously specified symbol, it is also possible to specify a new buffer by refining an existing buffer. However, a region may be refined only by the generic refinement decoding procedure. Such a refinement does not make use of the internal structure of the region in the buffer being refined. After a buffer has been refined, the original buffer is no longer available.

The result of decoding a dictionary segment is a new dictionary. The symbols in the dictionary may later be placed into a buffer by the text region decoding procedure.

0.1.6 Decoding procedures

The *generic region decoding procedure* fills or modifies a buffer directly, pixel-by-pixel if arithmetic coding is being used, or by runs of foreground and background pixels if MMR and Huffman coding are being used. In the




Figure 1 — Block diagram of major decoder components.

Table 1 — Entities in the decoding process

Concept	JBIG2 bitstream entity	JBIG2 decoding entity	Physical representation
Document	JBIG2 file	JBIG2 decoder	Output medium or device
Page	Collection of segments	Implicit in control decoding procedure	Page buffer
Region	Region segment	Region decoding procedure	Page buffer or auxiliary buffer
Dictionary	Dictionary segment	Dictionary decoding procedure	List of symbols
Character	Field within a symbol dictionary segment	Symbol dictionary decoding procedure	Symbol bitmap
Gray-scale value	Field within a halftone dictionary segment	Pattern dictionary decoding procedure	Pattern

arithmetic coding case, the prediction context contains only pixels determined by data already decoded within the current segment.

The *generic refinement region decoding procedure* modifies a buffer pixel-by-pixel using arithmetic coding. The prediction context uses pixels determined by data already decoded within the current segment as well as pixels already present either in the page buffer or in an auxiliary buffer.

The *text region decoding procedure* takes symbols from one or more symbol dictionaries and places them in a buffer. This procedure is invoked during the decoding of a text region segment. The text region segment contains the position and index information for each symbol to be placed in the buffer; the bitmaps of the symbols are taken from the symbol dictionaries.

The *symbol dictionary decoding procedure* creates a symbol dictionary, that is, an indexed set of symbol bitmaps. A bitmap in the dictionary may be coded directly; it may be coded as a refinement of a symbol already in a dictionary; or it may be coded as an aggregation of two or more symbols already in dictionaries. This decoding procedure is invoked during the decoding of a symbol dictionary segment.

The *halftone region decoding procedure* takes patterns from a pattern dictionary and places them in a buffer. This procedure is invoked during the decoding of a halftone region segment. The halftone region segment contains the position information for all the patterns to be placed in the buffer, as well as index information for the patterns themselves. The patterns, the fixed-size bitmaps of the halftone, are taken from the halftone dictionaries.

The *pattern dictionary decoding procedure* creates a dictionary, that is, an indexed set of fixed-size bitmaps (patterns). The bitmaps in the dictionary are coded directly and jointly. This decoding procedure is invoked during the decoding of a pattern dictionary segment.

The *control decoding procedure* decodes segment headers, which include segment type information. The segment type determines which decoding procedure must be invoked to decode the segment. The segment type also determines where the decoded output from the segment will be placed. The segment reference information, also present in the segment header and decoded by the control decoding procedure, determines which other segments must be used to decode the current segment. The control decoding procedure affects everything shown in Figure 1, and so is not shown there as a separate block.

Table 1 summarises the types of data being decoded, which decoding procedure is responsible for decoding them, and what the final representations of the decoded data are.

0.2 Lossy coding

This specification does not define how to control lossy coding of bi-level images. Rather it defines how to perform perfect reconstruction of a bitmap that the encoder has chosen to encode. If the encoder chooses to encode a bitmap that is different than the original, the entire process becomes one of lossy coding. The different coding methods allow for different methods of introducing loss in a profitable way.

0.2.1 Symbol coding

Lossy symbol coding provides a natural way of doing lossy coding of text regions. The idea is to allow small differences between the original symbol bitmap and the one indexed in the symbol dictionary. Compression gain is effected by not having to code a large dictionary and, afterwards, by having a cheap symbol index coding as a consequence of the smaller dictionary. It is up to the encoder to decide when two bitmaps are essentially the same or essentially different. This technique was first described in [1].

The hazard of lossy symbol coding is to have *substitution errors*, that is, to have the encoder replace a bitmap corresponding to one character by a bitmap depicting a different character, so that a human reader misreads the character. The risk of substitution errors can be reduced by using intricate measures of difference between bitmaps and/or by making sure that the critical pixels of the indexed bitmap are correct. One way to control this, described in [5], is to index the possibly wrong symbol and then to apply refinement coding to that symbol bitmap. The idea is to encode the basic character shape at little cost, then correct pixels that the encoder believes alter the meaning of the character.

The process of beneficially introducing loss in textual regions may also take simpler forms such as removing flyspecks from documents or regularizing edges of letters. Most likely such changes will lower the code length of the region without affecting the general appearance of the region — possibly even improving the appearance.

A number of examples of performing this sort of lossy symbol coding with JBIG2 can be found in [7].

NOTE — Although the term “text region” is used for regions of the page coded using symbol coding, other possible uses of symbol coding include coding line-art and other non-textual data.

0.2.2 Generic coding

To effect near-lossless coding using generic coding, the encoder applies a preprocess to an original image and encodes the changed image losslessly. The difficulties are to ensure that the changes result in a lower code length and that the quality of the changed image does not suffer badly from the changes. Two possible preprocesses are given in [11]. These preprocesses flip pixels that, when flipped, significantly lower the total code length of the region, but can be flipped without seriously impairing the visual quality. The preprocesses provide for effective near-lossless coding of periodic halftones and for a moderate gain in compression for other data types. The preprocesses are not well-suited for error diffused images and images dithered with blue noise as perceptually lossless compression will not be achieved at a significantly lower rate than the lossless rate.

0.2.3 Halftone coding

Halftone coding is the natural way to obtain very high compression for *periodic* halftones, such as clustered-dot ordered dithered images. In contrast to lossy generic coding as described above, halftone coding does not intend to preserve the original bitmap, although this is possible in special cases. Loss can also be introduced for additional compression by not putting all the patterns of the original image into the dictionary, thereby reducing both the number of halftone patterns and the number of bits required to specify which pattern is used in which location.

For lossy coding of error diffused images and images dithered with blue noise it is advisable to use halftone coding with a small grid size. A reconstructed image will lack fine details and may display blockiness but will be clearly recognizable. The blockiness may be reduced on the decoder side in a postprocess; for instance, by using other reconstruction patterns than those that appear in the dictionary. Error diffused images may also be coded losslessly, or with controlled loss as described above, using generic coding.

More details on performing this halftone coding can be found in [12].

0.2.4 Consequences of inadequate segmentation

In order to obtain optimum coding, both in terms of quality and file size, the correct form of encoding should be used for the appropriate regions of the document pages. This subclause briefly describes the consequences of errors in this segmentation.

Using lossy symbol coding for a document containing both text and halftone data will result in poor compression. Depending on the encoder, the quality of the halftone data may be good or bad. Using the form of lossy symbol coding described in [5] the visual quality will probably not suffer.

Using lossy generic coding (using the preprocesses given in [11]) for a document containing both symbol and halftone data usually results in good quality and moderate compression.

Line art and regions of handwritten text may be coded efficiently using generic coding, but depending on the encoder, these types of regions can also be very effectively coded with symbol coding.

1 Scope

This Recommendation | International Standard defines methods for coding bi-level images and sets of images (documents consisting of multiple pages). It is particularly suitable for bi-level images consisting of text and dithered (halftone) data.

The methods defined permit lossless (bit-preserving) coding, lossy coding, and progressive coding. In progressive coding, the first image is lossy; subsequent images may be lossy or lossless.

This Recommendation | International Standard also defines file formats to enclose the coded bi-level image data.

2 Normative References

The following ITU-T Recommendations and International Standards contain provisions which, through references in this text, constitute provisions of this Recommendation | International Standard. At the time of publication, the editions indicated were valid. All Recommendations and Standards are subject to revision, and parties to agreements based on this Recommendation | International Standard are encouraged to investigate the possibility of applying the most recent editions of the Recommendations and Standards listed below. Members of IEC and ISO maintain registers of currently valid International Standards. The ITU-T Telecommunication Standardization Bureau (TSB) maintains a list of the currently valid ITU-T Recommendations.

- ISO/IEC 8859-1:1987 to ISO 8859-10:1992, Information processing — 8-bit single byte coded graphic character sets
- ISO/IEC 10646-1:1993, Information technology — Universal multiple-octet coded character set (UCS) — Architecture and basic multilingual plane
- ITU-T T.6 (1988), Facsimile coding schemes and coding control functions for group 4 facsimile apparatus — Terminal Equipment and Protocols for Telematic Services (Study Group XIII)

3 Terms and Definitions

For the purposes of this Recommendation | International Standard, the terms and definitions given in the following apply.

3.1

Adaptive template pixel(s)

A special pixel(s), in a template, whose location is not fixed

3.2

Aggregation

A joining or merging of several individual symbols into a new symbol

3.3

Bi-level image

A rectangular array of bits

3.4

Bit

A binary digit, representing the value **0** or **1**

3.5

Bitmap

A bi-level image

3.6

Buffer

A storage area used to hold a bitmap

3.7

Byte

Eight bits of data

3.8

Combination operator

An operator used to combine the prior contents of a bitmap with new values being drawn into that bitmap

3.9

Coordinate system

A numbering system for two-dimensional locations where locations are labelled by two numbers, the first one increasing from left to right and the second one increasing from top to bottom.

3.10

Delta S

The difference in the S coordinates between two successive symbol instances in a non-empty strip

3.11

Delta T

The difference in the T coordinates between two successive non-empty strips

3.12

Decoding procedure

A component of a decoder that decodes a certain type of data

3.12.1

Integer decoding procedure

A decoding procedure whose output on each invocation is a single value

3.12.2

Arithmetic integer decoding procedure

An integer decoding procedure that uses arithmetic entropy decoding

3.12.3

Region decoding procedure

A decoding procedure whose output is a bitmap

3.12.4

Generic region decoding procedure

A region decoding procedure that operates by decoding pixels individually or in runs

3.12.5

Generic refinement region decoding procedure

A region decoding procedure that operates by modifying a reference bitmap to produce an output bitmap

3.12.6

Gray-scale decoding procedure

A decoding procedure whose output is a gray-scale image

3.12.7

Pattern dictionary decoding procedure

A decoding procedure whose output is a list of patterns

3.12.8

Halftone region decoding procedure

A region decoding procedure that operates by drawing a set of patterns into a bitmap, placing the patterns according to a halftone grid

3.12.9

Huffman table decoding procedure

A decoding procedure whose output is a Huffman table

3.12.10

Text region decoding procedure

A region decoding procedure that operates by drawing a set of symbol instances into a bitmap

3.12.11

Symbol dictionary decoding procedure

A decoding procedure whose output is a list of symbols

3.13

Decoder

An entity capable of decoding a bitstream in conformance with this Recommendation | International Standard

3.14

Dictionary

A list of bitmaps

3.14.1

Pattern dictionary

A list of patterns

3.14.2

Symbol dictionary

A list of symbols

3.15

Export flag

A bit indicating that a symbol is on the export list of a symbol dictionary

3.16

Export list

A list of the symbols in a symbol dictionary that may be used by referring to that symbol dictionary

3.17

Gray-scale image

A rectangular array of non-negative integer indices

3.18

Gray-scale pixel

An integer-valued element in a gray-scale image

3.19

Halftone grid

A rectilinear grid of locations specifying where patterns are to be drawn

3.20

Height class

A set of symbols in a symbol dictionary whose heights are all equal

3.21

Height class delta height

The difference in height between two height classes

3.22

Height class delta width

The difference in width between two symbols in a height class

3.23

Huffman table

A collection of table lines specifying how values are encoded

3.24

Lossless coding

A method of encoding data so that the decoded data are identical to the original data

3.25

Lossy coding

A method of encoding data so that the decoded data differ, ideally only in insignificant ways, from the original data

3.26

Ordinal

A value used as a counter

3.27

Out-of-band value

A non-numeric value that may be produced in place of an integer

3.28

Pattern

A bitmap produced by a pattern dictionary decoding procedure

3.29

Pixel

An element with **0** or **1** as its value in a bitmap

3.30

Prefix length

The length of the Huffman code prefix in a table line

3.31

Range length

The number of additional code bits in a table line

3.32

Reference bitmap

The bitmap used as the reference plane during the refinement region decoding procedure

3.33

Referred-to segment

Another segment required in order to decode the current segment

3.34

Region

A bitmap produced by a region decoding procedure

3.35

Segment

A segment header and its segment data

3.36

Strip

A full-width or full-height portion of the coordinate system of a text region

3.36.1

Empty strip

A strip containing the reference corners of no symbol instances

3.36.2

Non-empty strip

A strip containing the reference corner of at least one symbol instance

3.37

Strip size

The extent in pixels of the non-full dimension of a strip

3.38

Symbol

A bitmap produced by a symbol dictionary decoding procedure

3.39

Symbol ID

An integer used to identify a symbol or to index into an array of symbols to retrieve the symbol

3.40

Symbol instance

A symbol drawn, possibly with refinement, at a particular location in a text region

3.41

Symbol instance refinement delta height

The difference in height between a symbol instance's reference bitmap and the bitmap produced by the generic refinement region decoding procedure

3.42

Symbol instance refinement delta width

The difference in width between a symbol instance's reference bitmap and the bitmap produced by the generic refinement region decoding procedure

3.43

Symbol instance refinement delta X

The difference between the X coordinates of the top left corners of a symbol instance's reference bitmap and the bitmap produced by the generic refinement region decoding procedure

3.44

Symbol instance refinement delta Y

The difference between the Y coordinates of the top left corners of a symbol instance's reference bitmap and the bitmap produced by the generic refinement region decoding procedure

3.45

Table line

A specification of the encoding of a single value or a range of values as a Huffman code prefix followed by a fixed number of additional code bits

3.46

Typical prediction

Typical prediction signals that an entire row of a generic region is identical to the preceding row

3.47

Value

An integer or out-of-band indicator that is decoded

4 Symbols and Abbreviations

NOTE — Due to ISO nomenclature requirements, within the context of Clause 4, the term “symbol” is locally used to mean a variable name.

4.1 Abbreviations

The abbreviations used in this Recommendation | International Standard are listed below.

AT	Adaptive template
EOFB	End of Facsimile Block
ID	Identifier
LPS	Less probable symbol, i.e., less probable binary value
LSB	Least significant bit
MMR	Modified modified READ
MPS	More probable symbol, i.e., more probable binary value
MSB	Most significant bit
OOB	Out-of-band
READ	Relative Element Address Designate
TPGD	Typical prediction for generic direct bitmap coding
TPGR	Typical prediction for generic refinement bitmap coding

NOTE — The term “symbol” in the abbreviations LPS and MPS does not refer to the symbols (bitmaps) in this Recommendation | International Standard. The LPS and MPS abbreviations are used despite this because they are the generally-accepted terminology in arithmetic coding.

4.2 Symbol definitions

The following symbols used in this Recommendation | International Standard are listed below. A convention is used that parameters to any of the decoding procedures that are used in this Recommendation | International Standard are indicated in **bold face**.

A	Probability interval
<i>a</i>	A real number
ARR	An array
A_1, A_2, A_3, A_4	Adaptive template pixels in the generic region decoding procedure
B	Current byte of arithmetically-coded data
B1	Byte of arithmetically-coded data following the current byte
B_{HC}	A height class collective bitmap in a symbol dictionary decoding procedure
B_{HDC}	A dictionary collective bitmap in a pattern dictionary decoding procedure
B_P	A pattern bitmap in a pattern dictionary decoding procedure
B_S	A symbol bitmap in a symbol dictionary decoding procedure
BM	A bitmap
BP	Pointer to byte B
BPST	Initial value of BP
C	Value of bit stream in code register
Chigh	High-order 16 bits of C
Clow	Low-order 16 bits of C
CONTEXT	The values of the pixels in a template used in the generic or generic refinement decoding procedure
CT	Renormalisation shift counter

CURCODE	The Huffman code for the current table line in a Huffman table
CUREXFLAG	The current export flag.
CURLEN	The current table line prefix length in a Huffman table
CURRANGELOW	The lower bound of the range of the current table line in a Huffman table
CURS	The current S coordinate in a text region decoding procedure
CURT	The current symbol instance's T coordinate relative to the current strip's T coordinate in a text region decoding procedure
CX	A label identifying an arithmetic coding context
D	Arithmetic coding decision
DFS	The difference in S coordinates between the first instances of two strips
DT	The number of empty strips between two non-empty strips
DW	The difference in width between two symbol bitmaps in a symbol dictionary decoding procedure
EXFLAGS	An array of export flags
EXINDEX	An index for the array EXFLAGS
EXRUNLENGTH	The length of a run of identical export flag values
FIRSTS	The first S coordinate of the current strip
FIRSTCODE	The first code assigned to a particular prefix length in a Huffman table
GBATX₁	The X location of adaptive template pixel 1 in a generic region decoding procedure
GBATY₁	The Y location of adaptive template pixel 1 in a generic region decoding procedure
GBATX₂	The X location of adaptive template pixel 2 in a generic region decoding procedure
GBATY₂	The Y location of adaptive template pixel 2 in a generic region decoding procedure
GBATX₃	The X location of adaptive template pixel 3 in a generic region decoding procedure
GBATY₃	The Y location of adaptive template pixel 3 in a generic region decoding procedure
GBATX₄	The X location of adaptive template pixel 4 in a generic region decoding procedure
GBATY₄	The Y location of adaptive template pixel 4 in a generic region decoding procedure
GB	The prefix used for many of the variables associated with a generic (bitmap) region decoding procedure
GBH	The height of a generic region
GBREG	The region produced by a generic region decoding procedure
GBTEMPLATE	A parameter indicating the number and arrangement of the pixels in a template used in a generic region decoding procedure
GBW	The width of a generic region
GI	An array of gray-scale values
GR	The prefix used for many of the variables associated with a generic refinement region decoding procedure
GRATX₁	The X location of adaptive template pixel 1 in a generic refinement region decoding procedure
GRATY₁	The Y location of adaptive template pixel 1 in a generic refinement region decoding procedure
GRATX₂	The X location of adaptive template pixel 2 in a generic refinement region decoding procedure

GRATY₂	The Y location of adaptive template pixel 2 in a generic refinement region decoding procedure
GRAY	The current gray-scale value
GRAYMAX	The largest gray-scale value for which a pattern is given in a pattern dictionary decoding procedure
GRH	The height of a generic region being coded with refinement coding
GRREFERENCE	The reference bitmap in a generic refinement region decoding procedure
GRREFERENCEDX	The X offset of the reference bitmap with respect to the bitmap being decoded in a generic refinement region decoding procedure
GRREFERENCEDY	The Y offset of the reference bitmap with respect to the bitmap being decoded in a generic refinement region decoding procedure
GRREG	The region produced by a generic refinement region decoding procedure
GRTEMPLATE	A parameter indicating the number and arrangement of the pixels in a template used in decoding a generic region with refinement coding
GRW	The width of a generic region being coded with refinement coding
GS	The prefix used for many of the variables associated with a gray-scale image decoding procedure
GSBPP	The number of bits per gray-scale value in a gray-scale image decoding procedure
GSH	The height of the gray-scale image in a gray-scale image decoding procedure
GSKIP	A mask indicating gray-scale values to be skipped
GSMR	Whether MMR is used in a gray-scale image decoding procedure
GSTEMPLATE	A parameter indicating the number and arrangement of the pixels in a template used in a gray-scale image decoding procedure
GSUSESKIP	Whether some gray-scale values should be skipped in a gray-scale image decoding procedure
GSVALS	A decoded gray-scale image
GSW	The width of the gray-scale image in a gray-scale image decoding procedure
HB	The prefix used for many of the variables associated with a halftone (bitmap) region decoding procedure
HBH	The height of a halftone region
HBP	The number of bits per value in an array of gray-scale values
HBW	The width of a halftone region
HCHEIGHT	The height of the current height class in a symbol dictionary decoding procedure
HCDH	The difference in height between two height classes in a symbol dictionary decoding procedure
HCFIRSTSYM	The index of the first symbol decoded in a height class
HCOMBOP	The combination operator used in a halftone region decoding procedure
HD	The prefix used for many of the variables associated with a pattern dictionary region decoding procedure
HDEFPIXEL	The default for pixels in a halftone region
HDMMR	Whether MMR is used in a pattern dictionary decoding procedure
HDPATS	Array of patterns produced by a pattern dictionary decoding procedure
HDPH	The height of the patterns in a pattern dictionary
HDPW	The width of the patterns in a pattern dictionary

HDTEMPLATE	The template identifier used to decode patterns in a pattern dictionary decoding procedure
HENABLESKIP	Whether unneeded gray-scale values are skipped in a halftone region decoding procedure
HGH	The height of the gray-scale image in a halftone region decoding procedure
HGW	The width of the gray-scale image in a halftone region decoding procedure
HGX	The horizontal offset of the grid in a halftone region decoding procedure
HGY	The vertical offset of the grid in a halftone region decoding procedure
H_I	The height of a symbol instance bitmap
HIGHPREFLEN	The prefix length of the upper range table line in a Huffman table
HMMR	Whether MMR coding is used in a halftone region decoding procedure
HNUMPATS	The number of patterns that may be used in a halftone region decoding procedure
HO_I	The height of the original bitmap of a symbol instance containing refinement information
HPATS	Array of patterns used in a halftone region
HPH	The height of each pattern in a halftone region
HPW	The width of each pattern in a halftone region
HRX	The horizontal coordinate of a halftone grid vector
HRY	The vertical coordinate of a halftone grid vector
HSKIP	A mask indicating gray-scale values to be skipped
HT	The prefix used for many of the variables associated with a Huffman table decoding procedure
HTEMPLATE	A parameter indicating the number and arrangement of the pixels in a template used in a halftone region decoding procedure
HTHIGH	One greater than the largest value that is represented by any normal table line in a Huffman table
HTLOW	The lowest value that is represented by any normal table line in a Huffman table
HTOFFSET	The range offset of a table line when decoding using a Huffman table
HTOOB	Whether a Huffman table can produce the out-of-band value OOB
HTPS	The length of the encoded prefix field in a table line in a Huffman table
HTREG	The region produced by a halftone region decoding procedure
HTRS	The length of the encoded range field in a table line in a Huffman table
HTVAL	The value decoded using a Huffman table
I	The array, indexed by CX, of the indices of the adaptive probability estimates
I	An array index
IAAI	An arithmetic integer decoding procedure used to decode the number of symbol instances in an aggregation
IADH	An arithmetic integer decoding procedure used to decode the difference in height between two height classes
IADS	An arithmetic integer decoding procedure used to decode the S coordinate of the second and subsequent symbol instances in a strip
IADT	An arithmetic integer decoding procedure used to decode the T coordinate of the second and subsequent symbol instances in a strip
IADW	An arithmetic integer decoding procedure used to decode the difference in width between two symbols in a height class
IAEX	An arithmetic integer decoding procedure used to decode export flags

IAFS	An arithmetic integer decoding procedure used to decode the S coordinate of the first symbol instance in a strip
IAID	An arithmetic integer decoding procedure used to decode the symbol IDs of symbol instances
IARDH	An arithmetic integer decoding procedure used to decode the delta height of symbol instance refinements
IARDW	An arithmetic integer decoding procedure used to decode the delta width of symbol instance refinements
IARDX	An arithmetic integer decoding procedure used to decode the delta X values of symbol instance refinements
IARDY	An arithmetic integer decoding procedure used to decode the delta Y values of symbol instance refinements
IARI	An arithmetic integer decoding procedure used to decode the R_I bit of symbol instances
IAIT	An arithmetic integer decoding procedure used to decode the T coordinate of the symbol instances in a strip
IB_I	The bitmap of a symbol instance
IBO_I	The original bitmap of a symbol instance containing refinement information
ID_I	The symbol ID of a symbol instance
IDS	The delta S value for a symbol instance in a text region decoding procedure
J	An array index
K	The ordinal for a referred-to segment
LENCOUNT	A histogram of the prefix lengths in a Huffman table
LENMAX	The largest prefix length in a Huffman table
LOGSBSTRIPS	The base-2 logarithm of the strip size used to encode a text region
LOWPREFLEN	The prefix length of the lower range table line in a Huffman table
LTP	Whether the current line is coded explicitly in a generic region decoding procedure or a generic refinement region decoding procedure
m_g	Horizontal index for the current gray-scale value
MMR	Whether MMR coding is used in a generic region decoding procedure
MPS	The array, indexed by CX, of the current more probable binary values
NINSTANCES	A symbol instance counter
n_g	Vertical index for the current gray-scale value
NLPS	The next index for an LPS renormalisation
NMPS	The next index for an MPS renormalisation
NSYMSDECODED	The number of symbols decoded so far in a symbol dictionary decoding procedure
NTEMP	The number of table lines in a Huffman table
OOB	An out-of-band value
P	The page with which a segment is associated
PREFLEN	An array of prefix lengths representing the table lines in a Huffman table
Q_e	An estimate of the LPS probability
r	A segment retention flag
R	The number of segments referred to by some segment
RANGELEN	An array of the lengths of the ranges of the table lines in a Huffman table

RANGELOW	An array of the lower bounds of the ranges of the table lines in a Huffman table
RA_1, RA_2	Adaptive template pixels in the generic refinement region decoding procedure
RDH_I	The delta height of a symbol instance refinement bitmap
RDW_I	The delta width of a symbol instance refinement bitmap
RDX_I	The X offset of a symbol instance refinement
RDY_I	The Y offset of a symbol instance refinement
REFAGGNINST	The number of symbol instances in an aggregation
R_I	A bit indicating whether refinement information is present for a symbol instance
REFCORNER	Which corner of a symbol instance bitmap is to be used as a reference in a text region decoding procedure
S	One coordinate of the coordinate system used in a text region decoding procedure
S_I	The S coordinate of a symbol instance
SB	The prefix used for many of the variables associated with a symbol (bitmap) region decoding procedure
SBDSOFFSET	An offset for the coded delta S values in a text region
SBCOMBOP	The combination operator used in a text region decoding procedure
SBDEFPIXEL	The default for pixels in a text region
SBH	The height of a text region
SBHUFF	Whether Huffman coding is used in a text region decoding procedure
SBHUFFDS	The Huffman table used to decode the S coordinate of subsequent symbol instances in a strip
SBHUFFDT	The Huffman table used to decode the difference in T coordinates between non-empty strips
SBHUFFFS	The Huffman table used to decode the S coordinate of the first symbol instance in a strip
SBHUFFRDH	The Huffman table used to decode the difference between a symbol's height and the height of a refinement coded symbol instance bitmap
SBHUFFRDW	The Huffman table used to decode the difference between a symbol's width and the width of a refinement coded symbol instance bitmap
SBHUFFRDY	The Huffman table used to decode the difference between a symbol instance's X coordinate and the X coordinate of a refinement coded bitmap
SBHUFFRDX	The Huffman table used to decode the difference between a symbol instance's Y coordinate and the Y coordinate of a refinement coded symbol instance bitmap
SBHUFFRDY	The Huffman table used to decode the difference between a symbol instance's Y coordinate and the Y coordinate of a refinement coded symbol instance bitmap
SBHUFFRSIZE	The Huffman table used to decode the size of a symbol instance's refinement bitmap data
SBNUMINSTANCES	The number of symbol instances in a text region
SBNUMSYMS	The number of symbols that may be used in a text region
SBRATX₁	The X location of the adaptive template pixel RA_1 in a text region decoding procedure
SBRATY₁	The Y location of the adaptive template pixel RA_1 in a text region decoding procedure
SBRATX₂	The X location of the adaptive template pixel RA_2 in a text region decoding procedure
SBRATY₂	The Y location of the adaptive template pixel RA_2 in a text region decoding procedure
SBREFINE	Whether refinement coding is used in a text region decoding procedure
SBREG	The region produced by a text region decoding procedure
SBRTEMPLATE	Template identifier for refinement coding of bitmap in a text region decoding procedure
SBSTRIPS	The height of the symbol instance strips

SBSYMCODES	An array of variable-length codes identifying individual symbols
SBSYMS	An array of symbols used in a text region
SBW	The width of a text region
SD	The prefix used for many of the variables associated with a symbol dictionary region decoding procedure
SDATX₁	The X location of the adaptive template pixel A ₁ in a symbol dictionary decoding procedure
SDATY₁	The Y location of the adaptive template pixel A ₁ in a symbol dictionary decoding procedure
SDATX₂	The X location of the adaptive template pixel A ₂ in a symbol dictionary decoding procedure
SDATY₂	The Y location of the adaptive template pixel A ₂ in a symbol dictionary decoding procedure
SDATX₃	The X location of the adaptive template pixel A ₃ in a symbol dictionary decoding procedure
SDATY₃	The Y location of the adaptive template pixel A ₃ in a symbol dictionary decoding procedure
SDATX₄	The X location of the adaptive template pixel A ₄ in a symbol dictionary decoding procedure
SDATY₄	The Y location of the adaptive template pixel A ₄ in a symbol dictionary decoding procedure
SDEXSyms	The symbols exported from a symbol dictionary
SDHUFF	Whether Huffman coding is used in a symbol dictionary decoding procedure
SDHUFFAGGINST	The Huffman table used to decode the number of symbol instances in an aggregation in a symbol dictionary decoding procedure
SDHUFFDH	The Huffman table used to decode the difference in height between two height classes in a symbol dictionary decoding procedure
SDHUFFDW	The Huffman table used to decode the difference in width between two symbols in a symbol dictionary decoding procedure
SDHUFFBMSIZE	The Huffman table used to decode the size of a height class collective bitmap in a symbol dictionary decoding procedure
SDINSYMS	An array of symbols used as a parameter to a symbol dictionary decoding procedure
SDNEWSYMS	The symbols decoded in a symbol dictionary
SDNEWSYMWIDTHS	The widths of the symbols decoded in a symbol dictionary
SDNUMEXSYMS	The number of symbols exported from a symbol dictionary
SDNUMINSYMS	The number of symbols in the array that is used as a parameter to a symbol dictionary decoding procedure
SDNUMNEWSYMS	The number of symbols generated in a symbol dictionary
SDREFAGG	Whether refinement and aggregate coding are used in a symbol dictionary decoding procedure
SDRATX₁	The X location of the adaptive template pixel RA ₁ in a symbol dictionary decoding procedure
SDRATY₁	The Y location of the adaptive template pixel RA ₁ in a symbol dictionary decoding procedure
SDRATX₂	The X location of the adaptive template pixel RA ₂ in a symbol dictionary decoding procedure

SDRATY₂	The Y location of the adaptive template pixel RA ₂ in a symbol dictionary decoding procedure
SDRTEMPLATE	Template identifier for refinement coding of bitmaps in a symbol dictionary decoding procedure
SDTEMPLATE	The template identifier used to decode symbol bitmaps in a symbol dictionary decoding procedure
SKIP	A mask of pixels to be skipped during the decoding of a generic region
SLTP	A binary value indicating whether the current line was typically predicted and the previous line was not, or vice versa
STRIPT	The numerically smallest T coordinate in the current strip
SWITCH	Whether MPS and LPS are switched on an LPS renormalisation
SYMWIDTH	The current bitmap width in a symbol dictionary decoding procedure.
T	One coordinate of the coordinate system used in a text region decoding procedure
TEMPC	A temporary register in the MQ coder
T_I	The T coordinate of a symbol instance
TOTWIDTH	The total width of the bitmaps in a height class
TPGDON	Whether typical prediction is used in a generic region decoding procedure
TPGRON	Whether typical prediction is used in a generic region refinement decoding procedure
TPGRPIX	Whether the current pixel is to be decoded implicitly using a TPGR prediction
TPGRVAL	The value of the TPGR-predicted current pixel
TRANSPOSED	Whether the symbol instance coordinates are transposed in a text region decoding procedure
USESKEEP	Whether some pixels should be skipped in the decoding of a generic region
V1	A binary value
V2	A binary value
W_I	The width of a symbol instance bitmap
WO_I	The width of the original bitmap of a symbol instance containing refinement information
x	The horizontal coordinate of a location on a halftone grid
X	The horizontal coordinate of a pixel in a bitmap
y	The vertical coordinate of a location on a halftone grid
Y	The vertical coordinate of a pixel in a bitmap

4.3 Operator definitions

The following operators are defined

OR	If V1 and V2 are two binary values, then V1 OR V2 is equal to 0 if both V1 and V2 are 0 . It is equal to 1 if either of V1 or V2 is 1 . If V1 and V2 are two integer values, then it is the result of bitwise application of OR.
AND	If V1 and V2 are two binary values, then V1 AND V2 is equal to 0 if either of V1 or V2 is 0 . It is equal to 1 if both V1 and V2 are 1 . If V1 and V2 are two integer values, then it is the result of bitwise application of AND.
XOR	If V1 and V2 are two binary values, then V1 XOR V2 is equal to 0 if V1 and V2 are equal. It is equal to 1 if V1 and V2 differ. If V1 and V2 are two integer values, then it is the result of bitwise application of XOR.

XNOR	If V1 and V2 are two binary values, then V1 XNOR V2 is equal to 0 if V1 and V2 differ. It is equal to 1 if V1 and V2 are equal.
REPLACE	If V1 and V2 are two binary values, then V1 REPLACE V2 is equal to V2.
NOT	If V1 is a binary value, then NOT V1 is 1 if V1 is 0 , and is 0 if V1 is 1 .
min	If x and y are numbers, then $\min(x, y)$ is the smaller of x and y .
max	If x and y are numbers, then $\max(x, y)$ is the larger of x and y .
$\lfloor \rfloor$	If a is a number, then $\lfloor a \rfloor$ is the largest integer less than or equal to a .
$\lceil \rceil$	If a is a number, then $\lceil a \rceil$ is the smallest integer greater than or equal to a .
<<	If V1 and V2 are two integers, then V1 << V2 is the value obtained by shifting the value of V1 leftwards by V2 bits, filling the rightmost V2 bits of the new value with 0 .
>>	If V1 and V2 are two integers, then V1 >> V2 is the value obtained by shifting the value of V1 rightward by V2 bits, filling the leftmost V2 bits of the new value with 0 .
>> _A	If V1 and V2 are two integers, then V1 >> _A V2 is the value obtained by shifting the value of V1 rightward by V2 bits, filling the leftmost V2 bits of the new value with 0 if V1 is non-negative and 1 if V1 is negative.

5 Conventions

5.1 Typographic conventions

All parameter names are given in **bold face**.

5.2 Binary notation

The two binary values are denoted as **0** and **1**.

5.3 Hexadecimal notation

The prefix `0x` indicates that the following value is to be interpreted as a hexadecimal number (radix 16).

EXAMPLE — The value `0x6A` is equal to the decimal value 106.

5.4 Integer value syntax

5.4.1 Bit packing

Bits are packed into bytes starting at the most significant bit. If a decoder is reading a sequence of bits out of a bitstream, it shall first read the most significant bit of the first byte, then the next most significant bit, and so on, then proceed to the next byte.

EXAMPLE — The sequence of bytes `0x2F 0x05 0xC1`, if interpreted as a sequence of bits, is the sequence

001011110000010111000001

5.4.2 Multi-byte values

All multi-byte values shall be interpreted in a most-significant-first manner: the first byte of each value is the most significant, and the last byte is the least significant.

EXAMPLE — The sequence of bytes `0x01 0x5C 0x99 0xFA`, if interpreted as a four-byte value, represents the value `0x015C99FA`.

5.4.3 Bit numbering

The least significant bit of any value is numbered bit 0. For a one-byte value, the most significant bit is numbered bit 7; for a two-byte value, the most significant bit is numbered bit 15; for a four-byte value, the most significant bit is numbered bit 31.

5.4.4 Signedness

Unless otherwise specified, all multi-bit values shall be treated as unsigned values. When a value is to be treated as a signed number, it shall be interpreted in two's-complement form.

5.5 Array notation and conventions

Arrays are numbered starting from zero.

EXAMPLE — A one-dimensional array `ARR` containing twelve elements has elements

`ARR[0], ARR[1], . . . , ARR[11]`

5.6 Image and bitmap conventions

A bitmap is a rectangular array. Every element in this array has the value **0** or **1**. An element in a bitmap is referred to as a pixel.

NOTE 1 — Throughout this Recommendation | International Standard, pixels in bitmaps are treated as having the values **0** or **1**. In most applications of this Recommendation | International Standard, the application will select some interpretation of these two values. A typical interpretation of these pixels is that **0** represents white, or background, and **1** represents black, or foreground. However, this is not a requirement of this Recommendation | International Standard and applications are free to make other interpretations of these values.

The terms “left”, “right”, “top”, “bottom”, “width” and “height” are often applied to bitmaps. These terms do not refer to any physical aspect of the bitmap: if a bitmap is printed on paper, it may be printed with its “left” edge along any edge of the paper. They are used within this Recommendation | International Standard to refer to the four edges of the bitmap as shown in Figure 2.




Figure 2 — The four edges of a bitmap

A pixel in a bitmap is referred to by a pair of coordinates X and Y , sometimes written as a pair (X, Y) . The location $(0, 0)$ represents the pixel in the top left corner. The X coordinate increases rightwards and the Y coordinate increases downwards.

If BM is a bitmap, then the pixel whose coordinates are X and Y is referred to as $BM[X, Y]$.

NOTE 2 — These conventions are intended to make it easier to describe operations involving bitmaps, and are not intended to imply any physical characteristics of the image represented by the bitmap.

6 Decoding Procedures

6.1 Introduction to decoding procedures

This Recommendation | International Standard makes use of a number of different decoding procedures for different types of data. Each of these decoding procedures produces a certain kind of data as output. The generic region decoding procedure, generic refinement region decoding procedure, halftone region decoding procedure, and text region decoding procedures all produce regions as their output. The symbol dictionary decoding procedure produces an array of symbols as its output. The pattern dictionary decoding procedure similarly produces an array of halftone cell bitmaps as its output.

The various region decoding procedures operate in different manners:

- The generic region decoding procedure decodes a bitmap, treating it simply as an array of binary pixels.
- The generic region refinement decoding procedure decodes a bitmap by treating it as an array of binary pixels, but coding each pixel with respect to some reference bitmap.
- The text region decoding procedure decodes a bitmap by drawing a collection of symbols into it, possibly applying the generic refinement region decoding procedure to each one.
- The halftone region decoding procedure decodes a bitmap by placing a collection of patterns into it, at locations specified by a halftone grid.

Each decoding procedure is specified in terms of a number of parameters and a sequence of operations, which are affected by the values of the parameters. These parameters are supplied to the decoding procedure for each invocation, and the same decoding procedure may be invoked multiple times during the course of decoding a bitstream, with different parameters each time.

Some of the decoding procedure parameters are unused in certain circumstances, usually depending on the values of other parameters. In these circumstances, no value needs to be specified for those unused parameters.

In this clause, subsequent clauses, and normative annexes, restrictions are placed on the bitstream being decoded.

EXAMPLE 1 — In 7.3, some segment types are described as “Reserved; must not be used.”

EXAMPLE 2 — In 7.4.2.1.1, if the **SDHUFF** field is **0** then the **SDHUFFDH** field must contain the value 0.

These restrictions should be interpreted as meaning that the behaviour of a decoder encountering a bitstream that does not satisfy the restrictions is undefined, and is outside the scope of this Recommendation | International Standard.

NOTE — This means that if a decoder encounters a bitstream that does not satisfy the restrictions, it may take any action: it may give up and abort decoding; it may ignore the error and attempt to continue; it may interpret the error and change its behaviour (e.g., use the error to attempt to aid recovery from further errors); and so on.

6.2 Generic Region Decoding Procedure

6.2.1 General description

This decoding procedure is used to decode a rectangular array of **0** or **1** values, which are coded one pixel at a time (i.e., it is used to decode a bitmap using simple, generic, coding). The decoding procedure also modifies an array of probability information which may be used by other invocations of this generic region decoding procedure.

The generic region decoding procedure may be based on sequential coding of the image pixels using arithmetic coding as specified in Annex E and a template to determine the coding state. This technique was used in ITU-T Recommendation T.82 | ISO/IEC 11544 (JBIG). This type of decoding is described in 6.2.5.

Alternatively, for improved speed but reduced compression the generic region decoding procedure may be based on Huffman coding of runs of pixels. This technique was used in the MMR (Modified Modified READ) algorithm described in ITU-T Recommendation T.6 (G4). This type of decoding is described in 6.2.6.

6.2.2 Input parameters

The parameters to this decoding procedure are shown in Table 2.

Table 2 — Parameters for the generic region decoding procedure.

Name	Type	Size (bits)	Signed?	Description and restrictions
MMR	Integer	1	N	Whether MMR coding is used.
GBW	Integer	32	N	The width of the region.
GBH	Integer	32	N	The height of the region.
GBTEMPLATE	Integer	2	N	The template identifier. *
TPGDON	Integer	1	N	Whether typical prediction is used. *
USESKEEP	Integer	1	N	Whether some pixels should be skipped in the decoding. *
SKIP	Bitmap			A bitmap indicating which pixels should be skipped. GBW pixels wide, GBH pixels high. ***
GBATX₁	Integer	8	Y	The X location of the adaptive template pixel A ₁ . *
GBATY₁	Integer	8	Y	The Y location of the adaptive template pixel A ₁ . *
GBATX₂	Integer	8	Y	The X location of the adaptive template pixel A ₂ . **
GBATY₂	Integer	8	Y	The Y location of the adaptive template pixel A ₂ . **
GBATX₃	Integer	8	Y	The X location of the adaptive template pixel A ₃ . **
GBATY₃	Integer	8	Y	The Y location of the adaptive template pixel A ₃ . **
GBATX₄	Integer	8	Y	The X location of the adaptive template pixel A ₄ . **
GBATY₄	Integer	8	Y	The Y location of the adaptive template pixel A ₄ . **

* Unused if **MMR** = 1

** Unused if **MMR** = 1 or **GBTEMPLATE** ≠ 0

*** Unused if **USESKEEP** = 0 or **MMR** = 1

6.2.3 Return value

The variable whose value is the result of this decoding procedure is shown in Table 3.

Table 3 — Return value from the generic region decoding procedure.

Name	Type	Size (bits)	Signed?	Description and restrictions
GBREG	Bitmap			The decoded region bitmap.

6.2.4 Variables used in decoding

The variables used by this decoding procedure are shown in Table 4.

6.2.5 Decoding using a template and arithmetic coding

6.2.5.1 General description

If **MMR** is 0 the generic region decoding procedure is based on arithmetic coding with a template to determine the coding state. The remainder of 6.2.5 describes this form of decoding, and only applies when **MMR** is 0.

6.2.5.2 Coding order and edge conventions

The coding algorithm iterates through the bitmap in raster scan order, that is, by rows from top to bottom, and within each row from left to right. The processing for a current target pixel will reference some pixels in fixed spatial relationship to the target pixel.

Near the edges of the bitmap, these neighbour references might not lie in the actual bitmap. The rule to satisfy out-of-bounds references shall be:

Table 4 — Variables used in the generic region decoding procedure.

Name	Type	Size (bits)	Signed?	Description and restrictions
LTP	Integer	1	N	Whether the current image line is coded explicitly *
SLTP	Integer	1	N	Whether the current line's LTP value differs from the previous line's LTP value *
CONTEXT	Integer	16	N	The values of the pixels in the template *

* Unused if **MMR** = 1

- All pixels lying outside the bounds of the actual bitmap have the value 0.

6.2.5.3 Fixed templates

A template defines a neighborhood around a pixel to be coded. The values of the pixels in this neighborhood define a context. Each context has its own adaptive probability estimate used by the arithmetic coder (see Annex E). Although a template is a geometric pattern of pixels, the pixels in a template are said to take on values when the template is aligned with a particular part of the image.




Figure 3 — Template when GBTEMPLATE=0, showing the AT pixels at their nominal locations.




Figure 4 — Template when GBTEMPLATE=1, showing the AT pixel at its nominal location.

Figure 3 shows the template which shall be used when **GBTEMPLATE** is 0. Figure 4 shows the template which shall be used when **GBTEMPLATE** is 1. Figure 5 shows the template which shall be used when **GBTEMPLATE** is 2. Figure 6 shows the template which shall be used when **GBTEMPLATE** is 3. In each of these figures, the pixel denoted by a circle corresponds to the pixel to be coded and is not part of the template. The pixels denoted by 'X' correspond to ordinary pixels in the template. The pixels denoted A_1 – A_4 are special pixels in the template. They are denoted “adaptive” or AT pixels. These pixels are special in that their locations are not fixed, but can be placed at different locations. See 6.2.5.4 for a description of AT pixels. The legends A_1 – A_4 indicate the AT pixels 1 to 4. The pixels' actual locations are specified as parameters to this decoding procedure; Figures 3–6 show the nominal locations of these AT pixels for each template.

The values of the pixels in the template shall be combined to form a context. Each pixel in the template (including the adaptive pixels) shall correspond to a specific bit in the context, although the pixels in the template may be assigned to bits in the context in any order. Because there are up to 16 pixels in the template, contexts can take on up to 65536 different values. This context shall be used to identify which adaptive probability estimate shall be used by the arithmetic coder for encoding the pixel to be coded (see Annex E).




Figure 5 — Template when GBTEMPLATE=2, showing the AT pixel at its nominal location.




Figure 6 — Template when GBTEMPLATE=3, showing the AT pixel at its nominal location.

NOTE 1 — A rule of thumb is to use large templates for large bitmaps. Thus a full-size periodic halftone should be coded with the 16-pixel template and tiny bitmaps such as usual symbol bitmaps should be coded with one of the 10-pixel templates. In some cases an intermediate template is desired, for performance or decoder memory requirements; in this case the 13-pixel template should be used. It is also possible to generate further templates by placing one or more of the AT pixels on top of a regular template pixel, thus fixing its value.

NOTE 2 — The 10-pixel templates are those used in ITU-T Recommendation T.82 | ISO/IEC 11544 (JBIG). Software execution speed is somewhat higher with the two-line template than any of the three-line templates. For most images the 10-pixel, three-line template gives higher compression than the 10-pixel, two-line template.

6.2.5.4 Adaptive template pixels

In coding the image, the template shall be allowed to change in the restricted way described in this clause.

The pixels that are allowed to change are called AT pixels. Their nominal locations are indicated by ‘A₁’, ‘A₂’, ‘A₃’, and ‘A₄’ in Figures 3, 4, 5 and 6. Note that some templates have fewer than four AT pixels. In general, an AT pixel can be located anywhere in the field shown in Figure 7, not including the current pixel. Hence, there is the possibility to use an effective template size of 15, 14, 13, 12 or 9 pixels by having the moved location of the AT pixel overlap a regular template pixel. The actual locations of the AT pixels for any invocation of this decoding procedure are specified as parameters to the decoding procedure. The location of the pixel A₁ is given by (GBATX₁, GBATY₁). If GBTEMPLATE is 0 then

- the location of the pixel A₂ is given by (GBATX₂, GBATY₂),
- the location of the pixel A₃ is given by (GBATX₃, GBATY₃),
- and the location of the pixel A₄ is given by (GBATX₄, GBATY₄).

NOTE 1 — Some profiles may restrict AT pixel locations to a smaller range than that shown in Figure 7.

NOTE 2 — The indices of the AT pixels in Figure 3 correspond to the expected goodness. If moving only one AT pixel from its nominal location, it is advisable to move A₄. The next pixel to move is A₃ and so on.




Figure 7 — Field to which AT pixel locations are restricted.

NOTE 3 — The nominal locations of the AT pixels are as shown in Table 5. These locations should be used unless other locations improve compression performance. Some profiles may restrict AT pixel locations to only these nominal locations.

NOTE 4 — If an AT pixel’s location overlaps any regular template pixel’s location, then the AT pixel’s value can be ignored (since it duplicates another value). This can reduce the memory requirements of the decoder, since not all CX values can occur. However, when TPGD is enabled (**TPGDON** = 1), the context used to code the SLTP pseudo-pixel is used, regardless of whether AT pixels overlap regular template pixels. This means that contexts where the AT pixel’s value differs from the regular template pixel’s value can still occur, but only for SLTP when TPGD is enabled.

Table 5 — The nominal values of the AT pixel locations.

NOTE — NA means that the parameter has no nominal value.

GBTEMPLATE	GBATX₁ GBATY₁	GBATX₂ GBATY₂	GBATX₃ GBATY₃	GBATX₄ GBATY₄
0	3 -1	-3 -1	2 -2	-2 -2
1	3 -1	NA NA	NA NA	NA NA
2	2 -1	NA NA	NA NA	NA NA
3	2 -1	NA NA	NA NA	NA NA

6.2.5.5 Typical prediction for generic direct coding (TPGD)

Typical prediction for generic direct coding can be enabled or disabled with the **TPGDON** parameter. If typical prediction for generic direct coding is enabled (**TPGDON** is **1**), then before the first pixel of each row is decoded, a value indicating that a row is typical shall be decoded. If the row is typical then each pixel of this row is identical to the corresponding pixel in the row immediately above, and so no other pixels of this row need to be decoded. If the row is not typical, then each pixel of this row needs to be decoded.

6.2.5.6 Skipped pixels

If the parameter **USES SKIP** is **1**, then the parameter **SKIP** contains a **GBW**-by-**GBH** bitmap. Each pixel in **SKIP** corresponds to a pixel in the bitmap being decoded; if the pixel in **SKIP** is **1** then the corresponding pixel in the bitmap being decoded is **0**, is not actually decoded.

6.2.5.7 Decoding the bitmap

The decoding of the bitmap proceeds as follows.

1. Set

$$LTP = 0$$

2. Create a bitmap **GBREG** of width **GBW** and height **GBH** pixels.

3. Decode each row as follows.

- (a) If all **GBH** rows have been decoded then the decoding is complete; proceed to step 4.
- (b) If **TPGDON** is **1** then decode a bit using the arithmetic entropy coder, where the context used to decode this bit varies depending on the template in use:
 - If **GBTEMPLATE** is 0, use the context shown in Figure 8.
 - If **GBTEMPLATE** is 1, use the context shown in Figure 9.
 - If **GBTEMPLATE** is 2, use the context shown in Figure 10.
 - If **GBTEMPLATE** is 3, use the context shown in Figure 11.

Let **SLTP** be the value of this bit. Set

$$LTP = LTP \text{ XOR } SLTP$$

NOTE — In Figures 8 through 11, the template is shown with the **AT** pixel or pixels in their nominal locations. The same pixel values (**0** or **1**) shall be used for the **AT** pixels no matter what their actual locations are. That is, moving the **AT** pixels does not affect the context that is used to decode **SLTP**.

- (c) If **LTP** = **1** then set every pixel of the current row of **GBREG** equal to the corresponding pixel of the row immediately above.
- (d) If **LTP** = **0** then, from left to right, decode each pixel of the current row of **GBREG**. The procedure for each pixel is as follows:
 - i. If **USES SKIP** is **1** and the pixel in the bitmap **SKIP** at the location corresponding to the current pixel is **1**, then set the current pixel to **0**.
 - ii. Otherwise,
 - A. Place the template given by parameters **GBTEMPLATE**, **GBATX**₁ through **GBATX**₄ and **GBATY**₁ through **GBATY**₄ so that the current pixel is aligned with the location denoted by a circle in the figure describing the appearance of the template with identifier **GBTEMPLATE**.
 - B. Form an integer **CONTEXT** by gathering the values of the image pixels overlaid by the template (including **AT** pixels) at its current location. The order of this gathering is not standardised, but shall be consistent and independent of the location of the **AT** pixels.

- C. Decode the current pixel by invoking the arithmetic entropy decoding procedure, with CX set to the value formed by concatenating the label “GB” and the 10–16 pixel values gathered in CONTEXT. The result of this invocation is the value of the current pixel.

EXAMPLE — If **GBTEMPLATE** is 2, the image pixels overlaid by the template are as shown in Figure 10, and the pixels are gathered in reading order (in rows from top to bottom, and within each row from left to right), then CX is set to “GB0011100101”.

4. After all the rows have been decoded, the current contents of the bitmap GBREG are the results that shall be obtained by every decoder, whether it performs this exact sequence of steps or not.




Figure 8 — Reused context for coding the SLTP pseudo-pixel when **GBTEMPLATE** is 0.




Figure 9 — Reused context for coding the SLTP pseudo-pixel when **GBTEMPLATE** is 1.




Figure 10 — Reused context for coding the SLTP pseudo-pixel when **GBTEMPLATE** is 2.

6.2.6 Decoding using MMR coding

If **MMR** is 1, the generic region decoding procedure is identical to an MMR (Modified Modified READ) decoder described in ITU-T Recommendation T.6, with the following exceptions:

- An invocation of the generic region decoding procedure with **MMR** equal to 1 shall consume an integral number of bytes, beginning and ending on a byte boundary. This may involve skipping over some bits in the last byte read.




Figure 11 — Reused context for coding the SLTP pseudo-pixel when GBTEMPLATE is 3.

- The decoder in ITU-T Recommendation T.6 is specified as producing pixels whose value may be either “black” or “white”. For the purposes of this Recommendation | International Standard, the result of using the MMR decoder shall be interpreted as follows:
 - Pixels decoded by the MMR decoder having the value “black” shall be treated as having the value **1**.
 - Pixels decoded by the MMR decoder having the value “white” shall be treated as having the value **0**.
- If the number of bytes contained in the encoded bitmap is known in advance, then it is permissible for the data stream not to contain an EOFB (**0000000000100000000001**) at the end of the MMR-encoded data. The cases where the number of bytes is known are when this decoding procedure is invoked
 - from within the pattern dictionary decoding procedure,
 - from within the symbol dictionary decoding procedure, or
 - as part of decoding a generic region whose data length is known.

The number of bytes is not known when this decoding procedure is invoked from within the gray-scale image decoding procedure, or when it is invoked as part of a generic region whose data length is not known. In these cases, EOFB must be present.

- The extension codes of T.6, including uncompressed mode, must not be present in the MMR-encoded data.

NOTE — MMR provides less compression than image bitmap compression based on arithmetic coding. Image bitmap decoding using MMR is faster than image bitmap decoding based on arithmetic coding.

6.3 Generic Refinement Region Decoding Procedure

6.3.1 General description

This decoding procedure is used to decode a rectangular array of **0** or **1** values, which are coded one pixel at a time. There is a reference bitmap known to the decoding procedure, and this is used as part of the decoding process. The reference bitmap is intended to resemble the bitmap being decoded, and this similarity is used to increase compression. Each pixel is decoded using a context comprising pixels drawn from the reference bitmap as well as previously-decoded pixels from the bitmap being decoded.

6.3.2 Input parameters

The parameters to this decoding procedure are shown in Table 6.

6.3.3 Return value

The variable whose value is the result of this decoding procedure is shown in Table 7.

6.3.4 Variables used in decoding

The variables used by this decoding procedure are shown in Table 8.

Table 6 — Parameters for the generic refinement region decoding procedure.

Name	Type	Size (bits)	Signed?	Description and restrictions
GRW	Integer	32	N	The width of the region.
GRH	Integer	32	N	The height of the region.
GRTEMPLATE	Integer	1	N	The template identifier.
GRREFERENCE	Bitmap			The reference bitmap.
GRREFERENCEDX	Integer	32	Y	The X offset of the reference bitmap with respect to the bitmap being decoded.
GRREFERENCEDY	Integer	32	Y	The Y offset of the reference bitmap with respect to the bitmap being decoded.
TPGRON	Integer	1	N	Whether typical prediction for generic refinement is used.
GRATX₁	Integer	8	Y	The X location of the adaptive template pixel RA ₁ . *
GRATY₁	Integer	8	Y	The Y location of the adaptive template pixel RA ₁ . *
GRATX₂	Integer	8	Y	The X location of the adaptive template pixel RA ₂ . *
GRATY₂	Integer	8	Y	The Y location of the adaptive template pixel RA ₂ . *

* Unused if **GRTEMPLATE** \neq 0

Table 7 — Return value from the generic refinement region decoding procedure.

Name	Type	Size (bits)	Signed?	Description and restrictions
GRREG	Bitmap			The decoded region bitmap.

Table 8 — Variables used in the generic refinement region decoding procedure.

Name	Type	Size (bits)	Signed?	Description and restrictions
CONTEXT	Integer	13	N	The values of the pixels in the template
LTP	Integer	1	N	Whether the current image line is decoded explicitly *
SLTP	Integer	1	N	Whether the current line's LTP value is different from the previous line's LTP value *
TPGRPIX	Integer	1	N	Whether the current pixel is to be decoded implicitly using a TPGR prediction *
TPGRVAL	Integer	1	N	Value of the TPGR-predicted current pixel *

* Unused if **TPGRON** = 0

6.3.5 Decoding using a template and arithmetic coding

6.3.5.1 General description

The generic refinement region decoding procedure is based on arithmetic coding with a template to determine the coding state. The remainder of 6.3.5 describes this form of decoding.

6.3.5.2 Coding order and edge conventions

The coding algorithm iterates through the refine bitmap being decoded, along with a reference bitmap, in raster scan order. That is, it iterates by rows from top to bottom, and within each row from left to right. The processing for a current target pixel will reference some pixels in fixed spatial relationship to the target pixel. Some of these pixels are drawn from the reference version of the bitmap, and some of these pixels are drawn from the already-coded pixels of the refined bitmap.

Near the edges of the bitmap, these neighbour references might not lie in the actual bitmap. The rule to satisfy out-of-bounds references shall be:

- All pixels lying outside the bounds of the actual bitmap or the reference bitmap have the value **0**.

6.3.5.3 Fixed templates and adaptive templates

A template defines a neighborhood around a pixel to be coded. The values of the pixels in this neighborhood define a context. Each context has its own adaptive probability estimate used by the arithmetic coder (see Annex E). Although a template is a geometric pattern of pixels, the pixels in a template are said to take on values when the template is aligned with a particular part of the image.



Figure 12 — 13-pixel refinement template showing the AT pixels at their nominal locations.



Figure 13 — 10-pixel refinement template

Figure 12 shows the template which shall be used when **GRTEMPLATE** is 0. Figure 13 shows the template which shall be used when **GRTEMPLATE** is 1. In each of these figures, the left-hand group indicates the pixels from the already-coded pixels of the refined bitmap that are in the template, and the right-hand group indicates the pixels from the reference version of the template that are in the template. Each group in each figure includes

a pixel denoted by a circle; these pixels all correspond to the pixel to be coded. The pixels marked with an ‘X’ correspond to ordinary pixels in the template. The pixels denoted RA_1 – RA_2 are special pixels in the template. They are denoted “adaptive” or AT pixels. These pixels are special in that their locations are allowed to change during the process of encoding the image. See 6.3.5.4 for a description of AT pixels. The legends RA_1 – RA_2 indicate the nominal locations of AT pixels 1 to 2.

The AT pixel RA_1 can be located anywhere in the field shown in Figure 7, not including the current pixel. The AT pixel RA_2 can be located anywhere in the range $(-128, -128)$ to $(127, 127)$ in the reference bitmap.

The pixels in the left hand group of each template shall be aligned with the already-decoded pixels of the bitmap being decoded, with the pixel denoted by a circle lying on the pixel to be decoded. Let (X, Y) be the location of this pixel. The pixels of the right hand group of each template shall be aligned with the reference bitmap $GRREFERENCE$, with the pixel denoted by a circle placed at the location $(X - GRREFERENCEDX, Y - GRREFERENCEDY)$. The values of the pixels in the template shall be combined to form a context. Each pixel in the template (including the adaptive pixels) shall correspond to a specific bit in the context, although the pixels in the template may be assigned to bits in the context in any order. Because there are up to 13 pixels in the template, contexts can take on up to 8192 different values. This context shall be used to identify which adaptive probability estimate shall be used by the arithmetic coder for encoding the pixel to be coded (see Annex E).

6.3.5.4 Adaptive template pixels

In coding the image, the template shall be allowed to change in the restricted way described in this clause.

The pixels that are allowed to change shall be called AT pixels. Their standard locations are indicated by ‘ RA_1 ’ and ‘ RA_2 ’ in Figure 12. Note that only one template has AT pixels.

6.3.5.5 Typical prediction for generic refinement (TPGR)

Typical prediction for generic refinement can be enabled or disabled with the **TPGRON** parameter. If typical prediction for generic refinement is enabled (**TPGRON** is **1**) then before the first pixel of each row is decoded, a value indicating whether a row is typical shall be decoded. If the row is not typical, each pixel of the row needs to be explicitly decoded. If the row is typical, all typically-predictable pixels can be implicitly decoded using their predicted value, with the remainder of the pixels still being explicitly decoded. For a pixel to be typically-predictable it must meet the criteria defined in 6.3.5.6, step 3d.

6.3.5.6 Decoding the refinement bitmap

The decoding of the bitmap proceeds as follows.

1. Set $LTP = 0$.
2. Create a bitmap $GRREG$ of width GRW and height GRH pixels.
3. Decode each row as follows
 - (a) If all GRH rows have been decoded then the decoding is complete; proceed to step 4
 - (b) If **TPGRON** is **1** then decode a bit using the arithmetic entropy coder, where the context used to decode this bit varies depending on the template in use:
 - If **GRTEMPLATE** is **0**, use the context shown in Figure 14.
 - If **GRTEMPLATE** is **1**, use the context shown in Figure 15.

Let $SLTP$ be the value of this decoded bit. Set

$$LTP = LTP \text{ XOR } SLTP$$

- (c) If $LTP = 0$ then, from left to right, explicitly decode all pixels of the current row of $GRREG$. The procedure for each pixel is as follows:
 - i. Place the template given by parameters **GRTEMPLATE** (and **GRATX₁**, **GRATY₁**, **GRATX₂** and **GRATY₂** if **GRTEMPLATE** is **0**) so that the current pixel is aligned with the location denoted by a circle in the figure describing the appearance of the template with identifier **GRTEMPLATE**.

- ii. Form an integer CONTEXT by gathering the values of the image pixels overlaid by the template (including AT pixels) at its current location. The order of this gathering is not standardised, but must be consistent and independent of the location of the AT pixels.
- iii. Decode the current pixel by invoking the arithmetic entropy decoding procedure, with CX set to the value formed by concatenating the label “GR” and the 10–13 pixel values gathered in CONTEXT. The result of this invocation is the value of the current pixel.

EXAMPLE — If **GRTEMPLATE** is **1**, the image pixels overlaid by the template are as shown in Figure 15, and the pixels are gathered in reading order (in rows from top to bottom, and within each row from left to right, with the pixels in **GRREG** considered before the pixels in **GRREFERENCE**), then **CX** is set to “**GR0000001000**”.

- (d) If **LTP** = **1** then, from left to right, implicitly decode certain pixels of the current row of **GRREG**, and explicitly decode the rest. The procedure for each pixel is as follows:
 - i. Set **TPGRPIX** equal to **1** if
 - A. **TPGRON** is **1** AND
 - B. a 3×3 pixel array in the reference bitmap (Figure 16), centered at the location corresponding to the current pixel, contains pixels all of the same value.
 When **TPGRPIX** is set to **1**, set **TPGRVAL** equal to the current pixel predicted value, which is the common value of the nine adjacent pixels in the 3×3 array.
 - ii. If **TRPPPIX** is **1** then implicitly decode the current pixel by setting it equal to its predicted value (**TPGRVAL**).
 - iii. Otherwise, explicitly decode the current pixel using the methodology of steps 3(c)i through 3(c)iii above.
- 4. After all the rows have been decoded, the current contents of the bitmap **GRREG** are the results that shall be obtained by every decoder, whether it performs this exact sequence of steps or not.



Figure 14 — Reused context for coding the SLTP pseudo-pixel when **GRTEMPLATE** is **0**.

6.4 Text Region Decoding Procedure

6.4.1 General description

This decoding procedure is used to decode a bitmap by decoding a number of symbol instances. A symbol instance contains a location and a symbol ID, and possibly a refinement bitmap. These symbol instances are combined to form the decoded bitmap.

NOTE — This decoding procedure will normally be used to decode the text part of a page. The symbols are normally single text characters from some font or alphabet.

Table 9 — Parameters for the text region decoding procedure.

Name	Type	Size (bits)	Signed?	Description and restrictions
SBHUFF	Integer	1	N	Whether Huffman coding is used.
SBREFINE	Integer	1	N	Whether refinement coding is used.
SBW	Integer	32	N	The width of the region.
SBH	Integer	32	N	The height of the region.
SBNUMINSTANCES	Integer	32	N	The number of symbol instances in this region.
SBSTRIPS	Integer	4	N	The size of the symbol instance strips. May take on the values 1, 2, 4 or 8.
SBNUMSYMS	Integer	32	N	The number of symbols that may be used in this region.
SBSYMCODES	Array of Huffman codes			An array containing the codes for the symbols used in this region. Contains SBNUMSYMS codes. *
SBSYMCODELEN	Integer	6	N	The length of the symbol codes used in IAID ****
SBSYMS	Array of symbols			An array containing the symbols used in this text region. Contains SBNUMSYMS symbols.
SBDEFPIXEL	Integer	1	N	The default pixel for this bitmap.
SBCOMBOP	Operator			The combination operator for this text region. May take on the values OR, AND, XOR and XNOR.
TRANPOSED	Integer	1	N	Whether the strips run vertically.
REFCORNER	Corner			The reference corner of each symbol instance bitmap. May take on the values TOPLEFT, TOPRIGHT, BOTTOMLEFT and BOTTOMRIGHT.
SBDSoFFSET	Integer	5	Y	An offset for all the delta S values.
SBHUFFFS	Huffman table			The Huffman table used to decode the S coordinate of the first symbol instance in each strip. *
SBHUFFDS	Huffman table			The Huffman table used to decode the S coordinate of subsequent symbol instances in each strip. *
SBHUFFDT	Huffman table			The Huffman table used to decode the difference in T coordinates between non-empty strips. *
SBHUFFRDW	Huffman table			The Huffman table used to decode the difference between a symbol's width and the width of a refinement coded bitmap. **
SBHUFFRDH	Huffman table			The Huffman table used to decode the difference between a symbol's height and the height of a refinement coded bitmap. **
SBHUFFRDx	Huffman table			The Huffman table used to decode the difference between a symbol instance's X coordinate and the X coordinate of a refinement coded bitmap. **
SBHUFFRDY	Huffman table			The Huffman table used to decode the difference between a symbol instance's Y coordinate and the Y coordinate of a refinement coded bitmap. **
SBHUFFRSIZE	Huffman table			The Huffman table used to decode the size of a symbol instance's refinement bitmap data. **
SBRTemplate	Integer	1	N	Template identifier for refinement coding of symbol instance bitmaps. ***
SBRA_{Tx1}	Integer	8	Y	The X location of the adaptive template pixel RA ₁ . ***
SBRA_{Ty1}	Integer	8	Y	The Y location of the adaptive template pixel RA ₁ . ***
SBRA_{Tx2}	Integer	8	Y	The X location of the adaptive template pixel RA ₂ . ***
SBRA_{Ty2}	Integer	8	Y	The Y location of the adaptive template pixel RA ₂ . ***

* Unused if **SBHUFF** = 0. ** Unused if **SBHUFF** = 0 or **SBREFINE** = 0.

*** Unused if **SBREFINE** = 0. **** Unused if **SBHUFF** = 1.



Figure 15 — Reused context for coding the SLTP pseudo-pixel when GRTEMPLATE is 1.



Figure 16 — TPGR template.

6.4.2 Input parameters

The parameters to this decoding procedure are shown in Table 9.

NOTE — The values of some of these parameters in a typical situation, where a bitmap containing text characters in standard English reading order is being decoded, and 1 is the foreground pixel value, are

- **SBDEFPIXEL** is 0
- **SBCOMBOP** is OR
- **TRANSPOSED** is 0
- **REFCORNER** is BOTTOMLEFT

6.4.3 Return value

The variable whose value is the result of this decoding procedure is shown in Table 10.

Table 10 — Return value from the text region decoding procedure.

Name	Type	Size (bits)	Signed?	Description and restrictions
SBREG	Bitmap			The decoded region bitmap.

6.4.4 Variables used in decoding

The variables used by this decoding procedure are shown in Table 11.

Table 11 — Variables used in the text region decoding procedure.

Name	Type	Size (bits)	Signed?	Description and restrictions
STRIPT	Integer	32	Y	The numerically smallest T coordinate in the current strip.
FIRSTS	Integer	32	Y	The first S coordinate of the current strip.
NINSTANCES	Integer	32	N	A symbol instance counter.
DT	Integer	32	Y	The number of empty strips between two non-empty strips.
DFS	Integer	32	Y	The difference in S coordinates between the first symbol instances of two strips.
CURS	Integer	32	Y	The current S coordinate.
CURT	Integer	3	N	The current symbol instance's T coordinate relative to the current strip.
S_I	Integer	32	Y	A symbol instance's S coordinate.
T_I	Integer	32	Y	A symbol instance's T coordinate.
ID_I	Integer	32	N	A symbol instance's symbol ID.
IB_I	Bitmap			A symbol instance's symbol bitmap.
W_I	Integer	32	N	The width of a symbol instance's symbol bitmap.
H_I	Integer	32	N	The height of a symbol instance's symbol bitmap.
IDS	Integer	32	Y	The difference in S coordinates between two symbol instances within a strip.
R_I	Integer	1	N	Whether a symbol instance's symbol bitmap is coded using refinement.
RDW_I	Integer	32	Y	The delta width of a symbol instance's refinement bitmap. *
RDH_I	Integer	32	Y	The delta height of a symbol instance's refinement bitmap. *
RDX_I	Integer	32	Y	The delta X of a symbol instance's refinement bitmap. *
RDY_I	Integer	32	Y	The delta Y of a symbol instance's refinement bitmap. *
IBO_I	Bitmap			A symbol instance's original symbol bitmap. *
WO_I	Integer	32	N	The width of IBO_I . *
HO_I	Integer	32	N	The height of IBO_I . *

*Unused if **SBREFINE** = 0.

6.4.5 Decoding the text region

A symbol-coded bitmap is represented by a set of symbol instances. Each symbol instance encodes a location, a symbol ID, and possibly refinement information. The location of each symbol instance comprises an S coordinate and a T coordinate. If **TRANPOSED** is **0**, then the S coordinate axis corresponds to the X axis of the bitmap, and the T axis corresponds to the Y axis of the bitmap. If **TRANPOSED** is **1**, then the S coordinate axis corresponds to the Y axis of the bitmap, and the T axis corresponds to the X axis of the bitmap.

NOTE 1 — Transposing the coordinate axes allows efficient coding of text running vertically. The reference corner is variable because the most efficient coding is usually obtained when the reference corner of each symbol instance lies on a text baseline, and the text baselines may run in any direction.

In order to improve compression, symbol instances are grouped into strips according to their T_I values. This is done according to the value of **SBSTRIPS**. Symbol instances having T_I values between 0 and **SBSTRIPS** - 1 are grouped into one strip, symbol instances having T_I values between **SBSTRIPS** and $2 \times \text{SBSTRIPS} - 1$ into the next, and so on. Within each strip, the symbol instances are coded in the order of increasing S coordinate.

NOTE 2 — Normally the strips occur in the order of strictly increasing T coordinates, and the symbol instances within each strip occur in the order of nondecreasing S coordinates. However, it is possible for negative delta S or delta T values to occur during the decoding, meaning that the strips and symbol instances might occur in any order.

The overall structure of the data to be decoded in order to reconstruct the text region is shown in Figure 17. The format of each strip is as shown in Figure 18. When **SBREFINE** is **0**, the format of each symbol instance is as shown in Figure 19. When **SBREFINE** is **1**, the format of each symbol instance is as shown in Figure 20.

NOTE 3 — There may be some symbol instances whose reference corner lies off the top of the region. If these are to be coded, there must be some way to have a strip that also lies above the top of the region. The initial value of **STRIPT** is the coordinate with respect to which the first strip is located.

Initial STRIPT value
First strip
Second strip
...
Last strip

Figure 17 — Coded structure of a text region.

Delta T
First symbol instance
Second symbol instance
...
Last symbol instance
OOB

Figure 18 — Structure of a strip.

The result of decoding a text region shall be the bitmap that is produced by the following steps.

1. Fill a bitmap **SBREG**, of the size given by **SBW** and **SBH**, with the **SBDEFPIXEL** value.
2. Decode the initial **STRIPT** value as described in 6.4.6. Negate the decoded value and assign this negated value to the variable **STRIPT**. Assign the value 0 to **FIRSTS**. Assign the value 0 to **NINSTANCES**.

Symbol instance S coordinate
Symbol instance T coordinate
Symbol instance symbol ID

Figure 19 — Structure of a symbol instance when SBREFINE is 0.

Symbol instance S coordinate
Symbol instance T coordinate
Symbol instance symbol ID
Symbol instance refinement information

Figure 20 — Structure of a symbol instance when SBREFINE is 1.

3. Decode each strip as follows.

- (a) If NINSTANCES is equal to **SBNUMINSTANCES** then there are no more strips to decode, and the process of decoding the text region is complete; proceed to step 4.
- (b) Decode the strip's delta T value as described in 6.4.6. Let DT be the decoded value. Set

$$\text{STRIPT} = \text{STRIPT} + \text{DT}$$

(c) Decode each symbol instance in the strip as follows.

- i. If the current symbol instance is the first symbol instance in the strip, then decode the first symbol instance's S coordinate as described in 6.4.7. Let DFS be the decoded value. Set

$$\begin{aligned} \text{FIRSTS} &= \text{FIRSTS} + \text{DFS} \\ \text{CURS} &= \text{FIRSTS} \end{aligned}$$

- ii. Otherwise, if the current symbol instance is not the first symbol instance in the strip, decode the symbol instance's S coordinate as described in 6.4.8. If the result of this decoding is OOB then the last symbol instance of the strip has been decoded; proceed to step 3d. Otherwise, let IDS be the decoded value. Set

$$\text{CURS} = \text{CURS} + \text{IDS} + \text{SBDSOFFSET}$$

NOTE — The intended use of **SBDSOFFSET** is to make the most common value decoded in 6.4.8 zero. The shortest code in all of the default tables used in 6.4.8 is for the value zero.

- iii. Decode the symbol instance's T coordinate as described in 6.4.9. Let CURT be the decoded value. Set

$$T_I = \text{STRIPT} + \text{CURT}$$

- iv. Decode the symbol instance's symbol ID as described in 6.4.10. Let ID_I be the decoded value.
- v. Determine the symbol instance's bitmap IB_I as described in 6.4.11. The width and height of this bitmap shall be denoted as W_I and H_I respectively.
- vi. Update CURS as follows.

- If **TRANPOSED** is 0, and **REFCORNER** is TOPRIGHT or BOTTOMRIGHT, set

$$\text{CURS} = \text{CURS} + W_I - 1$$

- If **TRANPOSED** is **1**, and **REFCORNER** is **BOTTOMLEFT** or **BOTTOMRIGHT**, set

$$\text{CURS} = \text{CURS} + H_I - 1$$

- Otherwise, do not change CURS in this step.

vii. Set

$$S_I = \text{CURS}$$

viii. Determine the location of the symbol instance bitmap with respect to SBREG as follows.

- If **TRANPOSED** is **0**, then
 - If **REFCORNER** is **TOPLEFT** then the top left pixel of the symbol instance bitmap IB_I shall be placed at $\text{SBREG}[S_I, T_I]$.
 - If **REFCORNER** is **TOPRIGHT** then the top right pixel of the symbol instance bitmap IB_I shall be placed at $\text{SBREG}[S_I, T_I]$.
 - If **REFCORNER** is **BOTTOMLEFT** then the bottom left pixel of the symbol instance bitmap IB_I shall be placed at $\text{SBREG}[S_I, T_I]$.
 - If **REFCORNER** is **BOTTOMRIGHT** then the bottom right pixel of the symbol instance bitmap IB_I shall be placed at $\text{SBREG}[S_I, T_I]$.
- If **TRANPOSED** is **1**, then
 - If **REFCORNER** is **TOPLEFT** then the top left pixel of the symbol instance bitmap IB_I shall be placed at $\text{SBREG}[T_I, S_I]$.
 - If **REFCORNER** is **TOPRIGHT** then the top right pixel of the symbol instance bitmap IB_I shall be placed at $\text{SBREG}[T_I, S_I]$.
 - If **REFCORNER** is **BOTTOMLEFT** then the bottom left pixel of the symbol instance bitmap IB_I shall be placed at $\text{SBREG}[T_I, S_I]$.
 - If **REFCORNER** is **BOTTOMRIGHT** then the bottom right pixel of the symbol instance bitmap IB_I shall be placed at $\text{SBREG}[T_I, S_I]$.

If any part of IB_I , when placed at this location, lies outside the bounds of SBREG, then ignore this part of IB_I in step 3(c)ix.

ix. Draw IB_I into SBREG. Combine each pixel of IB_I with the current value of the corresponding pixel in SBREG, using the combination operator specified by **SBCOMBOP**. Write the results of each combination into that pixel in SBREG.

x. Update CURS as follows.

- If **TRANPOSED** is **0**, and **REFCORNER** is **TOPLEFT** or **BOTTOMLEFT**, set

$$\text{CURS} = \text{CURS} + W_I - 1$$

- If **TRANPOSED** is **1**, and **REFCORNER** is **TOPLEFT** or **TOPRIGHT**, set

$$\text{CURS} = \text{CURS} + H_I - 1$$

- Otherwise, do not change CURS in this step.

NOTE — The CURS update rules are designed to allow the gap between adjacent symbol instances to be encoded, rather than the distance between their reference corners; this takes out one source of variation (the symbol instance bitmap width or height), and allows better compression.

xi. Set

$$\text{NINSTANCES} = \text{NINSTANCES} + 1$$

(d) When the strip has been completely decoded, decode the next strip.

4. After all the strips have been decoded, the current contents of SBREG are the results that shall be obtained by every decoder, whether it performs this exact sequence of steps or not.

6.4.6 Strip delta T

If **SBHUFF** is **1**, decode a value using the Huffman table specified by **SBHUFFDT** and multiply the resulting value by **SBSTRIPS**.

If **SBHUFF** is **0**, decode a value using the IADT integer arithmetic decoding procedure (see Annex A) and multiply the resulting value by **SBSTRIPS**.

6.4.7 First symbol instance S coordinate

NOTE — The symbol instance S coordinate value for the first symbol instance of each strip is coded differently from the subsequent symbol instances in each strip. This takes advantage of the beginnings of lines being aligned.

If **SBHUFF** is **1**, decode a value using the Huffman table specified by **SBHUFFFS**.

If **SBHUFF** is **0**, decode a value using the IAFS integer arithmetic decoding procedure (see Annex A).

6.4.8 Subsequent symbol instance S coordinate

If **SBHUFF** is **1**, decode a value using the Huffman table specified by **SBHUFFDS**.

If **SBHUFF** is **0**, decode a value using the IADS integer arithmetic decoding procedure (see Annex A).

In either case it is possible that the result of this decoding is the out-of-band value OOB.

6.4.9 Symbol instance T coordinate

If **SBSTRIPS** = 1, then the value decoded is always zero. Otherwise,

- If **SBHUFF** is **1**, decode a value by reading $\lceil \log_2 \text{SBSTRIPS} \rceil$ bits directly from the bitstream.
- If **SBHUFF** is **0**, decode a value using the IAIT integer arithmetic decoding procedure (see Annex A).

NOTE — If **SBSTRIPS** = 1, then no bits are consumed, and the IAIT integer arithmetic decoding procedure is never invoked.

6.4.10 Symbol instance symbol ID

If **SBHUFF** is **1**, decode a value by reading one bit at a time until the resulting bit string is equal to one of the entries in **SBSYMCODES**. The resulting value, which is ID_I , is the index of the entry in **SBSYMCODES** that is read.

If **SBHUFF** is **0**, decode a value using the IAID integer arithmetic decoding procedure (see Annex A). Set ID_I to the resulting value.

6.4.11 Symbol instance bitmap

In some cases, the symbol instance bitmap IB_I is simply the bitmap of the symbol identified by ID_I . In other cases, however, the symbol instance bitmap is that bitmap modified by additional refinement information. The bit indicating which of the options is true for a symbol instance is called R_I .

If **SBREFINE** is **0**, then set R_I to **0**.

If **SBREFINE** is **1**, then decode R_I as follows.

- If **SBHUFF** is **1**, then read one bit and set R_I to the value of that bit.
- If **SBHUFF** is **0**, then decode one bit using the IARI integer arithmetic decoding procedure and set R_I to the value of that bit.

If R_I is **0** then set the symbol instance bitmap IB_I to **SBSYMS**[ID_I].

If R_I is **1** then determine the symbol instance bitmap as follows:

1. Decode the symbol instance refinement delta width as described in 6.4.11.1. Let RDW_I be the value decoded.
2. Decode the symbol instance refinement delta height as described in 6.4.11.2. Let RDH_I be the value decoded.

3. Decode the symbol instance refinement X offset as described in 6.4.11.3. Let $RD\mathit{X}_I$ be the value decoded.
4. Decode the symbol instance refinement Y offset as described in 6.4.11.4. Let $RD\mathit{Y}_I$ be the value decoded.
5. If **SBHUFF** is **1**, then
 - (a) Decode the symbol instance refinement bitmap data size as described in 6.4.11.5.
 - (b) Skip over any bits remaining in the last byte read.
6. Let IBO_I be **SBSYMS**[ID_I]. Let WO_I be the width of IBO_I and HO_I be the height of IBO_I . The symbol instance bitmap IB_I is the result of applying the generic refinement region decoding procedure described in 6.3. Set the parameters to this decoding procedure as shown in Table 12.

Table 12 — Parameters used to decode a symbol instance’s bitmap using refinement.

Name	Value
GRW	$WO_I + RD\mathit{W}_I$
GRH	$HO_I + RD\mathit{H}_I$
GRTEMPLATE	SBRTEMPLATE
GRREFERENCE	IBO_I
GRREFERENCEDX	$\lfloor RD\mathit{W}_I/2 \rfloor + RD\mathit{X}_I$
GRREFERENCEDY	$\lfloor RD\mathit{H}_I/2 \rfloor + RD\mathit{Y}_I$
TPGRON	0
GRATX₁	SBRATX₁
GRATY₁	SBRATY₁
GRATX₂	SBRATX₂
GRATY₂	SBRATY₂

7. If **SBHUFF** is **1**, then skip over any bits remaining in the last byte read. The total number of bytes processed by the generic refinement bitmap decoding procedure must be equal to the value read in step 5a.

6.4.11.1 Symbol instance refinement delta width

This field, and the following fields, indicate the size, location and contents of the refined symbol bitmap, as the size might not be the same as the size of the bitmap of the symbol whose ID is given in this symbol instance; also, the change in the size of the bitmap might extend to the left and top, not just to the right and bottom, so we need to supply an offset as well as a size. Note that the offsets are given in terms of X and Y, not S and T.

If **SBHUFF** is **1**, decode a value using the Huffman table specified by **SBHUFFRDW**.

If **SBHUFF** is **0**, decode a value using the IARDW integer arithmetic decoding procedure (see Annex A).

6.4.11.2 Symbol instance refinement delta height

If **SBHUFF** is **1**, decode a value using the Huffman table specified by **SBHUFFRDH**.

If **SBHUFF** is **0**, decode a value using the IARDH integer arithmetic decoding procedure (see Annex A).

6.4.11.3 Symbol instance refinement X offset

If **SBHUFF** is **1**, decode a value using the Huffman table specified by **SBHUFFRDX**.

If **SBHUFF** is **0**, decode a value using the IARDX integer arithmetic decoding procedure (see Annex A).

6.4.11.4 Symbol instance refinement Y offset

If **SBHUFF** is **1**, decode a value using the Huffman table specified by **SBHUFFRDY**.

If **SBHUFF** is **0**, decode a value using the IARDY integer arithmetic decoding procedure (see Annex A).

6.4.11.5 Symbol instance refinement bitmap data size

Decode a value using the Huffman table specified by **SBHUFFRSIZE**.

6.5 Symbol Dictionary Decoding Procedure

6.5.1 General description

This decoding procedure is used to decode a set of symbols; these symbols can then be used by text region decoding procedures, or in some cases by other symbol dictionary decoding procedures.

6.5.2 Input parameters

The parameters to this decoding procedure are shown in Table 13.

The **SDREFAGG** parameter determines how the symbols in this symbol dictionary are coded. If **SDREFAGG** is **0** then each symbol bitmap is coded via direct bitmap coding. If **SDREFAGG** is **1** then each symbol bitmap is coded by refining or aggregating previously-defined symbol bitmaps. These previously-defined symbol bitmaps may be drawn from other dictionaries and provided as input to this decoding procedure in **SDINSYMS**, or may be defined in the current dictionary.

6.5.3 Return value

The variable whose value is the result of this decoding procedure is shown in Table 14.

6.5.4 Variables used in decoding

The variables used by this decoding procedure are shown in Table 15.

6.5.5 Decoding the symbol dictionary

The internal structure of a symbol dictionary is shown in Figure 21. The symbols defined in the dictionary are ordered into height classes: a height class contains a number of symbols whose bitmaps are the same height.

NOTE — In most cases, the height classes occur in the order of strictly increasing height, shortest through tallest. If **SDREFAGG** is **1**, though, a symbol may be coded as a refinement of a larger symbol defined in the same dictionary. In this case, the height class for that base symbol must be decoded (and therefore must occur) before the shorter height class of the symbol that is coded by refining it. For this reason, height class delta heights (and symbol delta widths) may be zero or negative, as well as positive.

First height class
Second height class
...
Last height class
List of exported symbols

Figure 21 — The structure of a symbol dictionary.

If **SDHUFF** is **1** and **SDREFAGG** is **0** then the format of a height class is as shown in Figure 22. Otherwise, the format of a height class is as shown in Figure 23. The fields mentioned in those figures are described fully below.

Height class delta height
Delta width for first symbol
Delta width for second symbol
...
OOB
Height class collective bitmap

Figure 22 — Height class coding when **SDHUFF** is **1** and **SDREFAGG** is **0**.

The result of decoding a symbol dictionary is an array **SDEXSYMS** containing **SDNUMEXSYMS** bitmaps. This array shall be the array produced by the following steps.

Table 13 — Parameters for the symbol dictionary decoding procedure.

Name	Type	Size (bits)	Signed?	Description and restrictions
SDHUFF	Integer	1	N	Whether Huffman coding is used.
SDREFAGG	Integer	1	N	Whether refinement and aggregate coding are used.
SDNUMINSYMS	Integer	32	N	The number of symbols that are used as input to this symbol dictionary decoding procedure.
SDINSYMS	Array of symbols			An array containing the symbols that are used as input to this symbol dictionary decoding procedure. Contains SDNUMINSYMS symbols.
SDNUMNEWSYMS	Integer	32	N	The number of symbols to be defined in this symbol dictionary.
SDNUMEXSYMS	Integer	32	N	The number of symbols to be exported from this symbol dictionary.
SDHUFFDH	Huffman table			The Huffman table used to decode the difference in height between two height classes. *
SDHUFFDW	Huffman table			The Huffman table used to decode the difference in width between two symbols. *
SDHUFFBMSIZE	Huffman table			The Huffman table used to decode the size of a height class collective bitmap. *
SDHUFFAGGINST	Huffman table			The Huffman table used to decode the number of symbol instances in an aggregation. **
SDTEMPLATE	Integer	2	N	The template identifier used to decode symbol bitmaps. ***
SDATX₁	Integer	8	Y	The X location of the adaptive template pixel A ₁ . ***
SDATY₁	Integer	8	Y	The Y location of the adaptive template pixel A ₁ . ***
SDATX₂	Integer	8	Y	The X location of the adaptive template pixel A ₂ . ***
SDATY₂	Integer	8	Y	The Y location of the adaptive template pixel A ₂ . ***
SDATX₃	Integer	8	Y	The X location of the adaptive template pixel A ₃ . ***
SDATY₃	Integer	8	Y	The Y location of the adaptive template pixel A ₃ . ***
SDATX₄	Integer	8	Y	The X location of the adaptive template pixel A ₄ . ***
SDATY₄	Integer	8	Y	The Y location of the adaptive template pixel A ₄ . ***
SDRTEMPLATE	Integer	1	N	Template identifier for refinement coding of bitmaps. ****
SDRATX₁	Integer	8	Y	The X location of the adaptive template pixel RA ₁ . ****
SDRATY₁	Integer	8	Y	The Y location of the adaptive template pixel RA ₁ . ****
SDRATX₂	Integer	8	Y	The X location of the adaptive template pixel RA ₂ . ****
SDRATY₂	Integer	8	Y	The Y location of the adaptive template pixel RA ₂ . ****

* Unused if **SDHUFF** = 0.

** Unused if **SDHUFF** = 0 or **SDREFAGG** = 0.

*** Unused if **SDHUFF** = 1.

**** Unused if **SDREFAGG** = 0.

Table 14 — Return value from the symbol dictionary decoding procedure.

Name	Type	Size (bits)	Signed?	Description and restrictions
SDEXSYMS	Array of symbols			The symbols exported by this symbol dictionary. Contains SDNUMEXSYMS symbols.

Table 15 — Variables used in the symbol dictionary decoding procedure.

Name	Type	Size (bits)	Signed?	Description and restrictions
SDNEWSYMS	Array of symbols			The symbols defined in this symbol dictionary. Contains SDNUMNEWSYMS symbols.
SDNEWSYMWIDTHS	Array of integers			The widths of the symbols in SDNEWSYMS. Contains SDNUMNEWSYMS integers. Each integer is a 32-bit unsigned value.
HHEIGHT	Integer	32	N	Height of the current height class.
NSYMSDECODED	Integer	32	N	How many symbols have been decoded so far.
HCDH	Integer	32	Y	The difference in height between two height classes.
SYMWIDTH	Integer	32	N	The width of the current symbol.
TOTWIDTH	Integer	32	N	The width of the current height class.
HCFIRSTSYM	Integer	32	N	The index of the first symbol in the current height class.
DW	Integer	32	Y	The difference in width between two symbols.
B_S	Bitmap			The current symbol's bitmap.
B_{HC}	Bitmap			The current height class collective bitmap.
I	Integer	32	N	An array index.
J	Integer	32	N	An array index.
REFAGGNINST	Integer	32	N	The number of symbol instances in an aggregation.
EXFLAGS	Array of integers			The export flags for this dictionary. Contains SDNUMINSYMS + SDNUMNEWSYMS values. Each value is one bit.
EXINDEX	Integer	32	N	An array index.
CUREXFLAG	Integer	1	N	The current export flag.
EXRUNLENGTH	Integer	32	N	The length of a run of identical export flag values.

Height class delta height
Delta width for first symbol
Bitmap for first symbol
Delta width for second symbol
Bitmap for second symbol
...
OOB

Figure 23 — Height class coding when SDHUFF is 0 or SDREFAGG is 1.

1. Create an array SDNEWSYMS of bitmaps, having **SDNUMNEWSYMS** entries.
2. If **SDHUFF** is **1** and **SDREFAGG** is **0**, create an array SDNEWSYMWIDTHS of integers, having **SDNUMNEWSYMS** entries.
3. Set

$$\begin{aligned} \text{HCHEIGHT} &= 0 \\ \text{NSYMSDECODED} &= 0 \end{aligned}$$

4. Decode each height class as follows.
 - (a) If $\text{NSYMSDECODED} = \text{SDNUMNEWSYMS}$ then all the symbols in the dictionary have been decoded; proceed to step 5.
 - (b) Decode the height class delta height as described in 6.5.6. Let HCDH be the decoded value. Set

$$\begin{aligned} \text{HCHEIGHT} &= \text{HCHEIGHT} + \text{HCDH} \\ \text{SYMWIDTH} &= 0 \\ \text{TOTWIDTH} &= 0 \\ \text{HCFIRSTSYM} &= \text{NSYMSDECODED} \end{aligned}$$

- (c) Decode each symbol within the height class as follows.
 - i. Decode the delta width for the symbol as described in 6.5.7. If the result of this decoding is OOB then all the symbols in this height class have been decoded; proceed to step 4d. Otherwise let DW be the decoded value and set

$$\begin{aligned} \text{SYMWIDTH} &= \text{SYMWIDTH} + \text{DW} \\ \text{TOTWIDTH} &= \text{TOTWIDTH} + \text{SYMWIDTH} \end{aligned}$$

- ii. If **SDHUFF** is **0** or **SDREFAGG** is **1** then decode the symbol's bitmap as described in 6.5.8. Let B_S be the decoded bitmap (this bitmap has width SYMWIDTH and height HCHEIGHT). Set

$$\text{SDNEWSYMS}[\text{NSYMSDECODED}] = B_S$$

- iii. If **SDHUFF** is **1** and **SDREFAGG** is **0** then set

$$\text{SDNEWSYMWIDTHS}[\text{NSYMSDECODED}] = \text{SYMWIDTH}$$

- iv. Set

$$\text{NSYMSDECODED} = \text{NSYMSDECODED} + 1$$

- (d) If **SDHUFF** is **1** and **SDREFAGG** is **0** then decode the height class collective bitmap as described in 6.5.9. Let B_{HC} be the decoded bitmap. This bitmap has width TOTWIDTH and height HCHEIGHT. Break up the bitmap B_{HC} as follows to obtain the symbols SDNEWSYMS[HCFIRSTSYM] through SDNEWSYMS[NSYMSDECODED – 1].

B_{HC} contains the NSYMSDECODED – HCFIRSTSYM symbols concatenated left-to-right, with no intervening gaps. For each I between HCFIRSTSYM and NSYMSDECODED – 1,

- the width of SDNEWSYMS[I] is the value of SDNEWSYMWIDTHS[I],
- the height of SDNEWSYMS[I] is HCHEIGHT, and
- the bitmap SDNEWSYMS[I] can be obtained by extracting the columns of B_{HC} from

$$\sum_{J=HCFIRSTSYM}^{I-1} \text{SDNEWSYMWIDTHS}[J]$$

through

$$\left(\sum_{J=HCFIRSTSYM}^I \text{SDNEWSYMWIDTHS}[J] \right) - 1$$

EXAMPLE — Columns 0 through SDNEWSYMWIDTHS[HCFIRSTSYM] – 1 of B_{HC} contain the bitmap for SDNEWSYMS[HCFIRSTSYM], the first symbol in the height class.

5. Determine which symbol bitmaps are exported from this symbol dictionary, as described in 6.5.10. These bitmaps can be drawn from the symbols that are used as input to the symbol dictionary decoding procedure as well as the new symbols produced by the decoding procedure.

NOTE — Not all the new symbols need to be exported; this allows the dictionary to define some a symbol, use it via refinement/aggregate coding to build other symbols, and not actually export the original symbol. Also, since input symbols can be exported, this dictionary can in effect copy symbols from other dictionaries.

6.5.6 Height class delta height

If **SDHUFF** is **1**, decode a value using the Huffman table specified by **SDHUFFDH**.

If **SDHUFF** is **0**, decode a value using the IADH integer arithmetic decoding procedure (see Annex A).

6.5.7 Delta width

If **SDHUFF** is **1**, decode a value using the Huffman table specified by **SDHUFFDW**.

If **SDHUFF** is **0**, decode a value using the IADW integer arithmetic decoding procedure (see Annex A).

In either case it is possible that the result of this decoding is the out-of-band value OOB.

6.5.8 Symbol bitmap

This field is only present if **SDHUFF** = **0** or **SDREFAGG** = **1**. This field takes one of two forms; **SDREFAGG** determines which form is used.

6.5.8.1 Direct-coded symbol bitmap

If **SDREFAGG** is **0** then decode the symbol's bitmap using a generic region decoding procedure as described in 6.2. Set the parameters to this decoding procedure as shown in Table 16.

6.5.8.2 Refinement/aggregate-coded symbol bitmap

If **SDREFAGG** is **1** then the symbol's bitmap is coded by refinement and aggregation of other, previously-defined, symbols. Decode the bitmap as follows.

1. Decode the number of symbol instances contained in the aggregation, as specified in 6.5.8.2.1. Let REFLAG-NINST be the value decoded.

Table 16 — Parameters used to decode a symbol’s bitmap using generic bitmap decoding.

Name	Value
MMR	0
GBW	SYMWIDTH
GBH	HCHEIGHT
GBTEMPLATE	SDTEMPLATE
TPGDON	0
USESKEEP	0
GBATX₁	SDATX₁
GBATY₁	SDATY₁
GBATX₂	SDATX₂
GBATY₂	SDATY₂
GBATX₃	SDATX₃
GBATY₃	SDATY₃
GBATX₄	SDATX₄
GBATY₄	SDATY₄

- If REFAGGNINST is greater than one, then decode the bitmap itself using a using a text region decoding procedure as described in 6.4. Set the parameters to this decoding procedure as shown in Table 17.
- If REFAGGNINST is equal to one, then decode the bitmap as described in 6.5.8.2.2.

6.5.8.2.1 Number of symbol instances in aggregation

If **SDHUFF** is **1**, decode a value using the Huffman table specified by **SDHUFFAGGNINST**.

If **SDHUFF** is **0**, decode a value using the IAAI integer arithmetic decoding procedure (see Annex A).

6.5.8.2.2 Decoding a bitmap when REFAGGNINST = 1

If a symbol’s bitmap is coded by refinement/aggregate coding, and there is only one symbol in the aggregation, then the bitmap is decoded as follows. This is essentially the procedure followed by the symbol region decoding procedure, except that when a value is known, it is not decoded.

- Set **SBHUFF** = **SDHUFF**.
- Decode a symbol ID as described in 6.4.10, using the values of SBSYMCODES and SBSYMCODELEN described in 6.5.8.2.3. Let ID_I be the value decoded.
- Decode the instance refinement X offset as described in 6.4.11.3. If **SDHUFF** is **1**, use Table B.15 for **SBHUFFRDX**. Let RDX_I be the value decoded.
- Decode the instance refinement Y offset as described in 6.4.11.4. If **SDHUFF** is **1**, use Table B.15 for **SBHUFFRDX**. Let RDY_I be the value decoded.
- If **SDHUFF** is **1** then
 - Decode the symbol instance refinement bitmap data size as described in 6.4.11.5, using Table B.1 for **SBHUFFRSIZE**.
 - Skip over any bits remaining in the last byte read.
- Let IBO_I be **SBSYMS**[ID_I], where SBSYMS is as shown in 6.5.8.2.4. The symbol’s bitmap is the result of applying the generic refinement region decoding procedure described in 6.3. Set the parameters to this decoding procedure as shown in Table 18.
- If **SBHUFF** is **1**, then skip over any bits remaining in the last byte read. The total number of bytes processed by the generic refinement region decoding procedure must be equal to the value read in step 5a.

Table 17 — Parameters used to decode a symbol's bitmap using refinement/aggregate decoding.

Name	Value
SBHUFF	SDHUFF
SBREFINE	1
SBW	SYMWIDTH
SBH	HCHEIGHT
SBNUMINSTANCES	REFAGGNINST
SBSTRIPS	1
SBNUMSYMS	SDNUMINSYMS + NSYMSDECODED
SBSYMCODES	See 6.5.8.2.3. *
SBSYMCODELEN	See 6.5.8.2.3. **
SBSYMS	See 6.5.8.2.4.
SBDEFPIXEL	0
SBCOMBOP	OR
TRANSPOSED	0
REFCORNER	TOPLEFT
SBDSOFFSET	0
SBHUFFFS	Table B.6 *
SBHUFFDS	Table B.8 *
SBHUFFDT	Table B.11 *
SBHUFFRDW	Table B.15 *
SBHUFFRDH	Table B.15 *
SBHUFFRDY	Table B.15 *
SBHUFFRDX	Table B.15 *
SBHUFFRDY	Table B.15 *
SBHUFFRSIZE	Table B.1 *
SBRTEMPLATE	SDRTEMPLATE
SBRATX₁	SDRATX₁
SBRATY₁	SDRATY₁
SBRATX₂	SDRATX₂
SBRATY₂	SDRATY₂

* If **SDHUFF** = **0** then this parameter has no value.

** If **SDHUFF** = **1** then this parameter has no value.

Table 18 — Parameters used to decode a symbol's bitmap when REFAGGNINST = 1

Name	Value
GRW	SYMWIDTH
GRH	HCHEIGHT
GRTEMPLATE	SDRTEMPLATE
GRREFERENCE	<i>IBO_I</i>
GRREFERENCEDX	<i>RDX_I</i>
GRREFERENCEDY	<i>RDY_I</i>
TPGRON	0
GRATX₁	SDRATX₁
GRATY₁	SDRATY₁
GRATX₂	SDRATX₂
GRATY₂	SDRATY₂

6.5.8.2.3 Setting SBSYMCODES and SBSYMCODELEN

When **SDHUFF** = 1, set **SBSYMCODES** to an array of **SBNUMSYMS** codes, where the length of each code is

$$\max([\log_2(\text{SDNUMINSYMS} + \text{SDNUMNEWSYMS})], 1)$$

and the code **SBSYMCODES**[*I*] is *I* (for *I* between 0 and **SBNUMSYMS** – 1).

NOTE — This sets the codes as equal-length codes, assigned starting from zero. The code lengths are computed from the maximum number of symbols available in this symbol dictionary: all the imported symbols and all the symbols defined here. There is some wastage in choosing this code length and assigning these codes. However, doing it this way means that neither the code lengths nor the actual codes assigned to each symbol changes during the process of decoding this symbol dictionary.

Similarly, when **SDHUFF** is 0, **SBSYMCODELEN** should be set to

$$[\log_2(\text{SDNUMINSYMS} + \text{SDNUMNEWSYMS})]$$

so that the length of the bit strings decoded using IAID will not change during the decoding of this symbol dictionary.

6.5.8.2.4 Setting SBSYMS

Set **SBSYMS** to an array of **SDNUMINSYMS** + **NSYMSDECODED** symbols, formed by concatenating the array **SDINSYMS** and the first **NSYMSDECODED** entries of the array **SDNEWSYMS**.

6.5.9 Height class collective bitmap

This field is only present if **SDHUFF** = 1 and **SDREFAGG** = 0.

This field contains the bitmaps of all the symbols in the height class, concatenated left to right, and MMR encoded. It is preceded by a count of its size in bytes.

This field is decoded as follows.

1. Read the size in bytes using the **SDHUFFBMSIZE** Huffman table. Let **BMSIZE** be the value decoded.
2. Skip over any bits remaining in the last byte read.
3. If **BMSIZE** is zero, then the bitmap is stored uncompressed, and the actual size in bytes is

$$\text{HCHEIGHT} \times \left\lceil \frac{\text{TOTWIDTH}}{8} \right\rceil$$

Decode the bitmap by reading this many bytes and treating it as **HCHEIGHT** rows of **TOTWIDTH** pixels, each row padded out to a byte boundary with 0–7 0 bits.

4. Otherwise, decode the bitmap using a generic bitmap decoding procedure as described in 6.2. Set the parameters to this decoding procedure as shown in Table 19.

Table 19 — Parameters used to decode a height class collective bitmap.

Name	Value
MMR	1
GBW	TOTWIDTH
GBH	HCHEIGHT

5. Skip over any bits remaining in the last byte read.

6.5.10 Exported symbols

The symbols that may be exported from a given dictionary include any of the symbols that are input to the dictionary, plus any of the symbols defined in the dictionary.

The array of symbols exported from the dictionary is produced by decoding an a bit for each of those symbols. These bits form an array EXFLAGS of $\text{SDNUMINSYMS} + \text{SDNUMNEWSYMS}$ binary values, each one corresponding to an input symbol or a newly-defined symbol. A **1** bit for a symbol indicates that the symbol is exported. Exactly SDNUMEXSYMS symbols must be exported from the dictionary. The order of exported symbols is the order produced by concatenating the array **SDINSYMS** and the array **SDNEWSYMS**.

The following procedure produces this array of exported symbols.

1. Set

$$\begin{aligned}\text{EXINDEX} &= 0 \\ \text{CUREXFLAG} &= 0\end{aligned}$$

2. Decode a value using Table B.1 if **SDHUFF** is **1**, or the IAEX integer arithmetic decoding procedure if **SDHUFF** is **0**. Let EXRUNLENGTH be the decoded value.
3. Set EXFLAGS[EXINDEX] through EXFLAGS[EXINDEX + EXRUNLENGTH - 1] to CUREXFLAG. If EXRUNLENGTH = 0, then this step does not change any values.
4. Set

$$\begin{aligned}\text{EXINDEX} &= \text{EXINDEX} + \text{EXRUNLENGTH} \\ \text{CUREXFLAG} &= \text{NOT}(\text{CUREXFLAG})\end{aligned}$$

5. Repeat steps 2 through 4 until EXINDEX = $\text{SDNUMINSYMS} + \text{SDNUMNEWSYMS}$.
6. The array EXFLAGS now contains **1** for each symbol that is exported from the dictionary, and **0** for each symbol that is not exported.
7. Set

$$\begin{aligned}I &= 0 \\ J &= 0\end{aligned}$$

8. For each value of I from 0 to $\text{SDNUMINSYMS} + \text{SDNUMNEWSYMS} - 1$, if EXFLAGS[I] = **1** then perform the following steps.

- (a) If $I < \text{SDNUMINSYMS}$ then set

$$\begin{aligned}\text{SDEXSYS}[J] &= \text{SDINSYS}[I] \\ J &= J + 1\end{aligned}$$

- (b) If $I \geq \text{SDNUMINSYMS}$ then set

$$\begin{aligned}\text{SDEXSYS}[J] &= \text{SDNEWSYS}[I - \text{SDNUMINSYMS}] \\ J &= J + 1\end{aligned}$$

NOTE — Most dictionaries will export exactly the new symbols that they define; they will not export any of the symbols in **SDINSYMS**. In this case, the first SDNUMINSYMS values in EXFLAGS are **0**, and the remaining SDNUMNEWSYMS values are **1**.

6.6 Halftone Region Decoding Procedure

6.6.1 General description

This decoding procedure is used to decode a bitmap by decoding an array of values, which are used to draw patterns into a halftone grid. These patterns are combined to form the decoded bitmap.

NOTE — This form of coding is suitable to efficiently transmitting a bitmap containing *periodic* halftone image data, such as clustered-dot ordered dithered data. Other forms of halftone image data, such as error-diffused data, may be converted into this form via descreening, or may be coded in a form more closely resembling the original using generic bitmap coding.

6.6.2 Input parameters

The parameters to this decoding procedure are shown in Table 20.

Table 20 — Parameters for the halftone region decoding procedure.

Name	Type	Size (bits)	Signed?	Description and restrictions
HBW	Integer	32	N	The width of the region.
HBH	Integer	32	N	The height of the region.
HMMR	Integer	1	N	Whether MMR coding is used.
HTEMPLATE	Integer	2	N	The template identifier. *
HNUMPATS	Integer	32	N	The number of patterns that may be used in this region.
HPATS	Array of patterns			An array containing the patterns used in this region. Contains HNUMPATS patterns.
HDEFPIXEL	Integer	1	N	The default pixel for this bitmap.
HCOMBOP	Operator			The combination operator used in this halftone region. May take on the values OR, AND, XOR, XNOR and REPLACE.
HENABLESKIP	Integer	1	N	Whether unneeded gray-scale values are skipped. *
HGW	Integer	32	N	The width of the gray-scale image.
HGH	Integer	32	N	The height of the gray-scale image.
HGX	Integer	32	Y	256 times the horizontal offset of the grid origin.
HGY	Integer	32	Y	256 times the vertical offset of the grid origin.
HRX	Integer	16	N	256 times the horizontal coordinate of the grid vector.
HRY	Integer	16	N	256 times the vertical coordinate of the grid vector.
HPW	Integer	8	N	The width of each pattern.
HPH	Integer	8	N	The height of each pattern.

* Unused if **HMMR** = 1.

6.6.3 Return value

The variable whose value is the result of this decoding procedure is shown in Table 21.

Table 21 — Return value from the halftone region decoding procedure.

Name	Type	Size (bits)	Signed?	Description and restrictions
HTREG	Bitmap			The decoded region bitmap.

6.6.4 Variables used in decoding

The variables used by this decoding procedure are shown in Table 22.

Table 22 — Variables used in the halftone region decoding procedure.

Name	Type	Size (bits)	Signed?	Description and restrictions
n_g	Integer	32	N	Horizontal index for the current gray-scale value.
m_g	Integer	32	N	Vertical index for the current gray-scale value.
x	Integer	32	Y	The horizontal coordinate for the pattern corresponding to the current gray-scale value.
y	Integer	32	Y	The vertical coordinate for the pattern corresponding to the current gray-scale value.
HSKIP	Bitmap			Skip mask. HSKIP is HGW by HGH pixels. *
HBPP	Integer	32	N	The number of bits per value in the array of gray-scale values.
GI	Array			Array of gray-scale values. GI is a HGW by HGH array, each entry of which is a HBPP bits unsigned integer.

*Unused if **HENABLESKIP** = 0.

6.6.5 Decoding the halftone region

A halftone-coded bitmap is represented by a set of pattern instances. Each instance encodes a pattern. The location of each pattern is not coded explicitly but given by a grid global to the entire halftone bitmap. The halftone grid origin is specified by parameters **HGX** and **HGY**. The grid period is defined by parameters **HRX** and **HRY** (see Fig. 24). **HGX**, **HGY**, **HRX** and **HRY** are scaled by 256, which means that the grid origin and grid period have a fractional part of 8 bits.

NOTE 1 — Note that **HRX** and **HRY** are unsigned values; that is, their values are always greater than or equal to zero. This means that the grid vector is restricted to lie in a single quadrant. Despite this restriction, any halftone grid can be encoded by a suitable adjustment of **HGX** and **HGY**: **HGX** and **HGY** must be set so that the grid's origin is the leftmost corner. This is the top left corner in the case where the grid is axis-aligned, or is a slight counter-clockwise rotation of an axis-aligned grid (as shown in Figure 24, and is the bottom left corner in the case where the grid is a slight clockwise rotation of an axis aligned grid.

The possible patterns are given in a dictionary. The identity of a pattern is specified by an index which will usually represent the gray-scale value of the pattern.

NOTE 2 — We use the term gray-scale value for the index to illustrate the compression idea. There is no requirement in this specification that the index does indeed correspond to the gray-scale value.

The result of decoding a halftone bitmap is the bitmap that is produced by the following steps.

1. Fill a bitmap HTREG, of the size given by **HBW** and **HBH**, with the **HDEFPIXEL** value.
2. If **HENABLESKIP** equals **1**, compute a bitmap HSKIP as shown in 6.6.5.1.
3. Set HBPP to $\lceil \log_2(\mathbf{HNUMPATS}) \rceil$.
4. Decode an image GI of size **HGW** by **HGH** with **HBPP** bits per pixel using the gray-scale image decoding procedure as described in Annex C. Set the parameters to this decoding procedure as shown in Table 23.

Let GI be the results of invoking this decoding procedure.

5. Place sequentially the patterns corresponding to the values in GI into HTREG by the procedure described in 6.6.5.2. The rendering procedure is illustrated in Figure 24. The outline of two patterns are marked by dotted boxes.

Bounding box for page




Figure 24 — Specification of coordinate systems and grid parameters.

Table 23 — Parameters used to decode a halftone region's gray-scale value array.

Name	Value
GSMR	HMMR
GSW	HGW
GSH	HGH
GSBPP	HBPP
GSUSESIP	HENABLESKIP
GSSKIP	HSKIP *
GSTEMPLATE	HTEMPLATE **

* If HENABLESKIP = **0** then this parameter has no value.

** If HMMR = **1** then this parameter has no value.

6. After all the patterns have been placed on the bitmap, the current contents of the halftone-coded bitmap are the results that shall be obtained by every decoder, whether it performs this exact sequence of steps or not.

NOTE 3 — If **HGX** is 0, **HGY** is 0, **HRX** is equal to **HPW** × 256 and **HRY** is 0, then the grid is simple: it is axis-aligned, the primary direction is horizontal, and the grid step is equal to the size of the patterns. In this case, it is possible to optimise the drawing process, as none of the patterns can overlap.

6.6.5.1 Computing HSKIP

The bitmap HSKIP contains **1** at a pixel if drawing a pattern at the corresponding location on the halftone grid does not affect any pixels of HTREG. It is computed as follows.

1. For each value of m_g between 0 and **HGH** − 1, beginning from 0, perform the following steps.
 - (a) For each value of n_g between 0 and **HGW** − 1, beginning from 0, perform the following steps.
 - i. Set

$$x = (\mathbf{HGX} + m_g \times \mathbf{HRY} + n_g \times \mathbf{HRX}) \gg_A 8$$

$$y = (\mathbf{HGY} + m_g \times \mathbf{HRX} - n_g \times \mathbf{HRY}) \gg_A 8$$

- ii. If $((x + \mathbf{HPW} \leq 0) \text{ OR } (x \geq \mathbf{HBW}) \text{ OR } (y + \mathbf{HPH} \leq 0) \text{ OR } (y \geq \mathbf{HBH}))$ then set

$$\mathbf{HSKIP}[n_g, m_g] = \mathbf{1}$$

Otherwise, set

$$\mathbf{HSKIP}[n_g, m_g] = \mathbf{0}$$

6.6.5.2 Rendering the patterns

Draw the patterns into HTREG using the following procedure.

1. For each value of m_g between 0 and **HGH** − 1, beginning from 0, perform the following steps.
 - (a) For each value of n_g between 0 and **HGW** − 1, beginning from 0, perform the following steps.
 - i. Set

$$x = (\mathbf{HGX} + m_g \times \mathbf{HRY} + n_g \times \mathbf{HRX}) \gg_A 8$$

$$y = (\mathbf{HGY} + m_g \times \mathbf{HRX} - n_g \times \mathbf{HRY}) \gg_A 8$$

- ii. Draw the pattern **HPATS**[GI[n_g, m_g]] into HTREG such that its upper left pixel is at location (x, y) in HTREG.

A pattern is drawn into HTREG as follows. Each pixel of the pattern shall be combined with the current value of the corresponding pixel in the halftone-coded bitmap, using the combination operator specified by **HCOMBOP**. The results of each combination shall be written into that pixel in the halftone-coded bitmap.

If any part of a decoded pattern, when placed at location (x, y) lies outside the actual halftone-coded bitmap, then this part of the pattern shall be ignored in the process of combining the pattern with the bitmap.

NOTE — The gray-scale image can be used by the decoder to get a good rendition of the halftone on a multi-level output device of limited spatial resolution such as a computer screen. The use of the gray-scale image for such purposes is outside the scope of this specification.

The gray-scale image is coded by bit-plane coding so the decoder will receive the gray-scale image progressively. Consequently, the decoder may render a halftoned image using the quantised gray-scale values as indices. Such intermediate halftoned images shall not influence the final halftone-coded bitmap.

6.7 Pattern Dictionary Decoding Procedure

6.7.1 General description

This decoding procedure is used to decode a set of fixed-size patterns; these patterns can then be used by halftone region decoding procedures.

6.7.2 Input parameters

The parameters to this decoding procedure are shown in Table 24.

Table 24 — Parameters for the pattern dictionary decoding procedure.

Name	Type	Size (bits)	Signed?	Description and restrictions
HDMMR	Integer	1	N	Whether MMR is used.
HDPW	Integer	32	N	The width of each pattern.
HDPH	Integer	32	N	The height of each pattern.
GRAYMAX	Integer	32	N	The largest gray-scale value for which a pattern is given.
HDTEMPLATE	Integer	2	N	The template used to code the patterns. *

*Unused if **HDMMR** = 1.

6.7.3 Return value

The variable whose value is the result of this decoding procedure is shown in Table 25.

Table 25 — Return value from the pattern dictionary decoding procedure.

Name	Type	Size (bits)	Signed?	Description and restrictions
HDPATS	Array of patterns			The patterns exported by this pattern dictionary. Contains GRAYMAX + 1 patterns.

6.7.4 Variables used in decoding

The variables used by this decoding procedure are shown in Table 26.

Table 26 — Variables used in the pattern dictionary decoding procedure.

Name	Type	Size (bits)	Signed?	Description and restrictions
GRAY	Integer	32	N	Gray-scale index.
B_{HDC}	Bitmap			The dictionary collective bitmap.
B_P	Bitmap			A bitmap of size HDPW by HDPH .

6.7.5 Decoding the pattern dictionary

The result of decoding a pattern dictionary is a set of patterns: $HDPATS[0] \dots HDPATS[GRAYMAX]$. These patterns shall be the patterns produced by the following steps.

1. Create a bitmap B_{HDC} . The height of this bitmap is **HDPH**. The width of the bitmap is $(GRAYMAX + 1) \times HDPW$. This bitmap contains all the patterns concatenated left to right.
2. Decode the collective bitmap using a generic region decoding procedure as described in 6.2. Set the parameters to this decoding procedure as shown in Table 27.

Table 27 — Parameters used to decode a pattern dictionary's collective bitmap.

Name	Value
MMR	HDMMR
GBW	$(GRAYMAX + 1) \times HDPW$
GBH	HDPH
GBTEMPLATE	HDTEMPLATE *
TPGDON	0 *
USESIP	0
GBATX₁	-HDPW *
GBATY₁	0 *
GBATX₂	-3 **
GBATY₂	-1 **
GBATX₃	2 **
GBATY₃	-2 **
GBATX₄	-2 **
GBATY₄	-2 **

* If **HDMMR** = 1 then this parameter has no value.

** If **HDMMR** = 1 or **HDTEMPLATE** $\neq 0$ then this parameter has no value.

3. Set

$$GRAY = 0$$

4. While $GRAY \leq GRAYMAX$,

- (a) Let the subimage of B_{HDC} consisting of **HDPH** rows and columns $HDPW \times GRAY$ through $HDPW \times (GRAY + 1) - 1$ be denoted B_P . Set

$$HDPATS[GRAY] = B_P$$

- (b) Set

$$GRAY = GRAY + 1$$

7 Control Decoding Procedure

7.1 General description

This decoding procedure controls the invocation of all the other decoding procedure. The encoded bitstream consists of a collection of segments, each containing a part of the data necessary for decoding. There are several different types of segments.

A segment has two parts: a segment header part and a segment data part. All types of segments use a common format for the segment header, but different formats for segment data.

Some segments give information about the structure of the document: start of page, end of page, and so on. Some segments code regions, used in turn to produce the decoded image of a certain page. Some segments (“dictionary segments”) do neither, but instead define resources that can be used by segments that code regions.

A segment can be associated with some page, or not associated with any page. A segment can refer to other, preceding, segments. A segment also includes retention bits for the segment that it refers to, and for itself; these indicate when the decoder may discard the data created by decoding a segment.

EXAMPLE — A text region segment may make use of symbols defined in preceding symbol dictionary segments. This is indicated by the text region’s segment header referring to those symbol dictionary segments.

The format of segment headers is described in 7.2. The types of segments are defined in 7.3. The syntax of each type of segment is defined in 7.4.

In the following, some references are made to “preceding” and “following” segments (and other indications implying an order of segments). These terms are defined with reference to the order imposed on the segments by their segment numbers: a segment precedes all segments whose segment numbers are larger than its segment number.

NOTE — It is possible for there to be gaps in the segment numbering. A JBIG2 file might contain segments numbered 2, 3, 4, 8, and 10. This can occur due to editing: the segment numbers might originally have been contiguous, but at some point in the life of the file some pages were deleted and the remaining segments not renumbered.

A segment’s header part always begins and ends on a byte boundary.

A segment’s data part always begins and ends on a byte boundary. Any unused bits in the final byte of a segment must contain 0, and shall not be examined by the decoder.

The segment header part and the segment data part of a segment need not occur contiguously in the bitstream being decoded. See Annex D for an organisation where the segment header part of a segment may be stored at some distance from the segment data part of that segment.

This clause contains figures that describe various parts of the encoded data, such as Figures 25 and 31. These conventions used in these figures are

- The first byte encountered in the bitstream is at the left end.
- Fields whose sizes are fixed, and that are always present, are outlined with narrow lines.
- Fields whose sizes are not fixed, or that are not present in all cases, or whose structures are fully described elsewhere, are outlined with heavy lines.
- Some figures (such as Figure 25) are divided into fields, each of which is an integral number of bytes long. In these figures, hash marks extending down from the top of the figure denote byte boundaries, and fields are separated by lines running the full height of the figure.
- The remaining figures are divided into fields, each of which is an integral number of bits long, making up an integral number of bytes. In these figures, short hash marks extending up from the bottom of the figure show bit boundaries. Fields are separated by longer hash marks extending up from the bottom of the figure. Each bit’s number is shown below the figure.

7.2 Segment header syntax

7.2.1 Segment header fields

A segment header contains the fields shown in Figure 25 and described below.




Figure 25 — Segment header structure

Segment number See 7.2.2.

Segment header flags See 7.2.3.

Referred-to segment count and retention flags See 7.2.4.

Referred-to segment number fields See 7.2.5.

Segment page association See 7.2.6.

Segment data length See 7.2.7.

7.2.2 Segment number

This four-byte field contains the segment's segment number.

7.2.3 Segment header flags

This is a 1-byte field. The bits that are defined are shown in Figure 26 and are described below.




Figure 26 — Segment header flags

Bits 0–5 Segment type. See 7.3.

Bit 6 Page association field size. See 7.2.6.

Bit 7 Deferred non-retain. If this bit is **1**, this segment is flagged as retained only by itself and its attached extension segments, and is flagged as non-retained by the last attached extension segments. An extension segment is an attached extension segment when it refers to only one segment, and the only segments (if any) between it and that referred-to segment are other extension segments also referring only to that referred-to segment.

NOTE — The intention of this bit is to indicate to the decoder that the segment is only referred to by a small number of extension segments. The decoder may take some expensive actions when segments are flagged as retained, but if this retention is only for the benefit of the segment's attached extension segments, these actions may not be necessary. Knowing this in advance is helpful.

7.2.4 Referred-to segment count and retention flags

This field contains one or more bytes indicating how many other segments are referred to by this segment, and which segments contain data that is needed after this segment.

NOTE — The decoder’s memory requirements can be reduced by letting it know when it is allowed to forget about the data represented by some previous segment.

The number of bytes in this field depends on the number of segments referred to by this segment. If this segment refers to four or fewer segments, then this field is one byte long. If this segment refers to more than four segments, then this field is $4 + \lceil (R + 1) / 8 \rceil$ bytes long where R is the number of segments that this segment refers to.

EXAMPLE — If this segment refers to between five and seven other segments, then the field is five bytes long; if it refers to between eight and fifteen other segments, then the field is six bytes long.

The three most significant bits of the first byte in this field determine the length of the field. If the value of this three-bit subfield is between 0 and 4, then the field is one byte long. If the value of this three-bit subfield is 7, then the field is at least five bytes long. This three-bit subfield must not contain values of 5 and 6.

In the case where the field is one byte long, that byte is formatted as shown in Figure 27 and as described below.




Figure 27 — Referred-to segment count and retention flags — short form

Bit 0 Retain bit for this segment.

Bit 1 Retain bit for the first referred-to segment. If this segment refers to no other segments, this field must contain 0.

Bit 2 Retain bit for the second referred-to segment. If this segment refers to fewer than two other segments, this field must contain 0.

Bit 3 Retain bit for the third referred-to segment. If this segment refers to fewer than three other segments, this field must contain 0.

Bit 4 Retain bit for the fourth referred-to segment. If this segment refers to fewer than four other segments, this field must contain 0.

Bits 5–7 Count of referred-to segments. This field may take on values between zero and four. This specifies the number of segments that this segment refers to.

In the case where the field is in the long format (at least five bytes long), it is composed of an initial four-byte field, followed by a succession of one-byte fields. The initial four-byte field is formatted as follows.

Bits 0–28 Count of referred-to segments. This specifies the number of segments that this segment refers to.

Bits 29–31 Indication of long-form format. This field must contain the value 7.

The first one-byte field following the initial four-byte field is formatted as follows.

Bit 0 Retain bit for this segment.

Bit 1 Retain bit for the first referred-to segment.

Bit 2 Retain bit for the second referred-to segment.

Bit 3 Retain bit for the third referred-to segment.

Bit 4 Retain bit for the fourth referred-to segment.

Bit 5 Retain bit for the fifth referred-to segment. If this segment refers to fewer than five other segments, this field must contain **0**.

Bit 6 Retain bit for the sixth referred-to segment. If this segment refers to fewer than six other segments, this field must contain **0**.

Bit 7 Retain bit for the seventh referred-to segment. If this segment refers to fewer than seven other segments, this field must contain **0**.

The second one-byte field, if present, contains retain bits for the eighth through fifteenth referred-to segments; the bits corresponding to any segments beyond the count of segments actually referred to must be **0**. Succeeding one-byte fields are formatted similarly.

If the retain bit for this segment value is **0**, then no segment may refer to this segment.

If the retain bit for the first referred-to segment value is **0**, then no segment after this one may refer to the first segment that this segment refers to (i.e., this segment is the last segment that refers to that other segment). Further retain bit values have similar meanings: if the retain bit for the Kth referred-to segment value is **0**, then no segment after this one may refer to the Kth segment that this segment refers to.

7.2.5 Referred-to segment numbers

This field contains the segment numbers of the segments that this segment refers to, if any. The number of values in this field is determined by the referred-to segment count and retention flags field. Each value is the segment number of a segment that this segment refers to. A segment may refer to only segments with lower segment numbers. When the current segment's number is 256 or less, then each referred-to segment number is one byte long. Otherwise, when the current segment's number is 65536 or less, each referred-to segment number is two bytes long. Otherwise, each referred-to segment number is four bytes long.

7.2.6 Segment page association

This field encodes the number of the page to which this segment belongs. The first page must be numbered "1". This field may contain a value of zero; this value indicates that this segment is not associated with any page.

A segment that has a non-zero segment page association may only be referred to by segments having the same segment page association value as it.

This field is one byte long if this segment's page association field size flag bit is **0**, and is four bytes long if this segment's page association field size flag bit is **1**.

NOTE — Most documents have fewer than 256 pages, so this field has a short form that can hold values from 0 to 255 in a single byte. The page association field for unassociated segments can also be only a single byte long.

7.2.7 Segment data length

This 4-byte field contains the length of the segment's segment data part, in bytes.

If the segment's type is "Immediate generic region", then the length field may contain the value `0xFFFFFFFF`. This value is intended to mean that the length of the segment's data part is unknown at the time that the segment header is written (for example in a streaming application such as facsimile). In this case, the true length of the segment's data part shall be determined through examination of the data: if the segment uses template-based arithmetic coding, then the segment's data part ends with the two-byte sequence `0xFF 0xAC` followed by a four-byte row count. If the segment uses MMR coding, then the segment's data part ends with the two-byte sequence `0x00 0x00` followed by a four-byte row count. The form of encoding used by the segment may be determined by examining the eighteenth byte of its segment data part, and the end sequences can occur anywhere after that eighteenth byte.

NOTE — Given a list of segment headers in the random-access organisation (see Figure D.2), a decoder can build a map of the rest of the file by knowing the length of the data associated with each segment. This allows it to perform random access.

7.2.8 Segment header example

EXAMPLE 1 — A segment header consisting of the sequence of bytes

```
0x00 0x00 0x00 0x20 0x86 0x6B 0x02 0x1E 0x05 0x04
```

is parsed as follows

0x00 0x00 0x00 0x20 This segment's number is 0x00000020, or 32 decimal.

0x86 This segment's type is 6. Its page association field is one byte long. It is retained by only its attached extension segments.

0x6B This segment refers to three other segments. It is referred to by some other segment. This is the last reference to the second of the three segments that it refers to.

0x02 0x1E 0x05 The three segments that it refers to are numbers 2, 30, and 5.

0x04 This segment is associated with page number 4.

EXAMPLE 2 — A segment header consisting of the sequence of bytes, in hexadecimal

```
00 00 02 34 40 E0 00 00 09 02 FD 01 00 00 02 00  
1E 00 05 02 00 02 01 02 02 02 03 02 04 00 00 04  
01
```

is parsed as follows

00 00 02 34 This segment's number is 0x00000234, or 564 decimal.

40 This segment's type is 0. Its page association field is four bytes long.

E0 00 00 09 This segment's referred-to segment count field is in the long format. This segment refers to nine other segments.

02 FD This segment is referred to by some other segment. This is the last reference to the first and eighth of the nine segments that it refers to.

01 00 . . . 02 04 The nine segments that it refers to are each identified by two bytes, since this segment's number is between 256 and 65535. The segments that it refers to are, in decimal, numbers 256, 2, 30, 5, 512, 513, 514, 515, and 516.

00 00 04 01 This segment is associated with page number 1025.

7.3 Segment types

Each segment has a certain type. This type specifies the type of the data associated with the segment. This type restricts which other segments it may refer to, and which other segments may refer to it. These restrictions are detailed in 7.3.1.

The segment type is a number between 0 and 63, inclusive. Not all values are allowed. The allowed list of segment types, their full names, and where their formats are defined, are:

0 Symbol dictionary — see 7.4.2.

4 Intermediate text region — see 7.4.3.

6 Immediate text region — see 7.4.3.

- 7 Immediate lossless text region — see 7.4.3.
- 16 Pattern dictionary — see 7.4.4.
- 20 Intermediate halftone region — see 7.4.5.
- 22 Immediate halftone region — see 7.4.5.
- 23 Immediate lossless halftone region — see 7.4.5.
- 36 Intermediate generic region — see 7.4.6.
- 38 Immediate generic region — see 7.4.6.
- 39 Immediate lossless generic region — see 7.4.6.
- 40 Intermediate generic refinement region — see 7.4.7.
- 42 Immediate generic refinement region — see 7.4.7.
- 43 Immediate lossless generic refinement region — see 7.4.7.
- 48 Page information — see 7.4.8.
- 49 End of page — see 7.4.9.
- 50 End of stripe — see 7.4.10.
- 51 End of file — see 7.4.11.
- 52 Profiles — see 7.4.12.
- 53 Tables — see 7.4.13.
- 62 Extension — see 7.4.14.

All other segment types are reserved and must not be used.

NOTE — These segment numbers are allocated according to the following rules. The two high-order bits (bits 4–5) of this number specify the primary type of the segment, and the four low-order (bits 0–3) bits specify the secondary type of the segment.

The primary types are:

- 0 Symbol bitmap data
- 1 Halftone bitmap data
- 2 Generic bitmap data
- 3 Metadata

Primary types 0–2 are collectively referred to as region types.

For the region types, the interpretation of the four low-order bits is

Bit 0 If this bit is **1**, it indicates that the segment makes some region of the page lossless.

Bit 1 If this bit is **1**, it indicates that the segment can be drawn immediately into the page bitmap.
If this bit is **0**, it indicates that the segment is an intermediate segment. See 8.2.

Bits 2–3 These two bits define a subtype of the primary type:

- 0 Dictionary
- 1 Direct Region
- 2 Refinement Region

For metadata, the interpretations of the four low-order bits are:

- 0** Page information
- 1** End of page
- 2** End of stripe
- 3** End of file
- 4** Profiles
- 5** Tables
- 6–13** Reserved
- 14** Extension
- 15** Reserved

The segments of types “intermediate text region”, “immediate text region”, “immediate lossless text region”, “intermediate halftone region”, “immediate halftone region”, “immediate lossless halftone region”, “intermediate generic region”, “immediate generic region”, “immediate lossless generic region”, “intermediate generic refinement region”, “immediate generic refinement region”, and “immediate lossless generic refinement region” are collectively referred to as “region segments”.

The segments of types “intermediate text region”, “immediate text region”, “immediate lossless text region”, “intermediate halftone region”, “immediate halftone region”, “immediate lossless halftone region”, “intermediate generic region”, “immediate generic region”, and “immediate lossless generic region”, are collectively referred to as “direct region segments”.

The segments of types “intermediate text region”, “intermediate halftone region”, “intermediate generic region”, and “intermediate generic refinement region” are collectively referred to as “intermediate region segments”.

The segments of types “immediate text region”, “immediate lossless text region”, “immediate halftone region”, “immediate lossless halftone region”, “immediate generic region”, “immediate lossless generic region”, “immediate generic refinement region”, and “immediate lossless generic refinement region” are collectively referred to as “immediate region segments”.

The segments of types “intermediate generic refinement region”, “immediate generic refinement region” and “immediate lossless generic refinement region” are collectively referred to as “refinement region segments”.

7.3.1 Rules for segment references

The rules for segment references are as follows.

- An intermediate region segment may only be referred to by one other non-extension segment; it may be referred to by any number of extension segments.
- A segment of type “symbol dictionary” (type 0) may refer to any number of segments of type “symbol dictionary” and to up to four segments of type “tables”.
- A segment of type “intermediate text region”, “immediate text region” or “immediate lossless text region” (type 4, 6 or 7) may refer to any number of segments of type “symbol dictionary” and to up to eight segments of type “tables”.
- A segment of type “pattern dictionary” (type 16) must not refer to any other segment.
- A segment of type “intermediate halftone region”, “immediate halftone region” or “immediate lossless halftone region” (type 20, 22 or 23) must refer to exactly one segment, and this segment must be of type “pattern dictionary”.
- A segment of type “intermediate generic region”, “immediate generic region” or “immediate lossless generic region” (type 36, 38 or 37) must not refer to any other segment.
- A segment of type “intermediate generic refinement region” (type 40) must refer to exactly one other segment. This other segment must be an intermediate region segment.

- A segment of type “immediate generic refinement region” or “immediate lossless generic refinement region” (type 42 or 43) may refer to either zero other segments or exactly one other segment. If it refers to one other segment then that segment must be an intermediate region segment.
- A segment of type “page information” (type 48) must not refer to any other segments.
- A segment of type “end of page” (type 49) must not refer to any other segments.
- A segment of type “end of stripe” (type 50) must not refer to any other segments.
- A segment of type “end of file (type 51) must not refer to any other segments.
- A segment of type “profiles” (type 52) must not refer to any other segments.
- A segment of type “tables” (type 53) must not refer to any other segments.
- A segment of type “extension” (type 62) may refer to any number of segments of any type, unless the extension segment’s type imposes some restriction.

7.3.2 Rules for page associations

Every region segment must be associated with some page (i.e., have a non-zero page association field). “Page information”, “end of page” and “end of stripe” segments must be associated with some page. “End of file” segments must not be associated with any page. Segments of other types may be associated with a page or not.

If a segment is not associated with any page, then it must not refer to any segment that is associated with any page.

If a segment is associated with a page, then it may refer to segments that are not associated with any page, and to segments that are associated with the same page. It must not refer to any segment that is associated with a different page.

7.4 Segment syntaxes

This section describes in detail the syntax of the segment data part of each type of segment, and how it is to be decoded.

7.4.1 Region segment information field

Every region segment’s data part begins with a region segment information field; its format is specified here. A region segment information field contains the following subfields, as shown in Figure 28 and as described below.

Region segment bitmap width	Region segment bitmap height	Region segment bitmap X location	Region segment bitmap Y location	Region segment flags
--------------------------------	---------------------------------	-------------------------------------	-------------------------------------	----------------------------

Figure 28 — Region segment data header structure

Region segment bitmap width See 7.4.1.1.

Region segment bitmap height See 7.4.1.2.

Region segment bitmap X location See 7.4.1.3.

Region segment bitmap Y location See 7.4.1.4.

Region segment flags See 7.4.1.5

7.4.1.1 Region segment bitmap width

This four-byte field gives the width in pixels of the bitmap encoded in this segment.

7.4.1.2 Region segment bitmap height

This four-byte field gives the height in pixels of the bitmap encoded in this segment.

7.4.1.3 Region segment bitmap X location

This four-byte field gives the horizontal offset in pixels of the bitmap encoded in this segment relative to the page bitmap.

7.4.1.4 Region segment bitmap Y location

This four-byte field gives the vertical offset in pixels of the bitmap encoded in this segment relative to the page bitmap.

7.4.1.5 Region segment flags

This one-byte field is formatted as shown in Figure 29 and as described below.




Figure 29 — Region segment flags field structure

Bits 0–2 External combination operator. This three-bit field can take on the following values, representing one of five possible combination operators:

- 0 OR
- 1 AND
- 2 XOR
- 3 XNOR
- 4 REPLACE

NOTE 1 — These operators describe how the segment’s bitmap is to be combined with the page bitmap. REPLACE is intended to be used by refinement regions, where the refined region replaces the region it’s refining. Operators such as AND can be used for masking, where a portion of the page bitmap that already contains data is to be cleared so that another bitmap can be written there — think of writing a bitmap through a mask.

NOTE 2 — Intermediate region segments are never combined directly with the page, and so their location and external combination operators are not used. However, these values can still be useful: if a decoder wishes to draw a version of the page before all segments have been decoded (for progressive build-up), then it might want to render intermediate segments; setting the location and external combination according to how the final refinement of that intermediate segment will be combined with the page can help the decoder produce a useful sequence of progressive refinements of the page.

Bits 3–7 Reserved; must be 0.

In other words, this region segment information field describes the size and location of the bitmap encoded in this segment.

EXAMPLE — If the size and location values are (in order) 100, 200, 50 and 75, then this segment describes a bitmap 100 pixels wide, 200 pixels high, whose top left corner is 50 pixels to the right of, and 75 pixels below, the page’s top left corner.

7.4.2 Symbol dictionary segment syntax

7.4.2.1 Symbol dictionary segment data header

A symbol dictionary segment's data part begins with a symbol dictionary segment data header, containing the fields shown in Figure 30 and described below.




Figure 30 — Symbol dictionary segment data header structure

Symbol dictionary flags See 7.4.2.1.1.

Symbol dictionary AT flags See 7.4.2.1.2.

Symbol dictionary refinement AT flags See 7.4.2.1.3.

SDNUMEXSYMS See 7.4.2.1.4.

SDNUMNEWSYMS See 7.4.2.1.5.

7.4.2.1.1 Symbol dictionary flags

This two-byte field is formatted as shown in Figure 31 and as described below.




Figure 31 — Symbol dictionary flags field structure

Bit 0 SDHUFF

If this bit is **1**, then the segment uses the Huffman encoding variant. If this bit is **0**, then the segment uses the arithmetic encoding variant. The setting of this flag determines how the data in this segment are encoded, and may also modify the order in which some of the data are encoded.

Bit 1 SDREFAGG

If this bit is **0**, then no refinement or aggregate coding is used in this segment. If this bit is **1**, then every symbol bitmap is refinement/aggregate coded.

Bits 2–3 SDHUFFDH selection. This two-bit field can take on one of three values, indicating which table is to be used for **SDHUFFDH**.

0 Table B.4

1 Table B.5

3 User-supplied table

The value 2 is not permitted.

If **SDHUFF** is **0** then this field must contain the value 0.

Bits 4–5 SDHUFFDW selection. This two-bit field can take on one of three values, indicating which table is to be used for **SDHUFFDW**.

- 0 Table B.2
- 1 Table B.3
- 3 User-supplied table

The value 2 is not permitted.

If **SDHUFF** is **0** then this field must contain the value **0**.

Bit 6 SDHUFFBMSIZE selection.

If this field is **0** then Table B.1 is used for **SDHUFFBMSIZE**. If this field is **1** then a user-supplied table is used for **SDHUFFBMSIZE**.

If **SDHUFF** is **0** then this field must contain the value **0**.

Bit 7 SDHUFFAGGINST selection.

If this field is **0** then Table B.1 is used for **SDHUFFAGGINST**. If this field is **1** then a user-supplied table is used for **SDHUFFAGGINST**.

If **SDHUFF** is **0** or **SDREFAGG** is **0** then this field must contain the value **0**.

Bit 8 Bitmap coding context used.

If **SDHUFF** is **1** and **SDREFAGG** is **0** then this field must contain the value **0**.

Bit 9 Bitmap coding context retained.

If **SDHUFF** is **1** and **SDREFAGG** is **0** then this field must contain the value **0**.

Bits 10–11 SDTEMPLATE

This field controls the template used to decode symbol bitmaps if **SDHUFF** is **0**. If **SDHUFF** is **1**, this field must contain the value **0**.

Bit 12 SDRTEMPLATE

This field controls the template used to decode symbol bitmaps if **SDREFAGG** is **1**. If **SDREFAGG** is **0**, this field must contain the value **0**.

Bits 13–15 Reserved; must be **0**.

7.4.2.1.2 Symbol dictionary AT flags

This field is only present if **SDHUFF** is **0**. If **SDTEMPLATE** is **0**, it is an eight-byte field, formatted as shown in Figure 32 and as described below.




Figure 32 — Symbol dictionary AT flags field structure when SDTEMPLATE is 0

Byte 0 SDATX₁

Byte 1 SDATY₁

Byte 2 SDATX₂

Byte 3 SDATY₂

Byte 4 SDATX₃

Byte 5 SDATY₃

Byte 6 SDATX₄

Byte 7 SDATY₄

If **SDTEMPLATE** is 1, 2 or 3, it is a two-byte field formatted as shown in Figure 33 and as described below.




Figure 33 — Symbol dictionary AT flags field structure when SDTEMPLATE is not 0

Byte 0 SDATX₁

Byte 1 SDATY₁

If **SDTEMPLATE** is 1, 2 or 3 then the values of **SDATX₂** through **SDATX₄** and **SDATY₂** through **SDATY₄** are all zero.

The AT coordinate X and Y fields are signed values, and may take on values that are permitted according to Figure 7.

7.4.2.1.3 Symbol dictionary refinement AT flags

This field is only present if **SDREFAGG** is **1** and **SDRTEMPLATE** is **0**. It is a four-byte field, formatted as shown in Figure 34 and as described below.




Figure 34 — Symbol dictionary refinement AT flags field structure

Byte 0 SDRATX₁

Byte 1 SDRATY₁

Byte 2 SDRATX₂

Byte 3 SDRATY₂

The AT coordinate X and Y fields are signed values, and may take on values that are permitted according to 6.3.5.3.

7.4.2.1.4 Number of exported symbols (SDNUMEXSYMS)

This four-byte field contains the number of symbols exported from this dictionary.

It is very useful for the decoder be able to find out easily how many symbols are present — for example, it might want to allocate an array of structures before beginning to decode the dictionary.

7.4.2.1.5 Number of new symbols (SDNUMNEWSYMS)

This four-byte field contains the number of symbols defined in this dictionary.

NOTE — **SDNUMEXSYMS** and **SDNUMNEWSYMS** are often, but not always, the same value. For example, if a dictionary re-exports some of the symbols that it imported from dictionaries that it refers to, then the dictionary effectively copies those symbols. Those symbols are reflected in **SDNUMEXSYMS** but not in **SDNUMNEWSYMS**. Another possible source of difference comes from the possibility that a dictionary defines some symbols that it does not export.

7.4.2.1.6 Symbol dictionary segment Huffman table selection

Set the values of the parameters **SDHUFFDH**, **SDHUFFDW**, **SDHUFFBMSIZE** and **SDHUFFAGGINST** according to the selection fields shown in 7.4.2.1.1, and the tables segments referred to by this segment. More precisely, of these four Huffman tables, some may be specified to use some standard table, and some may be specified to use a user-supplied table. The number specified to use a user-supplied table must be equal to the number of tables segments referred to by this segment. These tables segments are matched up with the Huffman tables using user-supplied tables according to the order in which the tables segments are referred to, and the order

1. **SDHUFFDH**
2. **SDHUFFDW**
3. **SDHUFFBMSIZE**
4. **SDHUFFAGGINST**

If a user-specified table is used for **SDHUFFDW**, then this table must be capable of coding the out-of-band value OOB. If a user-specified table is used for **SDHUFFDH**, **SDHUFFBMSIZE** or **SDHUFFAGGINST**, then this table must not be capable of coding the out-of-band value OOB.

EXAMPLE — If **SDHUFFDH** and **SDHUFFAGGINST** are specified to use user-supplied tables, and **SDHUFFDW** and **SDHUFFBMSIZE** are specified to use standard tables (Table B.2 and Table B.1 respectively), then this segment must refer to exactly two tables segments; the tables segment that is referred to first is used for **SDHUFFDH** and the tables segment that is referred to second is used for **SDHUFFAGGINST**.

7.4.2.2 Decoding a symbol dictionary segment

A symbol dictionary segment is decoded according to the following steps.

1. Interpret its header, as described in 7.4.2.1.
2. Decode (or retrieve the results of decoding) any referred-to symbol dictionary and tables segments.
3. If the “bitmap coding context used” bit in the header was **1**, then, as described in E.3.8, set the arithmetic coding statistics for the generic region and generic refinement region decoding procedures to the values that they contained at the end of decoding the last-referred-to symbol dictionary segment. That symbol dictionary segment’s symbol dictionary segment data header must have had the “bitmap coding context retained” bit equal to **1**. The values of **SDHUFF**, **SDREFAGG**, **SDTEMPLATE**, **SDRTEMPLATE**, and all of the AT locations (both direct and refinement) for this symbol dictionary must match the corresponding values from the symbol dictionary whose context values are being used.
4. If the “bitmap coding context used” bit in the header was **0**, then, as described in E.3.7, reset all the arithmetic coding statistics for the generic region and generic refinement region decoding procedures to zero.
5. Reset the arithmetic coding statistics for all the contexts of all the arithmetic integer coders to zero.
6. Invoke the symbol dictionary decoding procedure described in 6.5, with the parameters to the symbol dictionary decoding procedure set as shown in Table 28.
7. If the “bitmap coding context retained” bit in the header was **1**, then, as described in E.3.8, preserve the current contents of the arithmetic coding statistics for the generic region and generic refinement region decoding procedures.

NOTE — Step 3 is intended to reduce the coding costs of symbol dictionaries. A side-effect of decoding a symbol dictionary is that the arithmetic coding statistics used for coding bitmaps “learn” the approximate statistics of the symbols in that symbol dictionary. These two steps allow some limited re-use of these statistics: the statistics learned when decoding

Table 28 — Parameters used to decode a symbol dictionary segment.

Name	Value
SDHUFF	As shown in 7.4.2.1.1.
SDREFAGG	As shown in 7.4.2.1.1.
SDNUMINSYMS	The total number of exported symbols from all the symbol dictionary segments referred to by this segment.
SDINSYMS	Concatenate the exported symbol arrays from all the symbol dictionary segments referred to by this segment, in the order in which they are referred to.
SDNUMNEWSYMS	As shown in 7.4.2.1.5.
SDNUMEXSYMS	As shown in 7.4.2.1.4.
SDHUFFDH	See 7.4.2.1.6
SDHUFFDW	See 7.4.2.1.6
SDHUFFBMSIZE	See 7.4.2.1.6
SDHUFFAGGINST	See 7.4.2.1.6
SDTEMPLATE	See 7.4.2.1.1
SDATX₁	See 7.4.2.1.2
SDATY₁	See 7.4.2.1.2
SDATX₂	See 7.4.2.1.2
SDATY₂	See 7.4.2.1.2
SDATX₃	See 7.4.2.1.2
SDATY₃	See 7.4.2.1.2
SDATX₄	See 7.4.2.1.2
SDATY₄	See 7.4.2.1.2
SDRTEMPLATE	See 7.4.2.1.1
SDRATX₁	See 7.4.2.1.3
SDRATY₁	See 7.4.2.1.3
SDRATX₂	See 7.4.2.1.3
SDRATY₂	See 7.4.2.1.3

the symbol dictionary that is the last symbol dictionary referred to are used as a starting point for decoding this symbol dictionary.

Step 7 is explicitly present because not every symbol dictionary’s arithmetic coding statistics will be used by another dictionary. Knowing that they will not be used allows the decoder to discard them, reducing memory usage.

7.4.3 Text region segment syntax

The data parts of all three of the text region segment types (“intermediate text region”, “immediate text region” and “immediate lossless text region”) are coded identically, but are acted upon differently; see 8.2. The syntax of these segment types’ data parts is specified here.

7.4.3.1 Text region segment data header

The data part of a text region segment begins with a text region segment data header. This header contains the fields shown in Figure 35 and described below.




Figure 35 — Text region segment data header structure

Region segment information field See 7.4.1.

Text region segment flags See 7.4.3.1.1.

Text region segment Huffman flags See 7.4.3.1.2.

Text region segment refinement AT flags See 7.4.3.1.3.

SBNUMINSTANCES See 7.4.3.1.4.

Text region segment symbol ID Huffman decoding table See 7.4.3.1.5.

7.4.3.1.1 Text region segment flags

This two-byte field is formatted as shown in Figure 36 and as described below.




Figure 36 — Text region flags field structure

Bit 0 SBHUFF.

If this bit is **1**, then the segment uses the Huffman encoding variant. If this bit is **0**, then the segment uses the arithmetic encoding variant. The setting of this flag determines how the data in this segment are encoded.

Bit 1 SBREFINE.

If this bit is **0**, then the segment contains no symbol instance refinements. If this bit is **1**, then the segment may contain symbol instance refinements.

Bits 2–3 LOGSBSTRIPS.

This two-bit field codes the base-2 logarithm of the strip size used to encode the segment. Thus, strip sizes of 1, 2, 4, and 8 can be encoded.

Bits 4–5 REFCORNER. The four values that this two-bit field can take on are

- 0 BOTTOMLEFT.
- 1 TOPLEFT.
- 2 BOTTOMRIGHT.
- 3 TOPRIGHT.

NOTE — The best compression is usually achieved when the reference point of each symbol is on the text baseline. Given that text can run in any of eight directions, there needs to be some flexibility in which corner of a given symbol is used as the reference point.

Bit 6 TRANSPOSED.

If this bit is **1**, then the primary direction of coding is top-to-bottom. If this bit is **0**, then the primary direction of coding is left-to-right. This allows for text running up and down the page.

Bits 7–8 SBCEMBOP. This field has four possible values, representing one of four possible combination operators:

- 0 OR
- 1 AND
- 2 XOR
- 3 XNOR

Bit 9 SBDEFPIXEL.

This bit contains the initial value for every pixel in the text region, before any symbols are drawn.

Bits 10–14 SBDSOFFSET.

This signed five-bit field contains the value of **SBDSOFFSET** — see 6.4.8.

Bit 15 SBRTEMPLATE

This field controls the template used to decode symbol instance refinements if **SBREFINE** is **1**. If **SBREFINE** is **0**, this field must contain the value **0**.

7.4.3.1.2 Text region segment Huffman flags

This field is only present if **SBHUFF** is **1**.

This two-byte field is formatted as shown in Figure 37 and as described below.




Figure 37 — Text region Huffman flags field structure

Bits 0–1 SBHUFFFS selection. This two-bit field can take on one of three values, indicating which table is to be used for **SBHUFFFS**.

- 0 Table B.6
- 1 Table B.7
- 3 User-supplied table

The value 2 is not permitted.

Bits 2–3 SBHUFFDS selection. This two-bit field can take on one of four values, indicating which table is to be used for **SBHUFFDS**.

- 0 Table B.8
- 1 Table B.9
- 2 Table B.10
- 3 User-supplied table

Bits 4–5 SBHUFFDT selection. This two-bit field can take on one of four values, indicating which table is to be used for **SBHUFFDT**.

- 0 Table B.11
- 1 Table B.12
- 2 Table B.13
- 3 User-supplied table

Bits 6–7 SBHUFFRDW selection. This two-bit field can take on one of three values, indicating which table is to be used for **SBHUFFRDW**.

- 0 Table B.14
- 1 Table B.15
- 3 User-supplied table

The value 2 is not permitted.

Bits 8–9 SBHUFFRDH selection. This two-bit field can take on one of three values, indicating which table is to be used for **SBHUFFRDH**.

- 0 Table B.14
- 1 Table B.15
- 3 User-supplied table

The value 2 is not permitted.

Bits 10–11 SBHUFFRDY selection. This two-bit field can take on one of three values, indicating which table is to be used for **SBHUFFRDY**.

- 0 Table B.14
- 1 Table B.15
- 3 User-supplied table

The value 2 is not permitted.

Bits 12–13 SBHUFFRDX selection. This two-bit field can take on one of three values, indicating which table is to be used for **SBHUFFRDX**.

- 0 Table B.14
- 1 Table B.15
- 3 User-supplied table

The value 2 is not permitted.

Bit 14 SBHUFFRSIZE selection. If this field is **0** then Table B.1 is used for **SBHUFFRSIZE**. If this field is **1** then a user-supplied table is used for **SBHUFFRSIZE**.

Bit 15 Reserved.




Figure 38 — Text region refinement AT flags field structure

7.4.3.1.3 Text region refinement AT flags

This field is only present if **SBREFINE** is **1** and **SBRTEMPLATE** is **0**. It is a four-byte field, formatted as shown in Figure 38 and as described below.

Byte 0 SBRATX₁

Byte 1 SBRATY₁

Byte 2 SBRATX₂

Byte 3 SBRATY₂

The AT coordinate X and Y fields are signed values, and may take on values that are permitted according to 6.3.5.3.

7.4.3.1.4 Number of symbol instances (SBNUMINSTANCES)

This four-byte field contains the number of symbol instances coded in this segment.

7.4.3.1.5 Text region segment symbol ID Huffman decoding table

This field contains a coded version of the Huffman codes used to decode symbol instance IDs in the text region decoding procedure. It is decoded as specified in 7.4.3.1.7. It is only present if **SBHUFF** is **1**.

7.4.3.1.6 Text region segment Huffman table selection

Set the values of the parameters **SBHUFFFS**, **SBHUFFDS**, **SBHUFFDT**, **SBHUFFRDW**, **SBHUFFRDH**, **SBHUFFRDX**, **SBHUFFRDY** and **SBHUFFRSIZE** according to the selection fields shown in 7.4.3.1.2, and the tables segments referred to by this segment. More precisely, of these eight Huffman tables, some may be specified to use some standard table, and some may be specified to use a user-supplied table. The number specified to use a user-supplied table must be equal to the number of tables segments referred to by this segment. These tables segments are matched up with the Huffman tables using user-supplied tables according to the order in which the tables segments are referred to, and the order

1. **SBHUFFFS**
2. **SBHUFFDS**
3. **SBHUFFDT**
4. **SBHUFFRDW**
5. **SBHUFFRDH**
6. **SBHUFFRDX**
7. **SBHUFFRDY**
8. **SBHUFFRSIZE**

If a user-specified table is used for **SBHUFFDS**, then this table must be capable of coding the out-of-band value OOB. If a user-specified table is used for **SBHUFFFS**, **SBHUFFDT**, **SBHUFFRDW**, **SBHUFFRDH**, **SBHUFFRDX**, **SBHUFFRDY** or **SBHUFFRSIZE** then this table must not be capable of coding the out-of-band value OOB.

7.4.3.1.7 Symbol ID Huffman table decoding

This table is encoded as **SBNUMSYMS** symbol ID code lengths; the actual codes in **SBSYMCODES** are assigned from these symbol ID code lengths using the algorithm in B.3.

The symbol ID code lengths themselves are run-length coded and the runs Huffman coded. This is very similar to the “zlib” coded format documented in RFC1951, though not identical. The encoding is based on the codes shown in Table 29.

Decoding a symbol ID Huffman table proceeds as follows.

1. Read the code lengths for RUNCODE0 through RUNCODE34; each is stored as a four-bit value.
2. Given the lengths, assign Huffman codes for RUNCODE0 through RUNCODE34 using the algorithm in B.3.
3. Read a Huffman code using this assignment. This decodes into one of RUNCODE0 through RUNCODE34. If it is RUNCODE32, read two additional bits. If it is RUNCODE33, read three additional bits. If it is RUNCODE34, read seven additional bits.
4. Interpret the RUNCODE code and the additional bits (if any) according to Table 29. This gives the symbol ID code lengths for one or more symbols.
5. Repeat steps 3 and 4 until the symbol ID code lengths for all **SBNUMSYMS** symbols have been determined.
6. Skip over the remaining bits in the last byte read, so that the actual text region decoding procedure begins on a byte boundary.
7. Assign a Huffman code to each symbol by applying the algorithm in B.3 to the symbol ID code lengths just decoded. The result is the symbol ID Huffman table **SBSYMCODES**.

EXAMPLE 1 — Suppose that **SBNUMSYMS** is 32 and the symbol ID code lengths for these 32 symbols are, in order,

0	0	0	9	6	6	6	6	3	4	4	4	4	4	4	0
7	9	8	7	5	5	5	5	5	5	3	6	7	4	7	7

These symbol ID code lengths might be transmitted as the sequence of bytes, in hexadecimal

```
0x50 0x03 0x35 0x32 0x53 0x00 0x00 0x00 0x00
0x00 0x00 0x00 0x00 0x00 0x00 0x00 0x35 0x0F
0x8B 0x30 0x9E 0xB8 0x5F 0x1D 0xD2 0x83 0x00
```

Interpretation of this sequence of bytes can be separated into the following three steps.

1. The first 17 bytes plus the first four bits of the 18th byte assign code lengths to the 35 run codes as follows

RUNCODE0	5	RUNCODE1	0	RUNCODE2	0
RUNCODE3	3	RUNCODE4	3	RUNCODE5	5
RUNCODE6	3	RUNCODE7	2	RUNCODE8	5
RUNCODE9	3	RUNCODE10	0	RUNCODE11	0
RUNCODE12	0	RUNCODE13	0	RUNCODE14	0
RUNCODE15	0	RUNCODE16	0	RUNCODE17	0
RUNCODE18	0	RUNCODE19	0	RUNCODE20	0
RUNCODE21	0	RUNCODE22	0	RUNCODE23	0
RUNCODE24	0	RUNCODE25	0	RUNCODE26	0
RUNCODE27	0	RUNCODE28	0	RUNCODE29	0
RUNCODE30	0	RUNCODE31	0	RUNCODE32	3
RUNCODE33	5	RUNCODE34	0		

Table 29 — Meaning of the run codes

RUNCODE0	Symbol ID code length is 0
RUNCODE1	Symbol ID code length is 1
RUNCODE2	Symbol ID code length is 2
RUNCODE3	Symbol ID code length is 3
RUNCODE4	Symbol ID code length is 4
RUNCODE5	Symbol ID code length is 5
RUNCODE6	Symbol ID code length is 6
RUNCODE7	Symbol ID code length is 7
RUNCODE8	Symbol ID code length is 8
RUNCODE9	Symbol ID code length is 9
RUNCODE10	Symbol ID code length is 10
RUNCODE11	Symbol ID code length is 11
RUNCODE12	Symbol ID code length is 12
RUNCODE13	Symbol ID code length is 13
RUNCODE14	Symbol ID code length is 14
RUNCODE15	Symbol ID code length is 15
RUNCODE16	Symbol ID code length is 16
RUNCODE17	Symbol ID code length is 17
RUNCODE18	Symbol ID code length is 18
RUNCODE19	Symbol ID code length is 19
RUNCODE20	Symbol ID code length is 20
RUNCODE21	Symbol ID code length is 21
RUNCODE22	Symbol ID code length is 22
RUNCODE23	Symbol ID code length is 23
RUNCODE24	Symbol ID code length is 24
RUNCODE25	Symbol ID code length is 25
RUNCODE26	Symbol ID code length is 26
RUNCODE27	Symbol ID code length is 27
RUNCODE28	Symbol ID code length is 28
RUNCODE29	Symbol ID code length is 29
RUNCODE30	Symbol ID code length is 30
RUNCODE31	Symbol ID code length is 31
RUNCODE32	Copy the previous symbol ID code length 3–6 times. The next two bits, plus 3, indicate this repeat length.
RUNCODE33	Repeat a symbol ID code length of 0 for 3–10 times. The next three bits, plus 3, indicate this repeat length.
RUNCODE34	Repeat a symbol ID code length of 0 for 11–138 times. The next seven bits, plus 11, indicate this repeat length.

Recall that codes that are not used are assigned a symbol ID code length of zero.

- The algorithm of B.3 assigns the following Huffman codes to the run codes (run codes that are not assigned Huffman codes are omitted).

RUNCODE0	11100	RUNCODE3	010	RUNCODE4	011
RUNCODE5	11101	RUNCODE6	100	RUNCODE7	00
RUNCODE8	11110	RUNCODE9	101	RUNCODE32	110
RUNCODE33	11111				

- The remaining part of the byte sequence is

0xF 0x8B 0x30 0x9E 0xB8 0x5F 0x1D 0xD2 0x83 0x00

where half of the first byte has already been consumed. Decoding this sequence using these Huffman codes provides the following results.

1111 000 RUNCODE33(0) — that is, RUNCODE33 followed by three bits containing the value 0, indicating a run of three zero lengths

101 RUNCODE9

100 RUNCODE6

110 00 RUNCODE32(0) — that is, RUNCODE32 followed by two bits containing the value 0)

010 RUNCODE3

011 RUNCODE4

110 10 RUNCODE32(2)

11100 RUNCODE0

00 RUNCODE7

101 RUNCODE9

11110 RUNCODE8

00 RUNCODE7

11101 RUNCODE5

110 10 RUNCODE32(2)

010 RUNCODE3

100 RUNCODE6

00 RUNCODE7

011 RUNCODE4

00 RUNCODE7

00 RUNCODE7

0000 Four bits of padding to fill the last byte.

- After interpreting the run codes according to Table 29, the desired sequence of symbol ID code lengths is decoded.

EXAMPLE 2 — This example describes how an encoder might generate an encoded symbol ID Huffman table. The symbol ID table is identical to that in the previous example.

Suppose that a text region refers to a dictionary containing 32 symbols, and that each symbol is used as follows:

0	0	0	1	8	8	8	8	64	32	32	32	32	32	32	0
4	1	2	4	16	16	16	16	16	16	64	8	4	32	4	4

Table 30 — Example of symbol ID Huffman table encoding

Symbol	Use count	Symbol ID code length	Runs	RUNCODEs
Symbol #1	0	0	Length 3 run of 0	RUNCODE33(0)
Symbol #2	0	0		
Symbol #3	0	0		
Symbol #4	1	9	Length 1 run of 9	RUNCODE9
Symbol #5	8	6	Length 4 run of 6	RUNCODE6
Symbol #6	8	6		RUNCODE32(0)
Symbol #7	8	6		
Symbol #8	8	6		
Symbol #9	64	3	Length 1 run of 3	RUNCODE3
Symbol #10	32	4	Length 6 run of 4	RUNCODE4
Symbol #11	32	4		RUNCODE32(2)
Symbol #12	32	4		
Symbol #13	32	4		
Symbol #14	32	4		
Symbol #15	32	4		
Symbol #16	0	0	Length 1 run of 0	RUNCODE0
Symbol #17	4	7	Length 1 run of 7	RUNCODE7
Symbol #18	1	9	Length 1 run of 9	RUNCODE9
Symbol #19	2	8	Length 1 run of 8	RUNCODE8
Symbol #20	4	7	Length 1 run of 7	RUNCODE7
Symbol #21	16	5	Length 6 run of 5	RUNCODE5
Symbol #22	16	5		RUNCODE32(2)
Symbol #23	16	5		
Symbol #24	16	5		
Symbol #25	16	5		
Symbol #26	16	5		
Symbol #27	64	3	Length 1 run of 3	RUNCODE3
Symbol #28	8	6	Length 1 run of 6	RUNCODE6
Symbol #29	4	7	Length 1 run of 7	RUNCODE7
Symbol #30	32	4	Length 1 run of 4	RUNCODE4
Symbol #31	4	7	Length 2 run of 7	RUNCODE7
Symbol #32	4	7		RUNCODE7

For example, the first, second and third symbols in the symbol dictionary are not used at all, the fourth symbol is used once, the fifth symbol is used eight times, and so on.

Table 30 then shows, from right to left, the progression of the encoding.

Using a standard Huffman tree algorithm, the code lengths shown in the “Symbol ID code length” column are assigned to the symbols (where a symbol ID code length of 0 represents “unused”). Next, those code lengths are grouped into runs, as shown in the “Runs” column. Following that, each run is expressed as one or more RUNCODEs, each one potentially with some extra bits. For example, RUNCODE32(2) represents RUNCODE32, followed by two bits encoding the value “2”, meaning “Copy the previous symbol ID code length 5 times”.

Once that has been done, the number of times each RUNCODE is used is counted. These counts are as follows (unused RUNCODEs are not shown):

RUNCODE0	1	RUNCODE3	2	RUNCODE4	2
RUNCODE5	1	RUNCODE6	2	RUNCODE7	5
RUNCODE8	1	RUNCODE9	2	RUNCODE32	3
RUNCODE33	1				

These counts are then converted into code lengths using a standard Huffman tree algorithm:

RUNCODE0	5	RUNCODE3	3	RUNCODE4	3
RUNCODE5	5	RUNCODE6	3	RUNCODE7	2
RUNCODE8	5	RUNCODE9	3	RUNCODE32	3
RUNCODE33	5				

The algorithm of B.3 assigns the following Huffman codes to the run codes:

RUNCODE0	11100	RUNCODE3	010	RUNCODE4	011
RUNCODE5	11101	RUNCODE6	100	RUNCODE7	00
RUNCODE8	11110	RUNCODE9	101	RUNCODE32	110
RUNCODE33	11111				

and these Huffman codes are then used to encode the “RUNCODEs” column of Table 30:

11111 000 RUNCODE33(0)
101 RUNCODE9
100 RUNCODE6
110 00 RUNCODE32(0)
010 RUNCODE3
011 RUNCODE4
110 10 RUNCODE32(2)
11100 RUNCODE0
00 RUNCODE7
101 RUNCODE9
11110 RUNCODE8
00 RUNCODE7
11101 RUNCODE5
110 10 RUNCODE32(2)

010 RUNCODE3
100 RUNCODE6
00 RUNCODE7
011 RUNCODE4
00 RUNCODE7
00 RUNCODE7

The encoder now emits the encoded RUNCODE code lengths, followed by the sequence of RUNCODES, plus four bits of padding to fill the last byte, yielding the sequence of bytes

```

0x50 0x03 0x35 0x32 0x53 0x00 0x00 0x00 0x00
0x00 0x00 0x00 0x00 0x00 0x00 0x00 0x35 0x0F
0x8B 0x30 0x9E 0xB8 0x5F 0x1D 0xD2 0x83 0x00
  
```

7.4.3.2 Decoding a text region segment

A text region segment is decoded according to the following steps.

1. Interpret its header, as described in 7.4.3.1.
2. Decode (or retrieve the results of decoding) any referred-to symbol dictionary and tables segments.
3. As described in E.3.7, reset all the arithmetic coding statistics to zero.
4. Invoke the text region decoding procedure described in 6.4, with the parameters to the text region decoding procedure set as shown in Table 31.

7.4.4 Pattern dictionary segment syntax

7.4.4.1 Pattern dictionary segment data header

A pattern dictionary segment's data part begins with a pattern dictionary segment data header, formatted as shown in Figure 39 and as described below.




Figure 39 — Pattern dictionary header structure

Pattern dictionary flags See 7.4.4.1.1.

HDPW See 7.4.4.1.2.

HDPH See 7.4.4.1.3.

GRAYMAX See 7.4.4.1.4.

7.4.4.1.1 Pattern dictionary flags

This one-byte field is formatted as shown in Figure 40 and as described below.

Bit 0 HDMMR

If this bit is **1**, then the segment uses the MMR encoding variant. If this bit is **0**, then the segment uses the arithmetic encoding variant.

Bits 1–2 HDTEMPLATE

This field controls the template used to decode patterns if **HDMMR** is **0**. If **HDMMR** is **1**, this field must contain the value 0.

Bits 3–7 Reserved; must be **0**.

7.4.4.1.2 Width of the patterns in the pattern dictionary (HDPW)

This one-byte field contains the width of the patterns defined in this pattern dictionary. Its value must be greater than zero.

7.4.4.1.3 Height of the patterns in the pattern dictionary (HDPH)

This one-byte field contains the height of the patterns defined in this pattern dictionary. Its value must be greater than zero.

7.4.4.1.4 Largest gray-scale value (GRAYMAX)

This four-byte field contains one less than the number of patterns defined in this pattern dictionary.

7.4.4.2 Decoding a pattern dictionary segment

A pattern dictionary segment is decoded according to the following steps.

1. Interpret its header, as described in 7.4.4.1.
2. As described in E.3.7, reset all the arithmetic coding statistics to zero.
3. Invoke the pattern dictionary decoding procedure described in 6.7, with the parameters to the pattern dictionary decoding procedure set as shown in Table 32.

Table 32 — Parameters used to decode a pattern dictionary segment.

Name	Value
HDMMR	As shown in 7.4.4.1.1.
HDTEMPLATE	As shown in 7.4.4.1.1.
HDPW	As shown in 7.4.4.1.2.
HDPH	As shown in 7.4.4.1.3.
GRAYMAX	As shown in 7.4.4.1.4.

7.4.5 Halftone region segment syntax

The data parts of all three of the halftone region segment types (“intermediate halftone region”, “immediate halftone region” and “immediate lossless halftone region”) are coded identically, but are acted upon differently; see 8.2. The syntax of these segment types’ data parts is specified here.

7.4.5.1 Halftone region segment data header

The data part of a halftone region segment begins with a halftone region segment data header. This header contains the fields shown in Figure 41 and described below.




Figure 41 — Halftone region segment data header structure

Region segment information field See 7.4.1.

Halftone region segment flags See 7.4.5.1.1.

Halftone grid position and size See 7.4.5.1.2.

Halftone grid vector See 7.4.5.1.3.




Figure 42 — Halftone region segment flags field structure

7.4.5.1.1 Halftone region segment flags

This one-byte field is formatted as shown in Figure 42 and as described below.

Bit 0 HMMR

If this bit is **1**, then the segment uses the MMR encoding variant. If this bit is **0**, then the segment uses the arithmetic encoding variant.

Bits 1–2 HTEMPLATE

This field controls the template used to decode halftone gray-scale value bitplanes if **HMMR** is **0**. If **HMMR** is **1**, this field must contain the value **0**.

Bit 3 HENABLESKIP

This field controls whether gray-scale values that do not contribute to the region contents are skipped during decoding. If **HMMR** is **1**, this field must contain the value **0**.

Bits 4–6 HCOMBOP

This field has five possible values, representing one of five possible combination operators:

- 0** OR
- 1** AND
- 2** XOR
- 3** XNOR
- 4** REPLACE

Bit 7 HDEFPIXEL

This bit contains the initial value for every pixel in the halftone region, before any patterns are drawn.

7.4.5.1.2 Halftone grid position and size

This field describes the location and size of the grid of gray-scale values. See Figure 24 for an illustration of these values. It is formatted as shown in Figure 43 and as described below.




Figure 43 — Halftone grid position and size field structure

HGW See 7.4.5.1.2.1.

HGH See 7.4.5.1.2.2.

HGX See 7.4.5.1.2.3.

HGY See 7.4.5.1.2.4.

7.4.5.1.2.1 Width of the gray-scale image (HGW)

This four-byte field contains the width of the array of gray-scale values.

7.4.5.1.2.2 Height of the gray-scale image (HGH)

This four-byte field contains the height of the array of gray-scale values.

7.4.5.1.2.3 Horizontal offset of the grid (HGX)

This signed four-byte field contains 256 times the horizontal offset of the origin of the halftone grid.

7.4.5.1.2.4 Vertical offset of the grid (HGY)

This signed four-byte field contains 256 times the vertical offset of the origin of the halftone grid.

7.4.5.1.3 Halftone grid vector

This field describes the vector used to draw the grid of gray-scale values. See Figure 24 for an illustration of these values. It is formatted as shown in Figure 44 and as described below.




Figure 44 — Halftone grid vector field structure

HRX See 7.4.5.1.3.1.

HRY See 7.4.5.1.3.2.

7.4.5.1.3.1 Horizontal coordinate of the halftone grid vector (HRX)

This unsigned two-byte field contains 256 times the horizontal coordinate of the halftone grid vector.

7.4.5.1.3.2 Vertical coordinate of the halftone grid vector (HRY)

This unsigned two-byte field contains 256 times the vertical coordinate of the halftone grid vector.

7.4.5.2 Decoding a halftone region segment

A halftone region segment is decoded according to the following steps.

1. Interpret its header, as described in 7.4.5.1.
2. Decode (or retrieve the results of decoding) the referred-to pattern dictionary segment.
3. As described in E.3.7, reset all the arithmetic coding statistics to zero.
4. Invoke the halftone region decoding procedure described in 6.6, with the parameters to the halftone region decoding procedure set as shown in Table 33.

7.4.6 Generic region segment syntax

The data parts of all three of the generic region segment types (“intermediate generic region”, “immediate generic region” and “immediate lossless generic region”) are coded identically, but are acted upon differently; see 8.2. The syntax of these segment types’ data parts is specified here.

Table 33 — Parameters used to decode a halftone region segment.

Name	Value
HBW	As specified by the region segment bitmap width in this segment's region segment data header.
HBH	As specified by the region segment bitmap height in this segment's region segment data header.
HMMR	As shown in 7.4.5.1.1.
HTEMPLATE	As shown in 7.4.5.1.1.
HENABLESKIP	As shown in 7.4.5.1.1.
HCOMBOP	As shown in 7.4.5.1.1.
HDEFPIXEL	As shown in 7.4.5.1.1.
HGW	As shown in 7.4.5.1.2.1.
HGH	As shown in 7.4.5.1.2.2.
HGX	As shown in 7.4.5.1.2.3.
HGY	As shown in 7.4.5.1.2.4.
HRX	As shown in 7.4.5.1.3.1.
HRY	As shown in 7.4.5.1.3.2.
HNUMPATS	The number of patterns in the pattern dictionary segment referred to by this segment.
HPATS	The patterns in the pattern dictionary segment referred to by this segment.
HPW	The width, in pixels, of each of the patterns contained in HPATS .
HPH	The height, in pixels, of each of the patterns contained in HPATS .




Figure 45 — Generic region segment data header structure

7.4.6.1 Generic region segment data header

The data part of a generic region segment begins with a generic region segment data header. This header contains the fields shown in Figure 45 and described below.

Region segment information field See 7.4.1.

Generic region segment flags See 7.4.6.2.

Generic region segment AT flags See 7.4.6.3.

7.4.6.2 Generic region segment flags

This one-byte field is formatted as shown in Figure 46 and as described below.




Figure 46 — Generic region segment flags field structure

Bit 0 MMR

Bits 1–2 GBTEMPLATE

This field specifies the template used for template-based arithmetic coding. If **MMR** is **1** then this field must contain the value zero.

Bit 3 TPGDON

This field specifies whether typical prediction for generic direct coding is used.

Bits 4–7 Reserved; must be zero.

7.4.6.3 Generic region segment AT flags

This field is only present if **MMR** is **0**. If **GBTEMPLATE** is 0, it is an eight-byte field, formatted as shown in Figure 47 and as described below.




Figure 47 — Generic region AT flags field structure when GBTEMPLATE is 0

Byte 0 GBATX₁

Byte 1 GBATY₁

Byte 2 GBATX₂

Byte 3 GBATY₂

Byte 4 GBATX₃

Byte 5 GBATY₃

Byte 6 GBATX₄




Figure 48 — Generic region AT flags field structure when GBTEMPLATE is not 0

Byte 7 GBATY₄

If **GBTEMPLATE** is 1, 2 or 3, it is a two-byte field formatted as shown in Figure 48 and as described below. If **GBTEMPLATE** is 1, 2 or 3 then the values of **GBATX₂** through **GBATX₄** and **GBATY₂** through **GBATY₄** are all zero.

Byte 0 GBATX₁

Byte 1 GBATY₁

The AT coordinate X and Y fields are signed values, and may take on values that are permitted according to Figure 7.

7.4.6.4 Decoding a generic region segment

A generic region segment is decoded according to the following steps.

1. Interpret its header, as described in 7.4.6.1
2. As described in E.3.7, reset all the arithmetic coding statistics to zero.
3. Invoke the generic region decoding procedure described in 6.2, with the parameters to the generic region decoding procedure set as shown in Table 34.

Table 34 — Parameters used to decode a generic region segment.

Name	Value
MMR	As shown in 7.4.6.2.
GBTEMPLATE	As shown in 7.4.6.2.
TPGDON	As shown in 7.4.6.2.
USESKIP	0
GBW	As specified by the region segment bitmap width in this segment's region segment data header.
GBH	As specified by the region segment bitmap height in this segment's region segment data header.
GBATX₁	See 7.4.6.3
GBATY₁	See 7.4.6.3
GBATX₂	See 7.4.6.3
GBATY₂	See 7.4.6.3
GBATX₃	See 7.4.6.3
GBATY₃	See 7.4.6.3
GBATX₄	See 7.4.6.3
GBATY₄	See 7.4.6.3

As a special case, as noted in 7.2.7, an immediate generic region segment may have an unknown length. In this case, it is also possible that the segment may contain fewer rows of bitmap data than are indicated in the segment's region segment information field.

In order for the decoder to correctly decode the segment, it needs to read the four-byte row count field, which is stored in the last four bytes of the segment's data part. These four bytes can be detected without knowing the

length of the data part in advance: if **MMR** is **1**, they are preceded by the two-byte sequence 0x00 0x00; if **MMR** is **0**, they are preceded by the two-byte sequence 0xFF 0xAC. The row count field contains the actual number of rows contained in this segment; it must be no greater than the region segment bitmap height value in the segment’s region segment information field.

NOTE — The sequence 0x00 0x00 cannot occur within MMR-encoded data; the sequence 0xFF 0xAC can occur only at the end of arithmetically-coded data. Thus, those sequences cannot occur by chance in the data that is decoded to generate the contents of the generic region.

7.4.7 Generic refinement region syntax

The data parts of all three of the generic refinement region segment types (“intermediate generic refinement region,” “immediate generic refinement region” and “immediate lossless generic refinement region”) are coded identically, but are acted upon differently; see 8.2. The syntax of these segment types’ data parts is specified here.

7.4.7.1 Generic refinement region segment data header

The data part of a generic refinement region segment begins with a generic refinement region segment data header. This header contains the fields shown in Figure 49 and described below.




Figure 49 — Generic refinement region segment data header structure

Region segment information field See 7.4.1.

Generic refinement region segment flags See 7.4.7.2.

Generic refinement region segment AT flags See 7.4.7.3.

7.4.7.2 Generic refinement region segment flags

This one-byte field is formatted as shown in Figure 50 and as described below.




Figure 50 — Generic refinement region segment flags field structure

Bit 0 GRTEMPLATE

This field specifies the template used for template-based arithmetic coding.

Bit 1 TPGRON

This field specifies whether typical prediction for generic refinement is used.

Bits 2–7 Reserved; must be zero.




Figure 51 — Generic refinement region AT flags field structure

7.4.7.3 Generic refinement region segment AT flags

This field is only present if **GRTEMPLATE** is 0. It is a four-byte field, formatted as shown in Figure 51 and as described below.

Byte 0 GRATX₁

Byte 1 GRATY₁

Byte 2 GRATX₂

Byte 3 GRATY₂

The AT coordinate X and Y fields are signed values, and may take on values that are permitted according to 6.3.5.3.

7.4.7.4 Reference bitmap selection

If this segment refers to another region segment, then set the reference bitmap **GRREFERENCE** to be the current contents of the auxiliary buffer associated with the region segment that this segment refers to.

If this segment does not refer to another region segment, set **GRREFERENCE** to be a bitmap containing the current contents of the page buffer (see Clause 8), restricted to the area of the page buffer specified by this segment's region segment information field.

7.4.7.5 Decoding a generic refinement region segment

A generic refinement region segment is decoded according to the following steps.

1. Interpret its header as described in 7.4.7.1. If this segment does not refer to another region segment then its external combination operator must be **REPLACE**. If it does refer to another region segment, then this segment's region bitmap size, location, and external combination operator must be equal to that other segment's region bitmap size, location, and external combination operator.

NOTE — The requirement that the locations and external combination operators match is present to assist decoders that want to produce images of a page that is only partially decoded: it ensures that the final location and external combination operator is known for all intermediate segments. These partially-decoded page images are outside the scope of this Recommendation | International Standard.

2. As described in E.3.7, reset all the arithmetic coding statistics to zero.
3. Determine the buffer associated with the region segment that this segment refers to.
4. Invoke the generic refinement region decoding procedure described in 6.3, with the parameters to the generic refinement region decoding procedure set as shown in Table 35

7.4.8 Page information segment syntax

A page information segment describes a page. It contains the fields shown in Figure 52 and described below.

Page bitmap width See 7.4.8.1.

Page bitmap height See 7.4.8.2.

Page X resolution See 7.4.8.3.

Table 35 — Parameters used to decode a generic refinement region segment.

Name	Value
GRTEMPLATE	As shown in 7.4.6.2.
TPGRON	As shown in 7.4.6.2.
GRW	As specified by the region segment bitmap width in this segment's region segment data header.
GRH	As specified by the region segment bitmap height in this segment's region segment data header.
GRREFERENCE	See 7.4.7.4.
GRREFERENCEDX	0
GRREFERENCEDY	0
GRATX₁	See 7.4.7.3
GRATX₂	See 7.4.7.3
GRATY₁	See 7.4.7.3
GRATY₂	See 7.4.7.3




Figure 52 — Page information segment structure

Page Y resolution See 7.4.8.4.

Page segment flags See 7.4.8.5.

Page striping information See 7.4.8.6.

The first segment that is associated with any page must be a page information segment.

7.4.8.1 Page bitmap width

This is a four-byte value containing the width in pixels of the page's bitmap.

7.4.8.2 Page bitmap height

This is a four-byte value containing height in pixels of the page's bitmap. In some cases, this value may not be known at the time that the page information segment is written. In this case, this field must contain 0xFFFFFFFF, and the actual page height may be communicated later, once it is known.

7.4.8.3 Page X resolution

This is a four-byte value containing the resolution of the original page medium, measured in pixels/metre in the horizontal direction. If this value is unknown then this field must contain 0x00000000.

7.4.8.4 Page Y resolution

This is a four-byte value containing the resolution of the original page medium, measured in pixels/metre in the vertical direction. If this value is unknown then this field must contain 0x00000000.

7.4.8.5 Page segment flags

This is a one-byte field. It is formatted as shown in Figure 53 and as described below.

Bit 0 Page is eventually lossless. If this bit is **0**, then the file does not contain a lossless representation of the original (pre-coding) page. If this bit is **1**, then the file contains enough information to reconstruct the original page.




Figure 53 — Page segment flags field structure

Bit 1 Page might contain refinements. If this bit is **0**, then no refinement region segment may be associated with the page. If this bit is **1**, then such segments may be associated with the page.

Bit 2 Page default pixel value. This bit contains the initial value for every pixel in the page, before any region segments are decoded or drawn.

Bits 3–4 Page default combination operator. This field has four possible values, representing one of four possible combination operators:

- 0** OR
- 1** AND
- 2** XOR
- 3** XNOR

This operator is used to merge overlapping region segments, and also to combine region segments with the page default pixel value.

Bit 5 Page requires auxiliary buffers. If this bit is **0**, then no region segment requiring an auxiliary buffer may be associated with the page. If this bit is **1**, then such segments may be associated with the page.

Bit 6 Page combination operator overridden. If this bit is **0**, then every direct region segment associated with this page must use the page’s combination operator. If this bit is **1**, then direct region segments associated with this page may use combination operators that are different from the page’s combination operator.

NOTE 1 — All region segments, except for refinement region segments, are direct region segments. Because of the requirements in 7.4.7.5 restricting the external combination operators of refinement region segments, if this bit is **0**, then refinement region segments associated with this page that refer to no region segments must have an external combination operator of REPLACE, and all other region segments associated with this page must have the external combination operator specified by this page’s “Page default combination operator”.

NOTE 2 — If all the direct region segments associated with a page use the same combination operator, then it is possible to reorder them to some extent (it is not possible switch the relative order of any refinement segment). If some of them use different combination operators, then the decoder is unable do any such reordering. Furthermore, the decoder cannot tell from the segment headers whether any such non-default combination operators are used in the page, so this bit indicates that reordering may be possible, if the decoder wishes to perform it.

Bit 7 Reserved; must be **0**.

7.4.8.6 Page striping information

This is a two-byte field. It is formatted as shown in Figure 54 and as described below.

Bits 0–14 Maximum stripe size

Bit 15 Page is striped




Figure 54 — Page striping information field structure

If the “page is striped” bit is **1**, then the page may have end of stripe segments associated with it. In this case, the maximum size of each stripe (the distance between an end of stripe segment’s end row and the end row of the previous end of stripe segment, or 0 in the case of the first end of strip segment) must be no more than the page’s maximum stripe size.

If the page’s bitmap height is unknown (indicated by a page bitmap height of 0xFFFFFFFF) then the “page is striped” bit must be **1**.

7.4.9 End of page segment syntax

An end of page segment has no associated data. Its segment data length field must be zero.

The last segment that is associated with any page must be an end of page segment.

If a page’s height was originally unknown, then there must be at least one end of stripe segment associated with the page. In this case, the end row of that last stripe is the last row of the page bitmap and no region segment may occur between the last end of stripe segment and the end of page segment.

7.4.10 End of stripe segment syntax

An end of stripe segment states that the encoder has finished coding a portion of the current page, and will not revisit it. It specifies the Y coordinate of a row of the page; no segment following the end of stripe may modify any portion of the page bitmap that lines on or above that row; furthermore, no segment preceding the end of stripe may modify any portion of the page bitmap that lies below that row. This row is called the “end row” of the stripe.

NOTE 1 — In some cases, the decoder may only have a limited amount of buffer memory for the page bitmap, smaller than the size of the page. The decoder needs to be told when it is able to output the current buffer contents and clear the buffer for the next stripe of the page.

The end row specified by an end of stripe segment must lie below any previous end row for that page. A page whose height was originally unknown must contain at least one end of stripe segment.

NOTE 2 — An end of stripe segment is used to communicate the size of the page in this case.

The segment data of an end of stripe segment consists of one four-byte value, specifying the Y coordinate of the end row.

7.4.11 End of file segment syntax

If a file contains an end of file segment, it must be the last segment.

An end of file segment has no associated data. Its segment data length field must be zero.

7.4.12 Profiles segment syntax

A profiles segment contains a list of the profiles that a given JBIG2 data stream is in compliance with. If any profiles segments are present, then the first segment of the data stream must be a profiles segment, and must not be associated with any page. Profiles of this Recommendation | International Standard are listed in Annex G.

A profiles segment begins with a four-byte field containing the number of profiles listed. This field is followed by that many four-byte fields. Each of those fields contains a profile identification number. The data stream must be in compliance with each of the profiles listed.

More than one profiles segment may be present. If more than one is present, then each one, other than the first one, must be associated with a page. No page may have more than one profiles segment associated with it. Also, each profiles segment past the first one must be more restrictive than the first one; that is, it must list all of the profile identification numbers listed in the first segment, and possibly more. The segments making up each page must, collectively, be in compliance with each of the profiles listed in any profiles segment associated with that page.

NOTE — The global profiles segment allows a decoder to find out quickly that it cannot decode a given data stream. Allowing each page to contain a possibly different (though more restrictive) profiles segment eases moving pages from one file to another.

7.4.13 Code table segment syntax

A code table segment's syntax is described in Annex B.

7.4.14 Extension segment syntax

An extension segment's data begins with a extension header:

Extension type This is a four-byte field which contains an identification of the type of data that are present in the extension segment.

The three most significant bits of this field have special meaning:

Bit 29 Reserved. Future revisions of this Recommendation | International Standard may define extension types; extension types may also be registered by other parties. Other parties may register only extension types with this bit equal to **0**; all extension types having bit 29 equal to **1** are reserved for future revisions of this Recommendation | International Standard.

Bit 30 Dependent. If this bit is **1**, then the coding of the data in the extension segment is dependent on the exact encoding of the data in the segments that the extension segment refers to. Any file manipulation program that modifies those referred-to segments needs to modify this extension segment's data correspondingly; if it does not understand the extension segment (due to not recognising its extension type), and if it is not a necessary extension segment, then the segment should be deleted.

EXAMPLE — An extension segment containing a CRC of the segment that it refers to should be flagged as dependent.

Bit 31 Necessary. If this bit is **1**, then any decoder that does not know how to parse extensions of this extension segment's type will not be able to correctly decode the file to produce the intended decoded page images.

NOTE — This is intended to facilitate future extensions to JBIG2, such as coding improvements. If this bit is **1**, then a decoder that does not understand the extension knows that it has encountered data necessary to the correct decoding of the page that it cannot handle. For example, an extension segment containing a region that is coded with some new method would be flagged as “necessary”, as without that region the page image is not complete. Another example might be an extension segment containing a set of colours that should be applied to the symbols on the page as they are drawn.

If the “necessary” bit is **1**, then the “reserved” bit must also be **1**.

The remainder of the extension segment's data immediately follows the extension type field, and is formatted in some way particular to the type of extension.

7.4.15 Defined extension types

The following extension types are currently defined.

0x20000000 ASCII comment. See 7.4.15.1.

0x20000002 Unicode comment. See 7.4.15.2.

7.4.15.1 Comment

An ASCII comment extension segment holds textual information about some other segment, page, or the bitstream as a whole. If it refers to no other segments, and is associated with no page, then it contains some set of comments applying to the entire bitstream. If it refers to no other segments, but is associated with some page, then it contains some set of comments applying to that page. If it refers to some segments, then it contains some set of comments applying to those segments.

An ASCII comment segment contains a number of (name, value) pairs. Each element of each pair is a string of characters, and is terminated by an ASCII NUL (0x00) character. The last pair is followed by an additional NUL character.

EXAMPLE — The comment containing the following pairs

```
Title           An Illustrated History of False Teeth
Author          The Big Cheese
```

is stored as the following sequence of bytes. The bytes are shown as hexadecimal numbers together with their ASCII equivalents, with “.” indicating an unprintable byte. Note the four-byte extension type at the start of the segment data:

```
20 00 00 00 54 69 74 6C 65 00 41 6E 20 49 6C 6C  ...Title.An Ill
75 73 74 72 61 74 65 64 20 48 69 73 74 6F 72 79  ustrated History
20 6F 66 20 46 61 6C 73 65 20 54 65 65 74 68 00  of False Teeth.
41 75 74 68 6F 72 00 54 68 65 20 42 69 67 20 43  Author.The Big C
68 65 65 73 65 00 00                               heese..
```

7.4.15.2 Unicode comment

A Unicode comment extension segment is formatted in the same manner as an ASCII comment extension segment, except that the individual characters each occupy two bytes, in the UCS-16 encoding (ISO/IEC 10646-1:1993). Each element of each pair in the comment is terminated by a 0x0000 and the final pair is followed by an additional 0x0000.

8 Page Make-up

8.1 Decoder model

This section describes the result that a decoder conforming to this Recommendation | International Standard shall produce when decoding a page. It does this by specifying a set of steps that produce the correct result; a conforming decoder need not perform these exact steps, but shall produce the same result as if the steps had been followed.

Here we describe only the steps taken to decode a single page. A conforming decoder may operate on multiple pages at once, as long as it produces the correct final result for each page.

In the following description, we will assume for simplicity that the decoder has a single page buffer, auxiliary buffers to be used while decoding that page, and additional dictionary memory. Decoders with other components are allowed, as long as they produce the same page buffer as this abstract decoder does.

At the end of the decoding process, the page buffer contains the result of decoding the page.

Each auxiliary buffer has a location associated with it; this location is the location of the buffer's top left pixel, relative to the top left pixel of the page buffer. Some region segments require the use of auxiliary buffers; others can be decoded directly into the page buffer. See 8.2 for details on how combinations of image segments are to be interpreted.

The dictionary memory contains the information obtained by decoding dictionary segments.

8.2 Page image composition

The final bitmap for each page is coded by zero or more region segments associated with that page. Each region segment describes some of the contents of a rectangular region of the page. Since these regions of the page may overlap, and since some parts of the page might be described at multiple levels of refinement, it is important to define what the rules for region segment composition are. Also, since a decoder might want to display intermediate representations of a page, based on partial information, it is useful to suggest the interpretation of partial pages.

As described in 7.4.8, each page has a default pixel value (**0** or **1**) and one of four combination operators (OR, AND, XOR, XNOR); these are specified in its page information segment. Each region segment also specifies a combination operator of its own. The "page combination operator overridden" flag bit in the page information segment specifies whether any of the page's direct region segments overrides the page combination operator. If the bit is **0**, then no direct region segment associated with this page overrides the page combination operator. The decoder may use this information to optimise its decoding.

The result of decoding a region segment is a bitmap. The size of this bitmap and its location with respect to the page buffer are given in the region segment information field.

The final contents of the page buffer that the decoder shall produce as the final result of decoding a page are those that would be generated by the following steps:

1. Decode the page information segment.
2. Create the page buffer, of the size given in the page information segment.

If the page height is unknown, then this is not possible. However, in this case the page must be striped, and the maximum stripe height specified, and the initial page buffer can be created with height initially equal to this maximum stripe height. As each end of stripe segment is encountered, the page buffer's height can be increased, so that the last row in the new buffer is the maximum stripe height plus the end row of the previous stripe. The end of page segment (together with the last end of stripe segment) allow determination of the page's actual height.

Alternately, when the page height is unknown, the decoder may use a fixed-size buffer whose height is equal to the page's maximum stripe height. As each end of stripe segment is encountered, the decoder can print, or copy to some other location, all the rows in this buffer up to and including the stripe's end row, then clear the buffer in preparation for the next stripe. The decoder may follow this strategy whenever the page is striped, even if the page height is known beforehand.

NOTE — The steps below can be followed regardless of which striping strategy is followed. The restrictions imposed by striping ensure that once an end of stripe segment is seen, no part of the page above or on that stripe's end row can be modified, and so the presentation

below is phrased in terms of a page buffer that is the full size of the page, even when the page's height is not known initially.

3. Fill the page buffer with the page's default pixel value.
4. Fetch the next region segment associated with that page.
5. The following cases exist:
 - (a) The region segment is an immediate direct region segment. In this case, decode the region segment. The result of decoding the region segment is a bitmap; combine this bitmap with the current contents of the page buffer, using the region segment's combination operator.
 - (b) The region segment is an intermediate direct region segment. In this case, allocate a new auxiliary buffer, using the size and location specified in the segment's region segment information field. This buffer is initially associated with the region segment. Decode the region segment, placing the resulting bitmap into the auxiliary buffer.
 - (c) The region segment is an immediate refinement region segment that refers to no other segments. In this case, the region segment is acting as a refinement of part of the page buffer. Perform the refinement according to the region segment on the part of the page buffer specified in the region segment, according to the data contained in the refinement region segment. This replaces a part of the page buffer with a refined version.
 - (d) The region segment is an immediate refinement region segment that refers to another region segment. This other region segment must be a previously occurring intermediate region segment that has not yet had a refinement region segment refer to it; the other region segment thus has an auxiliary buffer associated with it. Perform the refinement operation on that auxiliary buffer, according to the data contained in the current region segment, and combine the resulting buffer with the page buffer using the current region segment's combination operator, at the location associated with the auxiliary buffer. Discard the auxiliary buffer.
 - (e) The region segment is an intermediate refinement region segment. This region segment must refer to one other region segment, which must be a previously occurring intermediate region segment that has not yet had a refinement region segment refer to it; the other region segment thus has an auxiliary buffer associated with it. Perform the refinement operation on that auxiliary buffer, according to the data contained in the current region segment. Replace the previous contents of the auxiliary buffer with the bitmap resulting from the refinement. Change the association of the auxiliary buffer, so that it is now associated with the current region segment, and is no longer associated with the other region segment.
6. Repeat steps 4 and 5 until there are no more region segments associated with the page. At this point, all auxiliary buffers that have been allocated should have been refined, drawn into the page, and discarded, as described in step 5d; no auxiliary buffers should remain.
7. The result of decompressing that page is given by the final contents of the page buffer.

The rules described in step 5 are quite simple in principle. Immediate region segments are to be drawn into the page buffer, either by simply drawing them (direct segments, step 5a), by refining a part of the page buffer (refinement segments referring to no other segments, step 5c), or by refining and then drawing an auxiliary buffer (refinement segments referring to some other segment, step 5d). Intermediate region segments involve creating an auxiliary buffer containing the region bitmap (direct segments, step 5b), or replacing the current contents of an auxiliary buffer (refinement segments, step 5e).

Some examples of these rules in operation:

EXAMPLE 1 — If the page contains no region segments, then the page buffer is filled entirely with the page's default pixel value.

EXAMPLE 2 — The page information segment for page 1 specifies that the page default combination operator is OR and the page default pixel value is 0. The region segments associated with page 1 are, in order,

- Segment 3, an immediate lossless text region segment whose external combination operator is OR
- Segment 4, an immediate lossless generic region segment whose external combination operator is OR
- Segment 6, an immediate lossless halftone region segment whose external combination operator is OR

The resulting page bitmap can be obtained by decoding segments 3, 4 and 6, and drawing each one at its specified region location, using OR, into a bitmap initially containing 0 everywhere. Note that the order in which these three segments are decoded and drawn does not affect the resulting page bitmap. Also, if segment 3 has an internal combination operator of OR and a default pixel value of 0, then it may be drawn by simply drawing the symbol instances directly into the page buffer; it is not necessary to decode it into a temporary bitmap then draw that bitmap into the page buffer. A similar observation holds for segment 6.

EXAMPLE 3 — The page information segment for page 2 specifies that the page default combination operator is OR and the page default pixel value is 0. The region segments associated with page 2 are, in order,

- Segment 7, an intermediate text region segment
- Segment 8, an intermediate generic bitmap region segment
- Segment 13, an immediate generic bitmap refinement region segment whose external combination operator is OR that refers to segment 8
- Segment 14, an immediate generic bitmap refinement region segment whose external combination operator is OR that refers to segment 7
- Segment 19, an immediate text region segment whose external combination operator is OR
- Segment 22, an immediate generic bitmap region segment whose external combination operator is OR

The resulting page buffer is the buffer that would be obtained by following the steps

1. Fill the page buffer with the value 0
2. Decode segment 7 into an auxiliary buffer
3. Decode segment 8 into an auxiliary buffer
4. Refine segment 8's auxiliary buffer, according to the refinement information in segment 13, and draw the refined buffer into the page buffer using OR, discarding the auxiliary buffer after this is done
5. Refine segment 7's auxiliary buffer, according to the refinement information in segment 14, and draw the refined buffer into the page buffer using OR, discarding the auxiliary buffer after this is done
6. Decode segment 19 and draw the resulting bitmap into the page buffer using OR
7. Decode segment 22 and draw the resulting bitmap into the page buffer using OR

The correct result is also obtained *no matter what order* steps 4 through 7 are performed in; thus a conforming decoder is free to choose any order to decode these steps. In fact, any order of steps 2 through 7 produces the correct result, as long as step 2 is performed before step 5 and step 3 is performed before step 4.

EXAMPLE 4 — If a page contains several immediate direct-coded region segments that do not override the page's combination operator, and an immediate refinement region segment that does not refer to any other segments, then the resulting page buffer is the buffer that would be obtained by

- filling the page buffer with the page's default pixel value
- drawing all the direct-coded region segments that precede the refinement region segment
- refining the portion of the region covered by the refinement region segment
- drawing all the direct-coded region segments that follow the refinement region segment

In this case, the order of drawing does matter: all the immediate segments that precede the refinement segment shall be drawn before the refinement segment is drawn, and the refinement segment shall be drawn before any of the immediate segments that follow it.

NOTE 2 — In some cases, the decoder may want to display some intermediate form of the page. For example, it may want to provide the user with a progressive display of the page contents as the page segments are received over some transmission medium. Any intermediate page bitmaps that it displays are entirely up to the decoder, and are not specified by this Recommendation | International Standard.

One potential strategy a decoder could use is to take the current contents of the page buffer and any currently active auxiliary buffers, and combine all of these buffers using the page's default combination operator, and display that to the user. If the page combination operator is XOR or XNOR, then this combination can be done reversibly, and so might be done into the actual page buffer, then undone after it has been displayed to the user. If the page combination operator is OR or AND, then this combination is not reversible and an extra buffer is required to hold the results of the combination.

The step-by-step description above is intended to specify only the results of the decompression. A conforming decoder may take any steps it desires, as long as the final page buffer is the same as would have been obtained by following the steps.

EXAMPLE 5 — A decoder might notice that an intermediate region segment refers to a region of the page that is not overlapped by any other region segment, and so might not actually allocate an auxiliary buffer for that region segment, but might use the page buffer immediately. It can do this only if it is sure that this will not change the final results of decoding the page's region segments.

Annex A (normative) Arithmetic Integer Decoding Procedure

A.1 General description

This Recommendation | International Standard uses a number of arithmetic decoding procedures to decode integer values. These are

IAAI	Used to decode the number of symbol instances in an aggregation
IADH	Used to decode the difference in height between two height classes
IADS	Used to decode the S coordinate of the second and subsequent symbol instances in a strip
IADT	Used to decode the T coordinate of the second and subsequent symbol instances in a strip
IADW	Used to decode the difference in width between two symbols in a height class
IAEX	Used to decode export flags
IAFS	Used to decode the S coordinate of the first symbol instance in a strip
IAID	Used to decode the symbol IDs of symbol instances
IAIT	Used to decode the T coordinate of the symbol instances in a strip
IARDH	Used to decode the delta height of symbol instance refinements
IARDW	Used to decode the delta width of symbol instance refinements
IARDX	Used to decode the delta X position of symbol instance refinements
IARDY	Used to decode the delta Y position of symbol instance refinements
IARI	Used to decode the R_I bit of symbol instances

Each of these is used to decode integer values (which may include the out-of-band value OOB). The coding for an integer is based on a decision tree.

An invocation of an arithmetic integer decoding procedure involves decoding a sequence of bits, where each bit is decoded using a context formed by the bits decoded previously in this invocation. Each context for each arithmetic integer decoding procedure has its own adaptive probability estimate used by the underlying arithmetic coder, described in Annex E. The sequence of bits decoded is interpreted to form a value.

Table A.1 is used by all the arithmetic integer decoding procedures except for IAID.

A.2 Procedure for decoding values (except IAID)

The flowchart in Figure A.1 is used as part of the decoding procedure. It produces two values, V and S . The result of the integer arithmetic decoding procedure is equal to

- V if $S = 0$
- $-V$ if $S = 1$ and $V > 0$
- OOB if $S = 1$ and $V = 0$

Thus, V represents the absolute value of the integer value being decoded, and S represents the sign; the otherwise-redundant value -0 is interpreted to mean “OOB”.

In Figure A.1, each bit is decoded in a context formed from the particular integer arithmetic decoding procedure being invoked, and the previous bits decoded in this invocation of that decoding procedure. This context is formed as follows.

1. Set

$$\text{PREV} = 1$$

2. Follow the flowchart in Figure A.1. Decode each bit with CX equal to “IA_x + PREV” where “IA_x” represents the identifier of the current arithmetic integer decoding procedure, “+” represents concatenation, and the rightmost 9 bits of PREV are used.




Figure A.1 — Flowchart for the integer arithmetic decoding procedures (except IAID)

Table A.1 — Arithmetic integer decoding procedure table

VAL	Encoding
0...3	00 + VAL encoded as 2 bits
-1	1001
-3...-2	101 + (-VAL - 2) encoded as 1 bit
4...19	010 + (VAL - 4) encoded as 4 bits
-19...-4	110 + (-VAL - 4) encoded as 4 bits
20...83	0110 + (VAL - 20) encoded as 6 bits
-83...-20	1110 + (-VAL - 20) encoded as 6 bits
84...339	01110 + (VAL - 84) encoded as 8 bits
-339...-84	11110 + (-VAL - 84) encoded as 8 bits
340...4435	011110 + (VAL - 340) encoded as 12 bits
-4435...-340	111110 + (-VAL - 340) encoded as 12 bits
4436...∞	011111 + (VAL - 4436) encoded as 32 bits
-∞...-4436	111111 + (-VAL - 4436) encoded as 32 bits
OOB	1000

3. After each bit is decoded: If $PREV < 256$ set

$$PREV = (PREV \ll 1) \text{ OR } D$$

Otherwise set

$$PREV = (((PREV \ll 1) \text{ OR } D) \text{ AND } 511) \text{ OR } 256$$

where D represents the value of the just-decoded bit.

Thus, PREV always contains the values of the eight most-recently-decoded bits, plus a leading **1** bit, which is used to indicate the number of bits decoded so far.

4. The sequence of bits decoded, interpreted according to Table A.1, gives the value that is the result of this invocation of the integer arithmetic decoding procedure.

Note that each type of data, and each integer arithmetic decoding procedure, uses a separate set of contexts: the contexts used for IAFS are separate from the contexts used for IADW, for example.

EXAMPLE — An invocation of IADW might go as follows.

- Set CX to “IADW**000000001**”. This identifies a particular adaptive probability estimate identified. Decode a bit. Suppose the value decoded (D) is **0**.
- Using CX = IADW**000000010**, decode a bit; suppose the value decoded is **1**.
- Using CX = IADW**000000101**, decode a bit; suppose the value decoded is **0**.
- Using CX = IADW**000001010**, decode a bit; suppose the value decoded is **1**.
- Using CX = IADW**000010101**, decode a bit; suppose the value decoded is **0**.
- Using CX = IADW**000101010**, decode a bit; suppose the value decoded is **0**.
- Using CX = IADW**001010100**, decode a bit; suppose the value decoded is **0**.
- The sequence of bits decoded so far is **0101000**. According to Table A.1 and Figure A.1, this corresponds to the value 12 ($S = 0, V = 12$), which is the result of this invocation of IADW.

A context is identified by an arithmetic integer decoding procedure name and a sequence of nine bits. Thus, each arithmetic integer decoding procedure requires 512 bytes of storage for its context memory.

A.3 The IAID decoding procedure

This decoding procedure is different from all the other integer arithmetic decoding procedure. It uses fixed-length representations of the values being decoded, and does not limit the number of previously-decoded bits used as part of the context. The length is equal to **SBSYMCODELEN**. This decoding procedure is only invoked from within the text region decoding procedure, so at the time of invocation **SBSYMCODELEN** is known.

The procedure for decoding an integer using the IAID decoding procedure is as follows.

1. Set

$$\text{PREV} = 1$$

2. Decode **SBSYMCODELEN** bits as follows

- (a) Decode a bit with CX equal to “IAID + PREV” where “+” represents concatenation, and the rightmost **SBSYMCODELEN** + 1 bits of PREV are used.

- (b) After each bit is decoded, set

$$\text{PREV} = (\text{PREV} \ll 1) \text{ OR } D$$

where D represents the value of the just-decoded bit.

Thus, PREV always contains the values of all the bits decoded so far, plus a leading **1** bit, which is used to indicate the number of bits decoded so far.

3. After **SBSYMCODELEN** bits have been decoded, set

$$\text{PREV} = \text{PREV} - 2^{\text{SBSYMCODELEN}}$$

This step has the effect of clearing the topmost (leading **1**) bit of PREV before returning it.

4. The contents of PREV are the result of this invocation of the IAID decoding procedure.

The number of contexts required is $2^{\text{SBSYMCODELEN}}$, which is less than twice the maximum symbol ID. Thus, the amount of memory needed for contexts can be calculated from the number of symbols, and is typically no more than two bytes per symbol.

EXAMPLE — Suppose that **SBSYMCODELEN** = 3. An invocation of IAID might go as follows.

- Using the adaptive probability estimate identified setting CX equal to “IAID**0001**”, decode a bit. Suppose the value decoded is **0**.
- Using CX = IAID**0010**, decode a bit; suppose the value decoded is **1**.
- Using CX = IAID**0101**, decode a bit; suppose the value decoded is **0**.
- At this point, PREV = **1010**. Apply Step 3; PREV is now **010**. Thus, the result of this invocation of the IAID decoding procedure is the value **010**, or (in decimal) 2.

The context identification used here depends on the value of **SBSYMCODELEN**. In all cases the arithmetic coder contexts will be reset in between changes of **SBSYMCODELEN**: **SBSYMCODELEN** never changes during the decoding of a single segment (but may change between segments).

Annex B
(normative)
Huffman Table Decoding Procedure

B.1 General description

Code tables may be used for encoding any type of numerical data in the Huffman variant coders. In many locations where a table is used, the encoder has the option of using one of the standard tables, or sending its own table. A code table segment provides the means to send such a custom table. The code table is a list of code table lines, each describing how to encode a single value, or a value from a specified range. A table may optionally be able to code for an OOB, which is an out-of-band signal to the decoding procedure using the table.

B.2 Code table structure

Figure B.1 shows the internal structure of an encoded Huffman table. It consists of a set of table lines, each of which describes the encoding for a range of numerical values. There are also, potentially, two special additional table lines that encode “open-ended” ranges. The smallest value that can be encoded in a table described according to this specification is -2^{31} and the largest value is $2^{31} - 1$, so these ranges are not really open-ended. There is also, potentially, an additional special table line that encodes an out-of-band value OOB.

Code table flags
Code table lowest value
Code table highest value
First table line
Second table line
...
Last table line
Lower range table line
Upper range table line
Out-of-band table line

Figure B.1 — Coded structure of a Huffman table.

Each table line specifies the length of the prefix that is associated with it and the number of bits that follow that prefix to encode a value.

A decoder decoding an encoded Huffman table shall decode the table that is produced by the following steps.

1. Decode the code table flags field as described in B.2.1. This sets the values HTOOB, HTPS and HTRS.
2. Decode the code table lowest value field as described in B.2.2. Let HTLOW be the value decoded.
3. Decode the code table highest value field as described in B.2.3. Let HTHIGH be the value decoded.
4. Set

$$\begin{aligned} \text{CURRANGELOW} &= \text{HTLOW} \\ \text{NTEMP} &= 0 \end{aligned}$$

5. Decode each table line as follows.

- (a) Read HTPS bits. Set $\text{PREFLEN}[\text{NTEMP}]$ to the value decoded.
- (b) Read HTRS bits. Let $\text{RANGELEN}[\text{NTEMP}]$ be the value decoded.
- (c) Set

$$\begin{aligned} \text{RANGELOW}[\text{NTEMP}] &= \text{CURRANGELOW} \\ \text{CURRANGELOW} &= \text{CURRANGELOW} + 2^{\text{RANGELEN}[\text{NTEMP}]} \\ \text{NTEMP} &= \text{NTEMP} + 1 \end{aligned}$$

(d) If $CURRANGELOW \geq HTHIGH$ then proceed to step 6.

6. Read HTPS bits. Let LOWPREFLEN be the value read.

7. Set

$$\begin{aligned} \text{PREFLEN}[\text{NTEMP}] &= \text{LOWPREFLEN} \\ \text{RANGELEN}[\text{NTEMP}] &= 32 \\ \text{RANGELOW}[\text{NTEMP}] &= \text{HTLOW} - 1 \\ \text{NTEMP} &= \text{NTEMP} + 1 \end{aligned}$$

This is the lower range table line for this table.

8. Read HTPS bits. Let HIGHPREFLEN be the value read.

9. Set

$$\begin{aligned} \text{PREFLEN}[\text{NTEMP}] &= \text{HIGHPREFLEN} \\ \text{RANGELEN}[\text{NTEMP}] &= 32 \\ \text{RANGELOW}[\text{NTEMP}] &= \text{HTHIGH} \\ \text{NTEMP} &= \text{NTEMP} + 1 \end{aligned}$$

This is the upper range table line for this table.

10. If HTOOB is **1**, then

(a) Read HTPS bits. Let OOBPREFLEN be the value read.

(b) Set

$$\begin{aligned} \text{PREFLEN}[\text{NTEMP}] &= \text{OOBPREFLEN} \\ \text{NTEMP} &= \text{NTEMP} + 1 \end{aligned}$$

This is the out-of-band table line for this table. Note that there is no range associated with this value.

11. Create the prefix codes using the algorithm described in B.3.

B.2.1 Code table flags

This one-byte field has the following bits defined:

Bit 0 HTOOB. If this bit is **1**, the table can code for an out-of-band value.

Bits 1–3 Number of bits used in code table line prefix size fields. The value of HTPS is the value of this field plus one.

Bits 4–6 Number of bits used in code table line range size fields. The value of HTRS is the value of this field plus one.

Bit 7 Reserved; must be zero.

B.2.2 Code table lowest value

This signed four-byte field is the lower bound of the first table line in the encoded table.

B.2.3 Code table highest value

This signed four-byte field is one larger than the upper bound of the last normal table line in the encoded table.

B.3 Assigning the prefix codes

Given the table of prefix code lengths, PREFLEN, and the number of codes to be assigned, NTEMP, this algorithm assigns a unique prefix code to each table line, of the length given by PREFLEN for that table line.

Note that the PREFLEN value 0 indicates that the table line is never used.

1. Build a histogram in the array LENCOUNT counting the number of times each prefix length value occurs in PREFLEN: $\text{LENCOUNT}[I]$ is the number of times that the value I occurs in the array PREFLEN.
2. Let LENMAX be the largest value for which $\text{LENCOUNT}[\text{LENMAX}] > 0$. Set

$$\begin{aligned}\text{CURLEN} &= 1 \\ \text{FIRSTCODE}[0] &= 0 \\ \text{LENCOUNT}[0] &= 0\end{aligned}$$

3. While $\text{CURLEN} \leq \text{LENMAX}$, perform the following operations.

(a) Set

$$\begin{aligned}\text{FIRSTCODE}[\text{CURLEN}] &= (\text{FIRSTCODE}[\text{CURLEN} - 1] + \text{LENCOUNT}[\text{CURLEN} - 1]) \times 2 \\ \text{CURCODE} &= \text{FIRSTCODE}[\text{CURLEN}] \\ \text{CURTEMP} &= 0\end{aligned}$$

(b) While $\text{CURTEMP} < \text{NTEMP}$, perform the following operations.

i. If $\text{PREFLEN}[\text{CURTEMP}] = \text{CURLEN}$, then set

$$\begin{aligned}\text{CODES}[\text{CURTEMP}] &= \text{CURCODE} \\ \text{CURCODE} &= \text{CURCODE} + 1\end{aligned}$$

ii. Set $\text{CURTEMP} = \text{CURTEMP} + 1$.

(c) Set

$$\text{CURLEN} = \text{CURLEN} + 1$$

After this algorithm has executed, then table line number I has been assigned a $\text{PREFLEN}[I]$ -bit long code, whose value is stored in the $\text{PREFLEN}[I]$ low-order bits of $\text{CODES}[I]$, unless $\text{PREFLEN}[I]$ was equal to zero, in which case that table line has not been assigned any code.

B.4 Using a Huffman table

To decode a value using a Huffman table, perform the following steps.

1. Read one bit at a time until the bit string read matches the code assigned to one of the table lines. Since no code forms a prefix of any other code, this is possible. Let I be the index of the table line whose code was decoded.
2. Read $\text{RANGELEN}[I]$ bits. Let HTOFFSET be the value read.
3. If HTOOB is 1 for this table, and table line I is the out-of-band table line for this table, then set

$$\text{HTVAL} = \text{OOB}$$

4. Otherwise, if table line I is the lower range table line for this table, then set

$$\text{HTVAL} = \text{RANGELOW}[I] - \text{HTOFFSET}$$

5. Otherwise, set

$$\text{HTVAL} = \text{RANGELOW}[I] + \text{HTOFFSET}$$

The value of HTVAL is the value decoded using this table. Note that this may be a numerical value or the special value OOB.

EXAMPLE — The encoding for Table B.1 might be the sequence of bytes, in hexadecimal

```
0x42 0x00 0x00 0x00 0x00 0x00 0x01
0x01 0x10 0x49 0x23 0x81 0x80
```

Decoding this according to the algorithm of B.2 proceeds as follows.

- The code table flags field, 0x42. This field itself breaks down into the fields, in binary, **0 100 001 0**, which decode to produce the assignments

```
HTOOB = 0
HTPS  = 2
HTRS  = 5
```

- The code table lowest value field, and the value of HTLOW, 0x00000000.
- The code table highest value field, and the value of HTHIGH, 0x00010110 (which, in decimal, is 65808).
- Three table lines, the lower range table line and the upper range table line. These are encoded as the sequence of bytes 0x49 0x23 0x81 0x80, or in binary, **01001001 00100011 10000001 10000000**. This bitstring is further broken down into the table lines as follows.

01 00100 The first two (HTPS) bits of this table line indicate a prefix length of 1, and the last five (HTRS) bits of this table line indicate a range length of 4.

10 01000 This table line has a prefix length of 2 and a range length of 8.

11 10000 This table line has a prefix length of 3 and a range length of 16.

00 The lower range table line has a prefix length of 0, indicating that this table line is not used.

11 The upper range table line has a prefix length of 3.

0000000 Seven bits of padding, to fill out the last byte.

After decoding these table lines, the value of NTEMP is 5. The arrays PREFLEN, RANGELEN and RANGELOW are

PREFLEN	1	2	3	0	3
RANGELEN	4	8	16	32	32
RANGELOW	0	16	272	-1	65808

Applying the algorithm of B.3 to this yields the array of codes, in binary,

```
CODES  0  10  110  X  111
```

where the X indicates that the lower range table line has not been assigned a code. Thus, the prefix code **0** precedes a 4-bit field encoding a value from 0 to 15; the prefix code **10** precedes an 8-bit field encoding a value from 16 to 271, and so on, as shown in Table B.1.

B.5 Standard Huffman tables

This section presents some standard Huffman tables than may be used in the appropriate contexts without having been previously transmitted.

Each Huffman table is presented in a form that is similar to the table transmission described above. The table parameter HTOOB is given (HTPS, HTRS, HTLOW and HTHIGH can be derived from the values in the table), followed by a list of table lines, giving the range to which that table line applies, the table line prefix length, table line range length, and the actual encoding (prefix and base value) for that table line; these table lines are followed by a lower and upper range table line, and optionally (depending on HTOOB) an out-of-band table line. In some cases the lower or upper range table lines are omitted from the tables as shown, indicating that these table lines are not used in the table (and would be assigned a PREFLEN value of zero).

Table B.1 — Standard Huffman table A

HTOOB	0		
VAL	PREFLEN	RANGELEN	Encoding
0...15	1	4	0 + VAL encoded as 4 bits
16...271	2	8	10 + (VAL - 16) encoded as 8 bits
272...65807	3	16	110 + (VAL - 272) encoded as 16 bits
65808...∞	3	32	111 + (VAL - 65808) encoded as 32 bits

Table B.2 — Standard Huffman table B

HTOOB	1		
VAL	PREFLEN	RANGELEN	Encoding
0	1	0	0
1	2	0	10
2	3	0	110
3...10	4	3	1110 + (VAL - 3) encoded as 3 bits
11...74	5	6	11110 + (VAL - 11) encoded as 6 bits
75...∞	6	32	111110 + (VAL - 75) encoded as 32 bits
OOB	6		111111

Table B.3 — Standard Huffman table C

HTOOB	1		
VAL	PREFLEN	RANGELEN	Encoding
-256...-1	8	8	11111110 + (VAL + 256) encoded as 8 bits
0	1	0	0
1	2	0	10
2	3	0	110
3...10	4	3	1110 + (VAL - 3) encoded as 3 bits
11...74	5	6	11110 + (VAL - 11) encoded as 6 bits
-∞...-257	8	32	11111111 + (-257 - VAL) encoded as 32 bits
75...∞	7	32	1111110 + (VAL - 75) encoded as 32 bits
OOB	6		111110

Table B.4 — Standard Huffman table D

HTOOB	0		

Table B.5 — Standard Huffman table E

HTOOB	0		
VAL	PREFLEN	RANGELEN	Encoding
-255...0	7	8	1111110 + (VAL + 255) encoded as 8 bits
1	1	0	0
2	2	0	10
3	3	0	110
4...11	4	3	1110 + (VAL - 4) encoded as 3 bits
12...75	5	6	11110 + (VAL - 12) encoded as 6 bits
-∞...-256	7	32	1111111 + (-256 - VAL) encoded as 32 bits
76...∞	6	32	111110 + (VAL - 76) encoded as 32 bits

Table B.6 — Standard Huffman table F

HTOOB	0		
VAL	PREFLEN	RANGELEN	Encoding
-2048...-1025	5	10	11100 + (VAL + 2048) encoded as 10 bits
-1024...-513	4	9	1000 + (VAL + 1024) encoded as 9 bits
-512...-257	4	8	1001 + (VAL + 512) encoded as 8 bits
-256...-129	4	7	1010 + (VAL + 256) encoded as 7 bits
-128...-65	5	6	11101 + (VAL + 128) encoded as 6 bits
-64...-33	5	5	11110 + (VAL + 64) encoded as 5 bits
-32...-1	4	5	1011 + (VAL + 32) encoded as 5 bits
0...127	2	7	00 + VAL encoded as 7 bits
128...255	3	7	010 + (VAL - 128) encoded as 7 bits
256...511	3	8	011 + (VAL - 256) encoded as 8 bits
512...1023	4	9	1100 + (VAL - 512) encoded as 9 bits
1024...2047	4	10	1101 + (VAL - 1024) encoded as 10 bits
-∞...-2049	6	32	111110 + (-2049 - VAL) encoded as 32 bits
2048...∞	6	32	111111 + (VAL - 2048) encoded as 32 bits

Table B.7 — Standard Huffman table G

HTOOB		0		
VAL	PREFLEN	RANGELEN	Encoding	
-1024...-513	4	9	1000 + (VAL + 1024) encoded as 9 bits	
-512...-257	3	8	000 + (VAL + 512) encoded as 8 bits	
-256...-129	4	7	1001 + (VAL + 256) encoded as 7 bits	
-128...-65	5	6	11010 + (VAL + 128) encoded as 6 bits	
-64...-32	5	5	11011 + (VAL + 64) encoded as 5 bits	
-32...-1	4	5	1010 + (VAL + 32) encoded as 5 bits	
0...31	4	5	1011 + VAL encoded as 5 bits	
32...63	5	5	11100 + (VAL - 32) encoded as 5 bits	
64...127	5	6	11101 + (VAL - 64) encoded as 6 bits	
128...255	4	7	1100 + (VAL - 128) encoded as 7 bits	
256...511	3	8	001 + (VAL - 256) encoded as 8 bits	
512...1023	3	9	010 + (VAL - 512) encoded as 9 bits	
1024...2047	3	10	011 + (VAL - 1024) encoded as 10 bits	
-∞...-1025	5	32	11110 + (-1025 - VAL) encoded as 32 bits	
2048...∞	5	32	11111 + (VAL - 2048) encoded as 32 bits	

Table B.8 — Standard Huffman table H

HTOOB		1		
VAL	PREFLEN	RANGELEN	Encoding	
-15...-8	8	3	11111100 + (VAL + 15) encoded as 3 bits	
-7...-6	9	1	111111100 + (VAL + 7) encoded as 1 bits	
-5...-4	8	1	11111101 + (VAL + 5) encoded as 1 bits	
-3	9	0	111111101	
-2	7	0	1111100	
-1	4	0	1010	
0...1	2	1	00 + VAL encoded as 1 bits	
2	5	0	11010	
3	6	0	111010	
4...19	3	4	100 + (VAL - 4) encoded as 4 bits	
20...21	6	1	111011 + (VAL - 20) encoded as 1 bits	
22...37	4	4	1011 + (VAL - 22) encoded as 4 bits	
38...69	4	5	1100 + (VAL - 38) encoded as 5 bits	
70...133	5	6	11011 + (VAL - 70) encoded as 6 bits	
134...261	5	7	11100 + (VAL - 134) encoded as 7 bits	
262...389	6	7	111100 + (VAL - 262) encoded as 7 bits	
390...645	7	8	1111101 + (VAL - 390) encoded as 8 bits	
646...1669	6	10	111101 + (VAL - 646) encoded as 10 bits	
-∞...-16	9	32	111111110 + (-16 - VAL) encoded as 32 bits	
1670...∞	9	32	111111111 + (VAL - 1670) encoded as 32 bits	
OOB	2		01	

Table B.9 — Standard Huffman table I

HTOOB	1		
VAL	PREFLEN	RANGELEN	Encoding
-31...-16	8	4	11111100 + (VAL + 31) encoded as 4 bits
-15...-12	9	2	111111100 + (VAL + 15) encoded as 2 bits
-11...-8	8	2	11111101 + (VAL + 11) encoded as 2 bits
-7...-6	9	1	111111101 + (VAL + 7) encoded as 1 bits
-5...-4	7	1	1111100 + (VAL + 5) encoded as 1 bits
-3...-2	4	1	1010 + (VAL + 3) encoded as 1 bits
-1...0	3	1	010 + (VAL + 1) encoded as 1 bits
1...2	3	1	011 + (VAL - 1) encoded as 1 bits
3...4	5	1	11010 + (VAL - 3) encoded as 1 bits
5...6	6	1	111010 + (VAL - 5) encoded as 1 bits
7...38	3	5	100 + (VAL - 7) encoded as 5 bits
39...42	6	2	111011 + (VAL - 39) encoded as 2 bits
43...74	4	5	1011 + (VAL - 43) encoded as 5 bits
75...138	4	6	1100 + (VAL - 75) encoded as 6 bits
139...266	5	7	11011 + (VAL - 139) encoded as 7 bits
267...522	5	8	11100 + (VAL - 267) encoded as 8 bits
523...778	6	8	111100 + (VAL - 523) encoded as 8 bits
779...1290	7	9	1111101 + (VAL - 779) encoded as 9 bits
1291...3338	6	11	111101 + (VAL - 1291) encoded as 11 bits
-∞...-32	9	32	111111110 + (-32 - VAL) encoded as 32 bits
3339...∞	9	32	111111111 + (VAL - 3339) encoded as 32 bits
OOB	2		00

Table B.10 — Standard Huffman table J

HTOOB		1	
VAL	PREFLEN	RANGELEN	Encoding
-21...-6	7	4	1111010 + (VAL + 21) encoded as 4 bits
-5	8	0	11111100
-4	7	0	1111011
-3	5	0	11000
-2...1	2	2	00 + (VAL + 2) encoded as 2 bits
2	5	0	11001
3	6	0	110110
4	7	0	1111100
5	8	0	11111101
6...69	2	6	01 + (VAL - 6) encoded as 6 bits
70...101	5	5	11010 + (VAL - 70) encoded as 5 bits
102...133	6	5	110111 + (VAL - 102) encoded as 5 bits
134...197	6	6	111000 + (VAL - 134) encoded as 6 bits
198...325	6	7	111001 + (VAL - 198) encoded as 7 bits
326...581	6	8	111010 + (VAL - 326) encoded as 8 bits
582...1093	6	9	111011 + (VAL - 582) encoded as 9 bits
1094...2117	6	10	111100 + (VAL - 1094) encoded as 10 bits
2118...4165	7	11	1111101 + (VAL - 2118) encoded as 11 bits
-∞...-22	8	32	11111110 + (-22 - VAL) encoded as 32 bits
4166...∞	8	32	11111111 + (VAL - 4166) encoded as 32 bits
OOB	2		10

Table B.11 — Standard Huffman table K

HTOOB		0	
VAL	PREFLEN	RANGELEN	Encoding
1	1	0	0
2...3	2	1	10 + (VAL - 2) encoded as 1 bits
4	4	0	1100
5...6	4	1	1101 + (VAL - 5) encoded as 1 bits
7...8	5	1	11100 + (VAL - 7) encoded as 1 bits
9...12	5	2	11101 + (VAL - 9) encoded as 2 bits
13...16	6	2	111100 + (VAL - 13) encoded as 2 bits
17...20	7	2	1111010 + (VAL - 17) encoded as 2 bits
21...28	7	3	1111011 + (VAL - 21) encoded as 3 bits
29...44	7	4	1111100 + (VAL - 29) encoded as 4 bits
45...76	7	5	1111101 + (VAL - 45) encoded as 5 bits
77...140	7	6	1111110 + (VAL - 77) encoded as 6 bits
141...∞	7	32	11111111 + (VAL - 141) encoded as 32 bits

Table B.12 — Standard Huffman table L

HTOOB	0		
VAL	PREFLEN	RANGELEN	Encoding
1	1	0	0
2	2	0	10
3...4	3	1	110 + (VAL - 3) encoded as 1 bits
5	5	0	11100
6...7	5	1	11101 + (VAL - 6) encoded as 1 bits
8...9	6	1	111100 + (VAL - 8) encoded as 1 bits
10	7	0	1111010
11...12	7	1	1111011 + (VAL - 11) encoded as 1 bits
13...16	7	2	1111100 + (VAL - 13) encoded as 2 bits
17...24	7	3	1111101 + (VAL - 17) encoded as 3 bits
25...40	7	4	1111110 + (VAL - 25) encoded as 4 bits
41...72	8	5	11111110 + (VAL - 41) encoded as 5 bits
73...∞	8	32	11111111 + (VAL - 73) encoded as 32 bits

Table B.13 — Standard Huffman table M

HTOOB	0		
VAL	PREFLEN	RANGELEN	Encoding
1	1	0	0
2	3	0	100
3	4	0	1100
4	5	0	11100
5...6	4	1	1101 + (VAL - 5) encoded as 1 bits
7...14	3	3	101 + (VAL - 7) encoded as 3 bits
15...16	6	1	111010 + (VAL - 15) encoded as 1 bits
17...20	6	2	111011 + (VAL - 17) encoded as 2 bits
21...28	6	3	111100 + (VAL - 21) encoded as 3 bits
29...44	6	4	111101 + (VAL - 29) encoded as 4 bits
45...76	6	5	111110 + (VAL - 45) encoded as 5 bits
77...140	7	6	1111110 + (VAL - 77) encoded as 6 bits
141...∞	7	32	1111111 + (VAL - 141) encoded as 32 bits

Table B.14 — Standard Huffman table N

HTOOB	0		
VAL	PREFLEN	RANGELEN	Encoding
-2	3	0	100
-1	3	0	101
0	1	0	0
1	3	0	110
2	3	0	111

Table B.15 — Standard Huffman table O

HTOOB	0		
VAL	PREFLEN	RANGELEN	Encoding
-24... -9	7	4	1111100 + (VAL + 24) encoded as 4 bits
-8... -5	6	2	111100 + (VAL + 8) encoded as 2 bits
-4... -3	5	1	11100 + (VAL + 4) encoded as 1 bits
-2	4	0	1100
-1	3	0	100
0	1	0	0
1	3	0	101
2	4	0	1101
3... 4	5	1	11101 + (VAL - 3) encoded as 1 bits
5... 8	6	2	111101 + (VAL - 5) encoded as 2 bits
9... 24	7	4	1111101 + (VAL - 9) encoded as 4 bits
-∞... -25	7	32	1111110 + (-25 - VAL) encoded as 32 bits
25... ∞	7	32	1111111 + (VAL - 25) encoded as 32 bits

Annex C
(normative)
Gray-scale Image Decoding Procedure

C.1 General description

This decoding procedure is used by the halftone region decoding procedure to produce an array of gray-scale values, which are then used as indexes into a dictionary of patterns.

C.2 Input parameters

The parameters to this decoding procedure are shown in Table C.1.

Table C.1 — Parameters for the gray-scale image decoding procedure.

Name	Type	Size (bits)	Signed?	Description and restrictions
GSMMR	Integer	1	N	Specifies whether MMR is used.
GSUSES SKIP	Integer	1	N	Specifies whether skipping of gray-scale values may occur.
GSBPP	Integer	6	N	The number of bits per gray-scale value.
GSW	Integer	32	N	The width of the gray-scale image.
GSH	Integer	32	N	The height of the gray-scale image.
GSTEMPLATE	Integer	2	N	The template used to code the gray-scale bitplanes. **
GSKIP	Bitmap			A mask indicating which values should be skipped. GSW pixels wide, GSH pixels high. *

* Unused if **GSUSES SKIP** = 0.

** Unused if **GSMMR** = 1.

C.3 Return value

The variable whose value is the result of this decoding procedure is shown in Table C.2.

Table C.2 — Return value from the gray-scale image decoding procedure.

Name	Type	Size (bits)	Signed?	Description and restrictions
GSVALS	Array			The decoded gray-scale image. The array is GSW wide, GSH high.

C.4 Variables used in decoding

The variables used by this decoding procedure are shown in Table C.3.

Table C.3 — Variables used in the gray-scale image decoding procedure.

Name	Type	Size (bits)	Signed?	Description and restrictions
GSPLANES	Array of bitmaps			Bitplanes of the gray-scale image. There are GSBPP bitplanes in GSPLANES . Each bitplane is GSW pixels wide, GSH pixels high.
<i>J</i>	Integer	32	Y	Bitplane counter

C.5 Decoding the gray-scale image

The gray-scale image is obtained by decoding **GSBPP** bitplanes. These bitplanes are denoted (from least significant to most significant) $\text{GSPLANES}[0]$, $\text{GSPLANES}[1]$, ..., $\text{GSPLANES}[\text{GSBPP} - 1]$. The bitplanes are Gray-coded, so that each bitplane's true value is equal to its coded value XORed with the next-more-significant bitplane.

The gray-scale image is obtained by the following procedure:

1. Decode $\text{GSPLANES}[\text{GSBPP} - 1]$ using the generic region decoding procedure. The parameters to the generic region decoding procedure are as shown in Table C.4.

Table C.4 — Parameters used to decode a bitplane of the gray-scale image.

Name	Value
MMR	GSMMR
GBW	GSW
GBH	GSH
GBTEMPLATE	GSTEMPLATE
TPGDON	0
USESKIP	GSUSESKIP
SKIP	GSKIP
GBATX₁	3 if GSTEMPLATE ≤ 1; 2 if GSTEMPLATE ≥ 2.
GBATY₁	-1
GBATX₂	-3
GBATY₂	-1
GBATX₃	2
GBATY₃	-2
GBATX₄	-2
GBATY₄	-2

2. Set $J = \text{GSBPP} - 2$.
3. While $J \geq 0$, perform the following steps.
 - (a) Decode $\text{GSPLANES}[J]$ using the generic region decoding procedure. The parameters to the generic region decoding procedure are as shown in Table C.4.
 - (b) For each pixel (x, y) in $\text{GSPLANES}[J]$, set

$$\text{GSPLANES}[J][x, y] = \text{GSPLANES}[J + 1][x, y] \text{ XOR } \text{GSPLANES}[J][x, y]$$

- (c) Set $J = J - 1$.

4. For each (x, y) , set

$$\text{GSVALS}[x, y] = \sum_{J=0}^{\text{GSBPP}-1} \text{GSPLANES}[J][x, y] \times 2^J$$

Annex D (normative) File Formats

There are two standalone file organisations possible for a JBIG2 bitstream. There is also a third organisation, not intended for standalone usage, but instead to allow JBIG2-encoded data to be embedded in another file format.

NOTE — It is recommended that “.jbig2” is used as the extension for JBIG2 files. In environments where only three characters are allowed, “.jb2” is recommended. It is also recommended that JBIG2 decoders recognise both extensions.

D.1 Sequential organisation

This is a standalone file organisation. This organisation is intended for streaming applications, where the decoder is guaranteed to begin at the start of the bitstream and decode everything up to the end of the bitstream.

In this organisation, the file structure looks like Figure D.1. A file header is followed by a sequence of segments. The two parts of each segment are stored together: first the segment header then the segment data.

The segments must appear in increasing order of their segment numbers: no segment may precede a segment having a lower number than it.

File header
Segment 1 segment header
Segment 1 data
Segment 2 segment header
Segment 2 data
...
Segment N segment header
Segment N data

Figure D.1 — Sequential organisation

D.2 Random-access organisation

This is a standalone file organisation. This organisation is intended for random-access applications, where the decoder might want to process parts of the file in an arbitrary order, such as decoding all the odd-numbered pages before any even-numbered page, or decode pages individually in response to some user input. The ability to perform random access is therefore important.

In this organisation, the file structure looks like Figure D.2. A file header is followed by a sequence of segments headers; the last segment header is followed by the data for the first segment, then the data for the second segment, and so on. The last segment must be an end of file segment; otherwise, it is impossible for the decoder to determine when it has read the last segment header.

The segments must appear in increasing order of their segment numbers: no segment may precede a segment having a lower number than it.

D.3 Embedded organisation

This is not a standalone file organisation, but relies on some other file format to carry the JBIG2 segments. Each segment is stored by concatenating its segment header and segment data parts, but there is no defined storage order for these segments. The embedding file format is allowed to store those segments in any order, and may separate them by arbitrary data.

Applications may wish to precede and follow JBIG2 data with a unique two-byte combination (marker) so that the JBIG2 data can be detected within other data streams. It is suggested to use 0xFF 0xAA for the starting marker and 0xFF 0xAB for the ending marker. These markers are not considered to be part of the JBIG2 data. It should be noted that the first byte of a segment header is unlikely to take on the value 0xFF. Note that the two-byte sequences 0xFF 0xAA and 0xFF 0xAB may occur by chance within JBIG2 segments.

File header
Segment 1 segment header
Segment 2 segment header
...
Segment N segment header
Segment 1 data
Segment 2 data
...
Segment N data

Figure D.2 — Random-access organisation

NOTE — The intent of the embedded organisation is that many current systems can benefit from incorporating improved bi-level image compression. However, the best way to do this is not always to incorporate an entire JBIG2 bitstream as a monolithic entity, as this can conflict with other constraints. For example, the system might have its own ideas of how pages must be divided up, which might not agree with JBIG2’s ideas. Thus, JBIG2 is flexible in allowing the embedding system to store JBIG2 data in whatever way is most convenient.

D.4 File header syntax

A file header contains the following fields, in order.

ID string See D.4.1.

File header flags See D.4.2.

Number of pages See D.4.3.

D.4.1 ID string

This is an 8-byte sequence containing 0x97 0x4A 0x42 0x32 0x0D 0x0A 0x1A 0x0A.

NOTE — This is similar to the PNG ID string. The first character is nonprintable, so that the file cannot be mistaken for ASCII. The first character’s high bit is set, to detect passing through a 7-bit channel. The next three bytes are JB2, and are intended to allow a human looking at the header to guess the file type. The following bytes are CR LF CONTROL-Z LF; any corruption by CR/LF translation and DOS file truncation can be detected immediately.

D.4.2 File header flags

This is a 1-byte field. The bits that are defined are

Bit 0 File organisation type. If this bit is **0**, the file uses the random-access organisation. If this bit is **1**, the file uses the sequential organisation.

NOTE — Note that there is no way to indicate the embedded organisation, as that organisation does not include a JBIG2 file header.

Bit 1 Unknown number of pages. If this bit is **0**, then the number of pages contained in the file is known. If this bit is **1**, then the number of pages contained in the file was not known at the time that the file header was coded.

Bits 2–7 Reserved; must be **0**.

D.4.3 Number of pages

This is a 4-byte field, and is not present if the “unknown number of pages” bit was **1**. If present, it must equal the number of pages contained in the file.

Annex E (normative) Arithmetic Coding

An adaptive binary arithmetic coder may be used as the entropy coder when allowed by the models. The models used with adaptive binary arithmetic coding are defined in 6.2, 6.3 and Annex A. In this Annex the basic arithmetic coding procedures are defined.

In this Annex and all of its subclauses, the flow charts and tables are normative only in the sense that they are defining an output that alternative implementations shall duplicate. In H.2 a simple test example is given which should be helpful in determining if a given implementation is correct.

E.1 Binary encoding

Figure E.1 shows a simple block diagram of the binary adaptive arithmetic encoder. The decision (D) and context (CX) pairs are processed together to produce compressed data (CD) output. Both D and CX are provided by the model unit (not shown). CX selects the probability estimate to use during the coding of D. In this Recommendation | International Standard, CX is a label for a context, formed by some character string followed by a string of bits.

EXAMPLE — Two possible values of CX are “IADW001010100” and “GB1110110010000000”.




Figure E.1 — Arithmetic encoder inputs and outputs.

E.1.1 Recursive interval subdivision

The recursive probability interval subdivision of Elias coding is the basis for the binary arithmetic coding process. With each binary decision the current probability interval is subdivided into two sub-intervals, and the code string is modified (if necessary) so that it points to the base (the lower bound) of the probability sub-interval assigned to the symbol which occurred.

In the partitioning of the current interval into two sub-intervals, the sub-interval for the more probable symbol (MPS) is ordered above the sub-interval for the less probable symbol (LPS). Therefore, when the MPS is coded, the LPS sub-interval is added to the code string. This coding convention requires that symbols be recognised as either MPS or LPS, rather than 0 or 1. Consequently, the size of the LPS interval and the sense of the MPS for each decision must be known in order to code that decision.

Since the code string always points to the base of the current interval, the decoding process is a matter of determining, for each decision, which sub-interval is pointed to by the code string. This is also done recursively, using the same interval sub-division process as in the encoder. Each time a decision is decoded, the decoder subtracts any interval the encoder added to the code string. Therefore, the code string in the decoder is a pointer into the current interval relative to the base of the current interval. Since the coding process involves addition of binary fractions rather than concatenation of integer code words, the more probable binary decisions can often be coded at a cost of much less than one bit per decision.

E.1.2 Coding conventions and approximations

The coding operations are done using fixed precision integer arithmetic and using an integer representation of fractional values in which $0x8000$ is equivalent to decimal 0.75. The interval A is kept in the range $0.75 \leq A < 1.5$ by doubling it whenever the integer value falls below $0x8000$.

The code register C is also doubled each time A is doubled. Periodically - to keep C from overflowing - a byte of data is removed from the high order bits of the C-register and placed in an external compressed data string buffer. Carry-over into the external buffer is resolved by a bit stuffing procedure.

Keeping A in the range $0.75 \leq A < 1.5$ allows a simple arithmetic approximation to be used in the interval subdivision. If the interval is A and the current estimate of the LPS probability is Q_e , a precise calculation of the sub-intervals would require:

$$\begin{aligned} A - (Q_e \times A) &= \text{sub-interval for the MPS} \\ Q_e \times A &= \text{sub-interval for the LPS} \end{aligned}$$

Because the value of A is of order unity, these are approximated by

$$\begin{aligned} A - Q_e &= \text{sub-interval for the MPS} \\ Q_e &= \text{sub-interval for the LPS} \end{aligned}$$

Whenever the MPS is coded, the value of Q_e is added to the code register and the interval is reduced to $A - Q_e$. Whenever the LPS is coded, the code register is left unchanged and the interval is reduced to Q_e . The precision range required for A is then restored, if necessary, by renormalisation of both A and C .

With the process illustrated above, the approximations in the interval subdivision process can sometimes make the LPS sub-interval larger than the MPS sub-interval. If, for example, the value of Q_e is 0.5 and A is at the minimum allowed value of 0.75, the approximate scaling gives 1/3 of the interval to the MPS and 2/3 to the LPS. To avoid this size inversion, the MPS and LPS intervals are exchanged whenever the LPS interval is larger than the MPS interval. This MPS/LPS conditional exchange can only occur when a renormalisation is needed.

Whenever a renormalisation occurs, a probability estimation process is invoked which determines a new probability estimate for the context currently being coded. No explicit symbol counts are needed for the estimation. The relative probabilities of renormalisation after coding an LPS and MPS provide an approximate symbol counting mechanism which is used to directly estimate the probabilities.

E.2 Description of the arithmetic encoder

The ENCODER (Figure E.2) initialises the encoder through the INITENC procedure. CX and D pairs are read and passed on to ENCODE until all pairs have been read. The probability estimation procedures which provide adaptive estimates of the probability for each context are embedded in ENCODE. Bytes of compressed data are output when no longer modifiable. When all of the CX and D pairs have been read (Finished?), FLUSH sets the contents of the C-register to as many 1-bits as possible and then outputs the final bytes. FLUSH also terminates the encoding operations and generates the required terminating marker.

E.2.1 Encoder code register conventions

The flow charts given in this subclause assume the following register structures for the encoder:

	MSB			LSB
C-register	0000cbbb	bbbbbbsss	xxxxxxxx	xxxxxxxx
A-register	00000000	00000000	aaaaaaaa	aaaaaaaa

The "a" bits are the fractional bits in the A-register (the current interval value) and the "x" bits are the fractional bits in the code register. The "s" bits are spacer bits which provide useful constraints on carry-over, and the "b" bits indicate the bit positions from which the completed bytes of the data are removed from the C-register. The "c" bit is a carry bit.

The detailed description of bit stuffing and the handling of carry-over will be given in a later part of this Annex.

E.2.2 Encoding a decision (ENCODE)

The ENCODE procedure determines whether the decision D is a 0 or not. Then a CODE0 or a CODE1 procedure is called appropriately. Often embodiments will not have an ENCODE procedure, but will call the CODE0 or CODE1 procedures directly to code a 0-decision or a 1-decision.

E.2.3 Encoding a 1 or 0 (CODE1 and CODE0)

When a given binary decision is coded, one of two possibilities occurs - the symbol is either the more probable symbol or it is the less probable symbol. CODE1 and CODE0 are illustrated in Figures E.4 and E.5. In these figures, CX is the context. For each context, the index of the probability estimate which is to be used in the coding operations and the MPS value are stored. MPS(CX) is the sense (0 or 1) of the MPS for context CX.




Figure E.2 — Encoder for the MQ-coder.




Figure E.3 — ENCODE procedure.




Figure E.4 — CODE1 procedure.




Figure E.5 — CODE0 procedure.

E.2.4 Encoding an MPS or LPS (CODEMPS and CODELPS)

The CODELPS (Figure E.6) procedure usually consists of a scaling of the interval to $Q_e(I(CX))$, the probability estimate of the LPS determined from the index I stored for context CX . The upper interval is first calculated so it can be compared to the lower interval to confirm that Q_e has the smaller size. It is always followed by a renormalisation (RENORME). In the event that the interval sizes are inverted, however, the conditional MPS/LPS exchange occurs and the upper interval is coded. In either case, the probability estimate is updated. If the SWITCH flag for the index $I(CX)$ is set, then the MPS(CX) is inverted. A new index I is saved at CX as determined from the next LPS index (NLPS) column in Table E.1.




Figure E.6 — CODELPS procedure with conditional MPS/LPS exchange.

The CODEMPS (Figure E.7) procedure usually reduces the size of the interval to the MPS sub-interval and adjusts the code register so that it points to the base of the MPS sub-interval. However, if the interval sizes are inverted, the LPS sub-interval is coded instead. Note that the size inversion cannot occur unless a renormalisation (RENORME) is required after the coding of the symbol. The probability estimate update changes the index $I(CX)$ according to the next MPS index (NMPS) column in Table E.1.




Figure E.7 — CODEMPS procedure with conditional MPS/LPS exchange.

E.2.5 Probability estimation

Table E.1 shows the Q_e value associated with each Q_e index. The Q_e values are expressed as hexadecimal integers, as binary integers, and as decimal fractions. To convert the 15 bit integer representation of Q_e to the decimal probability, the Q_e values are divided by $(4/3) \times (0x8000)$.

The estimator can be defined as a finite-state machine — a table of Q_e indexes and associated next states for each type of renormalisation (i.e., new table positions) - as shown in Table E.1. The change in state occurs only when the arithmetic coder interval register is renormalised. This is always done after coding the LPS, and whenever the interval register is less than $0x8000$ (0.75 in decimal notation) after coding the MPS.

After an LPS renormalisation, NLPS gives the new index for the LPS probability estimate. After an MPS renormalisation, NMPS gives the new index for the LPS probability estimate. If Switch is 1, the MPS symbol sense is reversed.

The index to the current estimate is part of the information stored for context CX. This index is used as the index to the table of values in NMPS, which gives the next index for an MPS renormalisation. This index is saved in the context storage at CX. MPS(CX) does not change.

The procedure for estimating the probability on the LPS renormalisation path is similar to that of an MPS renormalisation, except that when $\text{Switch}(I(\text{CX}))$ is 1, the sense of MPS(CX) is inverted.

The final index state 46 can be used to establish a fixed 0.5 probability estimate.

E.2.6 Renormalisation in the encoder (RENORME)

Renormalisation is very similar in both encoder and decoder, except that in the encoder it generates compressed bits and in the decoder it consumes compressed bits.

The RENORME procedure for the encoder renormalisation is illustrated in Figure E.8. Both the interval register A and the code register C are shifted, one bit at a time. The number of shifts is counted in the counter CT, and when CT is counted down to zero, a byte of compressed data is removed from C by the procedure BYTEOUT. Renormalisation continues until A is no longer less than $0x8000$.

E.2.7 Compressed data output (BYTEOUT)

The BYTEOUT routine called from RENORME is illustrated in Figure E.9. This routine contains the bit-stuffing procedures which are needed to limit carry propagation into the completed bytes of compressed data. The conventions used make it impossible for a carry to propagate through more than the byte most recently written to the compressed data buffer.

The procedure in the block in the lower right section does bit stuffing after a $0xFF$ byte; the similar procedure on the left is for the case where bit stuffing is not needed.

B is the byte pointed to by the compressed data buffer pointer BP. If B is not a $0xFF$ byte, the carry bit is checked. If the carry bit is set, it is added to B and B is again checked to see if a bit needs to be stuffed in the next byte. After the need for bit stuffing has been determined, the appropriate path is chosen, BP is incremented and the new value of B is removed from the code register "b" bits.

E.2.8 Initialisation of the encoder (INITENC)

The INITENC procedure is used to start the arithmetic coder. The basic steps are shown in Figure E.10.

The interval register and code register are set to their initial values, and the bit counter is set. Setting $CT = 12$ reflects the fact that there are three spacer bits in the register which need to be filled before the field from which the bytes are removed is reached. Note that BP always points to the byte preceding the position BPST where the first byte is placed. Therefore, if the preceding byte is a $0xFF$ byte, a spurious bit stuff will occur, but can be compensated for by increasing CT. Note that the default initialisation of the statistics bins is $MPS = 0$ and $I = 0$ (i.e. $Q_e = 0x5601$ or decimal 0.503937).

E.2.9 Termination of encoding (FLUSH)

The FLUSH procedure shown in Figure E.11 is used to terminate the encoding operations and generate the required terminating marker. The procedure guarantees that the $0xFF$ prefix to the marker code overlaps the final bits of the compressed data. This guarantees that any marker code at the end of the compressed data will be recognized and interpreted before decoding is complete.

The first part of the FLUSH procedure sets as many bits in the C-register to 1 as possible as shown in Figure E.12. The exclusive upper bound for the C-register is the sum of the C-register and the interval register. The

Table E.1 — Qe values and probability estimation process

Index	Qe_Value			NMPS	NLPS	SWITCH
	(hexadecimal)	(binary)	(decimal)			
0	0x5601	0101011000000001	0.503937	1	1	1
1	0x3401	0011010000000001	0.304715	2	6	0
2	0x1801	0001100000000001	0.140650	3	9	0
3	0x0AC1	0000101011000001	0.063012	4	12	0
4	0x0521	0000010100100001	0.030053	5	29	0
5	0x0221	0000001000100001	0.012474	38	33	0
6	0x5601	0101011000000001	0.503937	7	6	1
7	0x5401	0101010000000001	0.492218	8	14	0
8	0x4801	0100100000000001	0.421904	9	14	0
9	0x3801	0011100000000001	0.328153	10	14	0
10	0x3001	0011000000000001	0.281277	11	17	0
11	0x2401	0010010000000001	0.210964	12	18	0
12	0x1C01	0001110000000001	0.164088	13	20	0
13	0x1601	0001011000000001	0.128931	29	21	0
14	0x5601	0101011000000001	0.503937	15	14	1
15	0x5401	0101010000000001	0.492218	16	14	0
16	0x5101	0101000100000001	0.474640	17	15	0
17	0x4801	0100100000000001	0.421904	18	16	0
18	0x3801	0011100000000001	0.328153	19	17	0
19	0x3401	0011010000000001	0.304715	20	18	0
20	0x3001	0011000000000001	0.281277	21	19	0
21	0x2801	0010100000000001	0.234401	22	19	0
22	0x2401	0010010000000001	0.210964	23	20	0
23	0x2201	0010001000000001	0.199245	24	21	0
24	0x1C01	0001110000000001	0.164088	25	22	0
25	0x1801	0001100000000001	0.140650	26	23	0
26	0x1601	0001011000000001	0.128931	27	24	0
27	0x1401	0001010000000001	0.117212	28	25	0
28	0x1201	0001001000000001	0.105493	29	26	0
29	0x1101	0001000100000001	0.099634	30	27	0
30	0x0AC1	0000101011000001	0.063012	31	28	0
31	0x09C1	0000100111000001	0.057153	32	29	0
32	0x08A1	0000100010100001	0.050561	33	30	0
33	0x0521	0000010100100001	0.030053	34	31	0
34	0x0441	0000010001000001	0.024926	35	32	0
35	0x02A1	0000001010100001	0.015404	36	33	0
36	0x0221	0000001000100001	0.012474	37	34	0
37	0x0141	0000000101000001	0.007347	38	35	0
38	0x0111	0000000100010001	0.006249	39	36	0
39	0x0085	0000000010000101	0.003044	40	37	0
40	0x0049	0000000001001001	0.001671	41	38	0
41	0x0025	0000000000100101	0.000847	42	39	0
42	0x0015	0000000000010101	0.000481	43	40	0
43	0x0009	0000000000001001	0.000206	44	41	0
44	0x0005	0000000000000101	0.000114	45	42	0
45	0x0001	0000000000000001	0.000023	45	43	0
46	0x5601	0101011000000001	0.503937	46	46	0




Figure E.8 — Encoder renormalisation procedure.




Figure E.9 — BYTEOUT procedure for encoder.




Figure E.10 — Initialisation of the encoder.

low order 16 bits of C are forced to 1, and the result is compared to the upper bound. If C is too big, the leading 1-bit is removed, reducing C to a value which is within the interval.

The byte in the C-register is then completed by shifting C, and two bytes are then removed. If the second byte is not 0xFF, another byte is added to the compressed data which is guaranteed to be 0xFF.

E.2.10 Minimisation of the compressed data

If desired, the compressed data can be truncated after the FLUSH procedure is complete. If a sequence of 1-bits is generated by the arithmetic coder, bit stuffing will produce pairs of 0xFF, 0x7F bytes. These byte pairs can be trimmed from the compressed data, provided that the earliest 0xFF byte in the sequence is not removed. This remaining 0xFF byte then becomes the prefix to the marker code which terminates the compressed data.

Decoding is not affected by this trimming process because the convention is used in the decoder that when a marker code is encountered, 1-bits (without bit stuffing) are supplied to the decoder until the coding interval is complete.

E.3 Arithmetic decoding procedure

Figure E.13 shows a simple block diagram of a binary adaptive arithmetic decoder. The compressed data CD and a context CX from the decoder's model unit (not shown) are input to the arithmetic decoder. The decoder's output is the decision D. The encoder and decoder model units need to supply exactly the same context CX for each given decision.

The DECODER (Figure E.14) initialises the decoder through INITDEC. Contexts, CX, and bytes of compressed data (as needed) are read and passed on to DECODE until all contexts have been read. The DECODE routine decodes the binary decision D and returns a value of either 0 or 1. The probability estimation procedures which provide adaptive estimates of the probability for each context are embedded in DECODE. When all contexts have been read (Finished?), the compressed data has been decompressed.

E.3.1 Decoder code register conventions

The flow charts given in this subclause assume the following register structures for the decoder:




Figure E.11 — FLUSH procedure.




Figure E.12 — Setting the final bits in the C register.




Figure E.13 — Arithmetic decoder inputs and outputs.




Figure E.14 — Decoder for the MQ-coder.

	15	0
Chigh register	xxxxxxxx	xxxxxxxx
Clow register	bbbbbbbb	00000000
A-register	aaaaaaaa	aaaaaaaa

Chigh and Clow can be thought of as one 32 bit C-register in that renormalisation of C shifts a bit of new data from bit 15 of Clow to bit 0 of Chigh. However, the decoding comparisons use Chigh alone. New data is inserted into the "b" bits of Clow one byte at a time.

The detailed description of the handling of data with stuff-bits will be given later in this subclause.

Note that the comparisons shown in the various procedures in this section assume precisions greater than 16 bits. Logical comparisons can be used with 16 bit precision.

E.3.2 Decoding a decision (DECODE)

The decoder decodes one binary decision at a time. After decoding the decision, the decoder subtracts any amount from the code string that the encoder added. The amount left in the code string is the offset from the base of the current interval to the sub-interval allocated to all binary decisions not yet decoded. In the first test in the Decode procedure illustrated in Figure E.15 the Chigh register is compared to the size of the LPS sub-interval. Unless a conditional exchange is needed, this test determines whether a MPS or LPS is decoded. If Chigh is logically greater than or equal to the LPS probability estimate Q_e for the current index I stored at CX, then Chigh is decremented by that amount. If A is not less than $0x8000$, then the MPS sense stored at CX is used to set the decoded decision D.

When a renormalisation is needed, the MPS/LPS conditional exchange may have occurred. For the MPS path the conditional exchange procedure is shown in Figure E.16. As long as the MPS sub-interval size A calculated as the first step in Figure E.16 is not logically less than the LPS probability estimate $Q_e(I(CX))$, an MPS did occur and the decision can be set from MPS(CX). Then the index I(CX) is updated from the next MPS index (NMPS) column in Table E.1. If, however, the LPS sub-interval is larger, the conditional exchange occurred and an LPS occurred. The probability update switches the MPS sense if the SWITCH column has a "1" and updates the index I(CX) from the next LPS index (NLPS) column in Table E.1. Note that the probability estimation in the decoder needs to be identical to the probability estimation in the encoder.

For the LPS path of the decoder the conditional exchange procedure is given the LPS_EXCHANGE procedure shown in Figure E.17. The same logical comparison between the MPS sub-interval A and the LPS sub-interval $Q_e(I(CX))$ determines if a conditional exchange occurred. On both paths the new sub-interval A is set to $Q_e(I(CX))$. On the left path the conditional exchange occurred so the decision and update are for the MPS case. On the right path, the LPS decision and update are followed.

E.3.3 Renormalisation in the decoder (RENORMD)

The RENORMD procedure for the decoder renormalisation is illustrated in Figure E.18. A counter keeps track of the number of compressed bits in the Clow section of the C-register. When CT is zero, a new byte is inserted into Clow in the BYTEIN procedure.

Both the interval register A and the code register C are shifted, one bit at a time, until A is no longer less than $0x8000$.

E.3.4 Compressed data input (BYTEIN)

The BYTEIN procedure called from RENORMD is illustrated in Figure E.19. This procedure reads in one byte of data, compensating for any stuff bits following the $0xFF$ byte in the process. It also detects the marker codes which must occur at the end of a scan or resynchronisation interval. The C-register in this procedure is the concatenation of the Chigh and Clow registers.

B is the byte pointed to by the compressed data buffer pointer BP. If B is not a $0xFF$ byte, BP is incremented and the new value of B is inserted into the high order 8 bits of Clow.

If B is a $0xFF$ byte, then B1 (the byte pointed to by BP+1) is tested. If B1 exceeds $0x8F$, then B1 must be one of the marker codes. The marker code is interpreted as required, and the buffer pointer remains pointed to the $0xFF$ prefix of the marker code which terminates the arithmetically compressed data. 1-bits are then fed to the decoder until the decoding is complete. This is shown by adding $0xFF00$ to the C-register and setting the bit counter CT to 8.




Figure E.15 — Decoding an MPS or an LPS.




Figure E.16 — Decoder MPS path conditional exchange procedure.




Figure E.17 — Decoder LPS path conditional exchange procedure.




Figure E.18 — Decoder renormalisation procedure.




Figure E.19 — BYTEIN procedure for decoder

If B1 is not a marker code, then BP is incremented to point to the next byte which contains a stuffed bit. The B is added to the C-register with an alignment such that the stuff bit (which contains any carry) is added to the low order bit of Chigh.

E.3.5 Initialisation of the decoder (INITDEC)

The INITDEC procedure is used to start the arithmetic decoder. The basic steps are shown in Figure E.20.

BP, the pointer to the compressed data, is initialised to BPST (pointing to the first compressed byte). The first byte of the compressed data is shifted into the low order byte of Chigh, and a new byte is then read in. The C-register is then shifted by 7 bits and CT is decremented by 7, bringing the C-register into alignment with the starting value of A. The interval register A is set to match the starting value in the encoder.

E.3.6 Resynchronisation of the decoder

Usually, when the end of the arithmetically compressed data is reached, the compressed data buffer pointer BP points to the 0xFF byte of the terminating marker code. If for any reason the compressed data buffer pointer is not at the 0xFF byte of the marker, a resynchronisation procedure needs to scan the compressed data until it finds the terminating marker code prefix. If a search of this type is needed, it is indicative of an error condition. This error recovery procedure is not standardised.

E.3.7 Resetting arithmetic coding statistics

At certain points during the decoding, some or all of the arithmetic coding statistics are reset. This process involves setting I(CX) and MPS(CX) equal to zero for some or all values of CX.

EXAMPLE — At the start of decoding a text region segment, all the arithmetic coding statistics are reset.

E.3.8 Saving arithmetic coding statistics

In some cases, the decoder needs to save or restore some values of I(CX) and MPS(CX). This is done as part of decoding a symbol dictionary segment. In this case, the values that are saved and/or restored are all the values indexed by CX values whose initial label is “GB” or “GR” (i.e., all those CX values used by the generic region decoding procedure or the generic refinement region decoding procedure).




Figure E.20 — Initialisation of the decoder.

Annex F
(informative)
Arithmetic Decoding Procedure (Software Conventions)

This annex provides some alternative flowcharts for a version of the adaptive entropy decoder. This alternative version may be more efficient when implemented in software, as it has fewer operations along the fast path.

The alternative version is obtained by making the following substitutions.

- Replace the flowchart in Figure E.20 with the flowchart in Figure F.1.
- Replace the flowchart in Figure E.15 with the flowchart in Figure F.2.
- Replace the flowchart in Figure E.19 with the flowchart in Figure F.3.




Figure F.1 — Initialisation of the software-conventions decoder.




Figure F.2 — Decoding an MPS or an LPS in the software-conventions decoder.




Figure F.3 — Inserting a new byte into the C register in the software-conventions decoder.

Annex G (informative) Profiles

It is recommended that a JBIG2 decoder either implement the entire specification, or one of the profiles described in Tables G.1 through G.5. Note that profile 0x00000001 (Table G.1) includes all the capabilities of the entire specification, and is the profile assumed when none is explicitly specified.

See 7.4.12 for information on how the profile identification numbers are used.

Profile identification numbers 0x00000000 through 0x00FFFFFF are reserved for future revisions of this Specification. Entities wishing to use an unassigned profile identification number should choose one in the range 0x01000000 through 0xFFFFFFFF that is not likely to conflict with any other entity's choice. It is recommended that the first three bytes of the profile identification number be chosen to match the first three letters of the name of the entity, or be a suitable abbreviation of that name.

Table G.1 — Profile description for profile 0x00000001

Profile identification	0x00000001
Requirements	All JBIG2 capabilities
Generic region coding	No restriction
Refinement region coding	No restriction
Halftone region coding	No restriction
Numerical data	No restriction
Resources required	Desktop computer
Application examples	

Table G.2 — Profile description for profile 0x00000002

Profile identification	0x00000002
Requirements	Maximum compression
Generic region coding	Arithmetic only; any template used
Refinement region coding	No restriction
Halftone region coding	No restriction
Numerical data	Arithmetic only
Resources required	Desktop computer
Application examples	Archiving; High-end fax; Wireless WWW

Table G.3 — Profile description for profile 0x00000003

Profile identification	0x00000003
Requirements	Medium complexity and medium compression
Generic region coding	Arithmetic only; only 10-pixel and 13-pixel templates
Refinement region coding	10-pixel template only
Halftone region coding	No skip mask used
Numerical data	Arithmetic only
Resources required	Laptop computer
Application examples	WWW

Table G.4 — Profile description for profile 0x00000004

Profile identification	0x00000004
Requirements	Low complexity with progressive lossless capability
Generic region coding	MMR only
Refinement region coding	10-pixel template only
Halftone region coding	No skip mask used
Numerical data	Huffman only
Resources required	Laptop computer
Application examples	WWW

Table G.5 — Profile description for profile 0x00000005

Profile identification	0x00000005
Requirements	Low complexity
Generic region coding	MMR only
Refinement region coding	Not available
Halftone region coding	No skip mask used
Numerical data	Huffman only
Resources required	Standalone
Application examples	Low-end fax; high-speed printing

Annex H (informative) Datastream Example and Test Sequence

H.1 Datastream example

This subclause gives a small datastream that exercises a large number of the features of JBIG2.

The raw data here is shown in the following format:

```
0023: 01 23 45 67 89 AB CD EF
```

where the first field (before the colon) is the byte offset into the datastream of the data being displayed, and the remainder of the line is a sequence of bytes starting at that offset. All these values are in hexadecimal.

In general, the decoding of the first occurrence of any type of data is explained in detail; further occurrences of the same type of data are not explained in as much detail.

This datastream encodes one symbol dictionary that is not associated with any page and three pages. The first two pages each contain a page information segment, a symbol dictionary segment, a text region segment, a generic region segment, a pattern dictionary segment, a halftone region segment, and an end of page segment. The bitmaps encoded by these two pages are identical, and are shown in Figure H.1. The data encoded by the corresponding segments in the two pages are also identical (e.g., the text region segment for page 1 contains the same data, in the same order, as the text region segment for page 2). However, the segments are encoded differently in the two pages: in page 1, all the segments use some form of Huffman or MMR coding; in page 2, all the segments use some form of arithmetic coding. Thus, implementors can cross-check against their own implementations to ensure that they are decoding correctly.

The third page contains two symbol dictionaries, one of which defines symbols by refinement and aggregation from the other one, and one text region, which uses the symbols from the dictionary including refining one of them.

Throughout this subclause, pixels having the value **1** are shown as black pixels, while pixels having the value **0** are shown as white pixels. This is a typical interpretation of **0** and **1**, as might be made by an application using this Recommendation | International Standard.

The datastream is

```
0000: 97 4A 42 32 0D 0A 1A 0A 01 00 00 00 03 00 00 00
0010: 00 00 01 00 00 00 00 18 00 01 00 00 00 01 00 00
0020: 00 01 E9 CB F4 00 26 AF 04 BF F0 78 2F E0 00 40
0030: 00 00 00 01 30 00 01 00 00 00 13 00 00 00 40 00
0040: 00 00 38 00 00 00 00 00 00 00 00 01 00 00 00 00
0050: 00 02 00 01 01 00 00 00 1C 00 01 00 00 00 02 00
0060: 00 00 02 E5 CD F8 00 79 E0 84 10 81 F0 82 10 86
0070: 10 79 F0 00 80 00 00 00 03 07 42 00 02 01 00 00
0080: 00 31 00 00 00 25 00 00 00 08 00 00 00 04 00 00
0090: 00 01 00 0C 09 00 10 00 00 00 05 01 10 00 00 00
00A0: 00 00 00 00 00 00 00 00 00 00 00 00 0C 40 07 08
00B0: 70 41 D0 00 00 00 04 27 00 01 00 00 00 2C 00 00
00C0: 00 36 00 00 00 2C 00 00 00 04 00 00 00 0B 00 01
00D0: 26 A0 71 CE A7 FF FF FF FF FF FF FF FF FF FF
00E0: FF FF FF FF FF FF FF F8 F0 00 00 00 05 10 01
00F0: 01 00 00 00 2D 01 04 04 00 00 00 0F 20 D1 84 61
0100: 18 45 F2 F9 7C 8F 11 C3 9E 45 F2 F9 7D 42 85 0A
0110: AA 84 62 2F EE EC 44 62 22 35 2A 0A 83 B9 DC EE
0120: 77 80 00 00 00 06 17 20 05 01 00 00 00 57 00 00
0130: 00 20 00 00 00 24 00 00 00 10 00 00 00 0F 00 01
0140: 00 00 00 08 00 00 00 09 00 00 00 00 00 00 00 00
0150: 04 00 00 00 AA AA AA AA 80 08 00 80 36 D5 55 6B
0160: 5A D4 00 40 04 2E E9 52 D2 D2 D2 8A A5 4A 00 20
0170: 02 23 E0 95 24 B4 92 8A 4A 92 54 92 D2 4A 29 2A
0180: 49 40 04 00 40 00 00 00 07 31 00 01 00 00 00 00
```

```

0190: 00 00 00 08 30 00 02 00 00 00 13 00 00 00 40 00
01A0: 00 00 38 00 00 00 00 00 00 00 01 00 00 00 00
01B0: 00 09 00 01 02 00 00 00 1B 08 00 02 FF 00 00 00
01C0: 02 00 00 00 02 4F E7 8C 20 0E 1D C7 CF 01 11 C4
01D0: B2 6F FF AC 00 00 00 0A 07 40 00 09 02 00 00
01E0: 1F 00 00 00 25 00 00 00 08 00 00 00 04 00 00
01F0: 01 00 0C 08 00 00 00 05 8D 6E 5A 12 40 85 FF AC
0200: 00 00 00 0B 27 00 02 00 00 00 23 00 00 00 36 00
0210: 00 00 2C 00 00 00 04 00 00 00 0B 00 08 03 FF FD
0220: FF 02 FE FE FE 04 EE ED 87 FB CB 2B FF AC 00 00
0230: 00 0C 10 01 02 00 00 00 1C 06 04 04 00 00 00 0F
0240: 90 71 6B 6D 99 A7 AA 49 7D F2 E5 48 1F DC 68 BC
0250: 6E 40 BB FF AC 00 00 00 0D 17 20 0C 02 00 00 00
0260: 3E 00 00 00 20 00 00 00 24 00 00 00 10 00 00 00
0270: 0F 00 02 00 00 00 08 00 00 00 09 00 00 00 00 00
0280: 00 00 00 04 00 00 00 87 CB 82 1E 66 A4 14 EB 3C
0290: 4A 15 FA CC D6 F3 B1 6F 4C ED BF A7 BF FF AC 00
02A0: 00 00 0E 31 00 02 00 00 00 00 00 00 00 0F 30 00
02B0: 03 00 00 00 13 00 00 00 25 00 00 00 08 00 00 00
02C0: 00 00 00 00 00 01 00 00 00 00 00 10 00 01 00 00
02D0: 00 00 16 08 00 02 FF 00 00 00 01 00 00 00 01 4F
02E0: E7 8D 68 1B 14 2F 3F FF AC 00 00 00 11 00 21 10
02F0: 03 00 00 00 20 08 02 02 FF FF FF FF FF 00 00 00
0300: 03 00 00 00 02 4F E9 D7 D5 90 C3 B5 26 A7 FB 6D
0310: 14 98 3F FF AC 00 00 00 12 07 20 11 03 00 00 00
0320: 25 00 00 00 25 00 00 00 08 00 00 00 00 00 00 00
0330: 00 00 8C 12 00 00 00 04 A9 5C 8B F4 C3 7D 96 6A
0340: 28 E5 76 8F FF AC 00 00 00 13 31 00 03 00 00 00
0350: 00 00 00 00 14 33 00 00 00 00 00 00 00

```

The datastream is decoded as follows.

1. The file header

```
0000: 97 4A 42 32 0D 0A 1A 0A 01 00 00 00 02
```

(a) The eight-byte ID string

```
0000: 97 4A 42 32 0D 0A 1A 0A
```

(b) The one-byte file header flags field

```
0008: 01
```

This field indicates that the file uses the sequential organisation, and that the number of pages is known.

(c) The four-byte number of pages field

```
0009: 00 00 00 03
```

This field indicates that the file has three pages.

2. The first segment header

```
000D: 00 00 00 00 00 01 00 00 00 00 18
```

(a) The four-byte segment number field

```
000D: 00 00 00 00
```

This field indicates that the segment is segment number 0.

(b) The one-byte segment header flags field

```
0011: 00
```

This field indicates that the segment has type “Symbol dictionary” (type 0), has a short page association field, and does not have the deferred non-retain bit set.




Figure H.1 — Test datastream page bitmap

- (c) The one-byte referred-to segment count and retention flags field
0012: 01
This field indicates that the segment refers to no other segment, and that it should be retained.
- (d) The one-byte (short-form) segment page association field
0013: 00
This field indicates that this segment is not associated with any page.
- (e) The four-byte segment data length field
0014: 00 00 00 18
This field indicates that the segment's data part is 24 bytes long.

3. The first segment data part

0018: 00 01 00 00 00 01 00 00 00 01 E9 CB F4 00 26 AF
0028: 04 BF F0 78 2F E0 00 40

- (a) The two-byte symbol dictionary flags field
0018: 00 01
This field indicates that the segment is encoded using the Huffman coding variant, does not use refinement/aggregate coding, uses Table B.4 for **SDHUFFDH**, and uses Table B.2 for **SDHUFFDW**.
- (b) The four-byte **SDNUMEXSYMS** field.
001A: 00 00 00 01
This field indicates that **SDNUMEXSYMS** is 1: one symbol is exported by this symbol dictionary.
- (c) The four-byte **SDNUMNEWSYMS** field.
001E: 00 00 00 01
This field indicates that **SDNUMNEWSYMS** is 1: one symbol is defined by this symbol dictionary.
- (d) The encoded symbol dictionary data
0022: E9 CB F4 00 26 AF 04 BF F0 78 2F E0 00 40
This is decoded as follows.
 - i. Using Table B.4, decode a height class delta height value. This consumes the bits **1110 100**, indicating a height class delta height of 8. The first height class thus has a height of 8 pixels.
 - ii. Using Table B.2, decode a delta width value. This consumes the bits **1110 010**, indicating a delta width of 5. The first symbol thus has a width of 5 pixels.
 - iii. Using Table B.2, decode a delta width value. This consumes the bits **111111**, indicating a delta width of OOB. This ends the height class; the height class contains one symbol whose width is 5 pixels and whose height is 8 pixels.
 - iv. Using Table B.1, decode the size in bytes of the height class collective bitmap. This consumes the bits **01000**, indicating a size of eight bytes.
 - v. Skip the remaining bits in the last byte read. This consumes the bits **0000000**.
 - vi. Decode the next eight bytes
0026: 26 AF 04 BF F0 78 2F E0
using MMR. This produces the height class collective bitmap, which is also the bitmap for the single symbol in the height class, shown in Figure H.2.




Figure H.2 — The first symbol in the first symbol dictionary

- vii. Since **SDNUMNEWSYMS** is 1, the last symbol has now been decoded.
- viii. Using Table B.1, decode an export run length. This consumes the bits **00000**, indicating that the first 0 symbols are not exported.
- ix. Using Table B.1, decode an export run length. This consumes the bits **00001**, indicating that the next 1 symbols are exported. Thus, this symbol dictionary defines one symbol, which is exported.
- x. Skip the remaining bits in the last byte. This consumes the bits **000000**.

4. The second segment header

0030: 00 00 00 01 30 00 01 00 00 00 13

This segment has a segment number of 1, a type of “Page information” (type 48), a short page association field, and does not have the deferred non-retain bit set. It refers to no other segments, and is not retained. It is associated with page 1, and has a data length of 19 bytes.

5. The second segment data part

003B: 00 00 00 40 00 00 00 38 00 00 00 00 00 00 00 00

004B: 01 00 00

- (a) The page bitmap width field

003B: 00 00 00 40

This indicates that the page is 64 pixels wide.

- (b) The page bitmap height field

003F: 00 00 00 38

This indicates that the page is 56 pixels high.

- (c) The page X resolution field

0043: 00 00 00 00

This indicates that the page’s X resolution is unknown.

- (d) The page Y resolution field

0047: 00 00 00 00

This indicates that the page’s Y resolution is unknown.

- (e) The page segment flags field

004B: 01

This indicates that the page is eventually lossless, the page does not contain any refinements, the page default pixel value is 0, the page default combination operator is OR, the page does not require any auxiliary buffers, and the page default combination operator is used by every region segment on the page.

- (f) The page striping information field

004C: 00 00

This indicates that the page is not striped.

6. The third segment header

004E: 00 00 00 02 00 01 01 00 00 00 1C

This segment has a segment number of 2, a type of “Symbol dictionary” (type 0), a short page association field, and does not have the deferred non-retain bit set. It refers to no other segments, and is retained. It is associated with page 1, and has a data length of 28 bytes.

7. The third segment data part

0059: 00 01 00 00 00 02 00 00 00 02 E5 CD F8 00 79 E0

0069: 84 10 81 F0 82 10 86 10 79 F0 00 80

- (a) The two-byte symbol dictionary flags field

0059: 00 01

This field indicates that the segment is encoded using the Huffman coding variant, does not use refinement/aggregate coding, uses Table B.4 for **SDHUFFDH**, and uses Table B.2 for **SDHUFFDW**.

- (b) The four-byte **SDNUMEXSYMS** field.

005B: 00 00 00 02

This field indicates that **SDNUMEXSYMS** is 2: two symbols are exported by this symbol dictionary.

- (c) The four-byte **SDNUMNEWSYMS** field.

005F: 00 00 00 02

This field indicates that **SDNUMNEWSYMS** is 2: two symbols are defined by this symbol dictionary.

- (d) The encoded symbol dictionary data

0063: E5 CD F8 00 79 E0 84 10 81 F0 82 10 86 10 79 F0

0073: 00 80

This is decoded as follows.

- i. Using Table B.4, decode a height class delta height value. This consumes the bits **1110 010**, indicating a height class delta height of 6. The first height class thus has a height of 6 pixels.
- ii. Using Table B.2, decode a delta width value. This consumes the bits **1110 011**, indicating a delta width of 6. The first symbol thus has a width of 6 pixels.
- iii. Using Table B.2, decode a delta width value. This consumes the bits **0**, indicating a delta width of 0. The second symbol thus has a width of 6 pixels.
- iv. Using Table B.2, decode a delta width value. This consumes the bits **111111**, indicating a delta width of OOB. This ends the height class; the height class contains two symbols, which both are 6 pixels wide and 6 pixels high.
- v. Using Table B.1, decode the size in bytes of the height class collective bitmap. This consumes the bits **00000**, indicating a size of zero bytes. This indicates that the height class collective bitmap is stored uncompressed. Since the total width of the symbols in the height class is 12, each row of the height class is padded to be 16 bits (2 bytes) wide.
- vi. Skip the remaining bits in the last byte read. This consumes the bits **000000**.
- vii. Read the next 12 bytes (6 rows of 2 bytes each), and use the leftmost 12 bits of each row as the height class collective bitmap. These 12 bytes are

0067: 79 E0 84 10 81 F0 82 10 86 10 79 F0

or, in binary

```

01111001 11100000
10000100 00010000
10000001 11110000
10000010 00010000
10000110 00010000
01111001 11110000

```

The height class collective bitmap is therefore as shown in Figure H.3, and the two symbols are as shown in Figure H.4(a) and (b).






Figure H.3 — The height class collective bitmap in the second symbol dictionary

- viii. Since **SDNUMNEWSYMS** is 2, the last symbol has now been decoded.
- ix. Using Table B.1, decode an export run length. This consumes the bits **00000**, indicating that the first 0 symbols are not exported.



(a)



(b)

Figure H.4 — The symbols in the second symbol dictionary

- x. Using Table B.1, decode an export run length. This consumes the bits **00010**, indicating that the next 2 symbols are exported. Thus, this symbol dictionary defines two symbols, which are both exported.
 - xi. Skip the remaining bits in the last byte. This consumes the bits **000000**.
8. The fourth segment header

```
0075: 00 00 00 03 07 42 00 02 01 00 00 00 31
```

This segment has a segment number of 3, a type of “Immediate lossless text region” (type 7), a short page association field, and does not have the deferred non-retain bit set. It refers to two other segments, segments number 0 and 2; segment 0 should be retained, but segment 2 and this segment should not be retained. It is associated with page 1, and has a data length of 49 bytes.

9. The fourth segment data part

```
0082: 00 00 00 25 00 00 00 08 00 00 00 04 00 00 00 01
0092: 00 0C 09 00 10 00 00 00 05 01 10 00 00 00 00 00
00A2: 00 00 00 00 00 00 00 00 00 00 0C 40 07 08 70 41
00B2: D0
```

- (a) The region segment bitmap width field

```
0082: 00 00 00 25
```

This field indicates that the region bitmap is 37 pixels wide.

- (b) The region segment bitmap height field

```
0086: 00 00 00 08
```

This field indicates that the region bitmap is 8 pixels high.

- (c) The region segment bitmap X location field

```
008A: 00 00 00 04
```

This field indicates that the region bitmap’s left edge is 4 pixels right of the page’s left edge.

- (d) The region segment bitmap Y location field

```
008E: 00 00 00 01
```

This field indicates that the region bitmap’s top edge is 1 pixel down from the page’s top edge.

- (e) The region segment flags field

```
0092: 00
```

This field indicates that the region should be drawn into the page using the combination operator OR.

- (f) The two-byte text region segment flags field

```
0093: 0C 09
```

This field indicates that the segment is encoded using the Huffman coding variant, does not contain any refinements, has a **SBSTRIPS** value of 4, has a reference corner of **BOTTOMLEFT**, is not transposed, combines its symbols using OR, has a default pixel value of **0**, and has a **SBDSOFFSET** value of 3.

- (g) The two-byte text region segment Huffman flags field

```
0095: 00 10
```

This field indicates that the segment uses Table B.6 for **SBHUFFFS**, Table B.8 for **SBHUFFDS**, and Table B.12 for **SBHUFFDT**.

(h) The four-byte **SBNUMINSTANCES** field

0097: 00 00 00 05

This field indicates that **SBNUMINSTANCES** is 5: five symbol instances are encoded in this text region.

(i) The text region segment symbol ID Huffman decoding table.

009B: 01 10 00 00 00 00 00 00 00 00 00 00 00 00 00 00

00AB: 00 0C

The two symbol dictionaries referred to by this segment have a total of 3 symbols in them. Decoding the **RUNCODE** Huffman table, consuming all of the data but the last four bits, gives the following assignment of code lengths to the **RUNCODE**s:

RUNCODE1	1	RUNCODE2	1
-----------------	----------	-----------------	----------

and therefore the following Huffman table for the **RUNCODE**s:

RUNCODE1	0	RUNCODE2	1
-----------------	----------	-----------------	----------

Decoding using this table produces the sequence **RUNCODE2**, **RUNCODE2**, **RUNCODE1** (consuming the bits **110**). Thus, the first symbol (the “p” from the first symbol dictionary) has a Huffman code length of 2; the second symbol (the “c” from the second symbol dictionary) has a Huffman code length of 2, and the third symbol (the “a” from the second symbol dictionary) has a code length of 1. Applying the Huffman code assignment algorithm gives the table

p	10
c	11
a	0

At this point, there is one bit (**0**) remaining in the last of data; this is now skipped.

(j) The encoded text region data

00AD: 40 07 08 70 41 D0

This is decoded as follows.

- i. Using Table B.12, decode a delta T value. This consumes the bits **0**, indicating a delta T value of 4 (the table’s decoded value of 1, multiplied by **SBSTRIPS**). The initial **STRIPT** value is -4.
- ii. Using Table B.12, decode a delta T value. This consumes the bits **10**, indicating a delta T value of 8 (2 times **SBSTRIPS**). **STRIPT** is therefore now 4.
- iii. Using Table B.6, decode a first S value. This consumes the bits **00 0000000**, indicating a first S value of 0.
- iv. Reading two bits (since **SBSTRIPS**) consumes the bits **01**. The first symbol instance T coordinate is therefore 5 (**STRIPT** plus the decoded value of 1).
- v. Using the symbol ID Huffman table, decode a symbol ID value. This consumes the bits **11**, indicating the symbol “c”. Thus, the symbol “c” should be drawn with its lower left corner at (0, 5).
- vi. At this point, **CURS** is 8 (0 plus **SBDSOFFSET** plus the previous symbol’s width of 6 minus 1).
- vii. Using Table B.8, decode a delta S value. This consumes the bits **00 0**, indicating a delta S value of 0.
- viii. Reading two bits consumes the bits **01**. The second symbol instance T coordinate is therefore 5.
- ix. Using the symbol ID Huffman table, decode a symbol ID value. This consumes the bits **0**, indicating the symbol “a”. Thus, the symbol “a” should be drawn with its lower left corner at (8, 5).
- x. At this point, **CURS** is 16 (8 plus **SBDSOFFSET** plus the previous symbol’s width of 6 minus 1).
- xi. Using Table B.8, decode a delta S value. This consumes the bits **00 0**, indicating a delta S value of 0.




Figure H.5 — The text region bitmap

- xii. Reading two bits consumes the bits **11**. The third symbol instance T coordinate is therefore 7.
 - xiii. Using the symbol ID Huffman table, decode a symbol ID value. This consumes the bits **10**, indicating the symbol “p”. Thus, the symbol “p” should be drawn with its lower left corner at (16, 7).
 - xiv. At this point, CURS is 23 (16 plus **SBDSOFFSET** plus the previous symbol’s width of 5 minus 1).
 - xv. Using Table B.8, decode a delta S value. This consumes the bits **00 0**, indicating a delta S value of 0.
 - xvi. Reading two bits consumes the bits **01**. The fourth symbol instance T coordinate is therefore 5.
 - xvii. Using the symbol ID Huffman table, decode a symbol ID value. This consumes the bits **0**, indicating the symbol “a”. Thus, the symbol “a” should be drawn with its lower left corner at (8, 5).
 - xviii. At this point, CURS is 31 (23 plus **SBDSOFFSET** plus the previous symbol’s width of 6 minus 1).
 - xix. Using Table B.8, decode a delta S value. This consumes the bits **00 0**, indicating a delta S value of 0.
 - xx. Reading two bits consumes the bits **01**. The fifth symbol instance T coordinate is therefore 5.
 - xxi. Using the symbol ID Huffman table, decode a symbol ID value. This consumes the bits **11**, indicating the symbol “c”. Thus, the symbol “c” should be drawn with its lower left corner at (31, 5).
 - xxii. Using Table B.8, decode a delta S value. This consumes the bits **01**, indicating a delta S value of OOB, indicating the end of this strip. Since **SBNUMINSTANCES** is 5, and five symbol instances have been decoded, there are no more strips.
 - xxiii. Skip the remaining bits in the last byte read. This consumes the bits **0000**.
- (k) Decoding the data produced the following list of symbol instances and locations (the locations are where the symbol’s lower left corner should be placed):

Symbol	Location
c	(0, 5)
a	(8, 5)
p	(16, 7)
a	(23, 5)
c	(31, 5)

Drawing these symbol instances produces the 37-by-8 pixel region bitmap shown in Figure H.5.

10. The fifth segment header

00B3: 00 00 00 04 27 00 01 00 00 00 2C

This segment has a segment number of 4, a type of “Immediate lossless generic region” (type 39), a short page association field, and does not have the deferred non-retain bit set. It refers to no other segments, and is not retained. It is associated with page 1, and has a data length of 44 bytes.

11. The fifth segment data part

00BE: 00 00 00 36 00 00 00 2C 00 00 00 04 00 00 00 0B




Figure H.6 — The generic region bitmap

```
00CE: 00 01 26 A0 71 CE A7 FF FF FF FF FF FF FF FF FF
00DE: FF FF FF FF FF FF FF FF FF FF F8 F0
```

(a) The region segment information field

```
00BE: 00 00 00 36 00 00 00 2C 00 00 00 04 00 00 00 0B
00CE: 00
```

This indicates that the region bitmap encoded by this segment is 54 pixels wide, 44 pixels high, and its top left corner is 4 pixels right of the page’s left edge and 11 pixels down from the page’s top edge. It should be drawn into the page using OR.

(b) The region data

```
00CF: 01 26 A0 71 CE A7 FF FF FF FF FF FF FF FF FF
00DF: FF FF FF FF FF FF FF FF FF F8 F0
```

The first byte (01) is the generic region segment flags byte, and indicates that the region is encoded using MMR. The remaining bytes are the MMR-encoded data for the region bitmap. These bytes MMR-decompress to the 54-by-44 region bitmap shown in Figure H.6.

12. The sixth segment header

```
00EA: 00 00 00 05 10 01 01 00 00 00 2D
```

This segment has a segment number of 5, a type of “Pattern dictionary” (type 16), a short page association field, and does not have the deferred non-retain bit set. It refers to no other segments, and is retained. It is associated with page 1, and has a data length of 45 bytes.

13. The sixth segment data part




Figure H.7 — The pattern dictionary collective bitmap




Figure H.8 — The patterns defined in the pattern dictionary

```
00F5: 01 04 04 00 00 00 0F 20 D1 84 61 18 45 F2 F9 7C
0105: 8F 11 C3 9E 45 F2 F9 7D 42 85 0A AA 84 62 2F EE
0115: EC 44 62 22 35 2A 0A 83 B9 DC EE 77 80
```

- (a) The one-byte pattern dictionary flags field

```
00F5: 01
```

This field indicates that the segment is encoded using the MMR coding variant.

- (b) The one-byte **HDPW** field

```
00F6: 04
```

This field indicates that **HDPW**, the width of the patterns defined in this dictionary, is 4.

- (c) The one-byte **HDPH** field

```
00F7: 04
```

This field indicates that **HDPH**, the height of the patterns defined in this dictionary, is 4.

- (d) The four-byte **GRAYMAX** field

```
00F8: 00 00 00 0F
```

This field indicates that **GRAYMAX** is 15, and thus there are 16 patterns in this pattern dictionary (numbered 0 through 15).

- (e) The remaining 38 bytes in the segment

```
00FC: 20 D1 84 61 18 45 F2 F9 7C 8F 11 C3 9E 45 F2 F9
010C: 7D 42 85 0A AA 84 62 2F EE EC 44 62 22 35 2A 0A
011C: 83 B9 DC EE 77 80
```

These bytes MMR-decompress to the pattern dictionary's collective bitmap. The width of the bitmap is $(\mathbf{GRAYMAX} + 1) \times \mathbf{HDPW}$, and the height is **HDPH** pixels. The 64-by-4 bitmap that is the result of this MMR decompression is shown in Figure H.7.

The 16 individual patterns are obtained from the collective bitmap by breaking it into 4-pixel-wide pieces. They are shown in Figure H.8, where pattern number 0 is the top left pattern, pattern number 1 is to its right, and so on.

14. The seventh segment header

```
0122: 00 00 00 06 17 20 05 01 00 00 00 57
```

This segment has a segment number of 6, a type of “Immediate lossless halftone region” (type 23), a short page association field, and does not have the deferred non-retain bit set. It refers to one other segment, segment number 5; neither segment 5 nor this segment should be retained. It is associated with page 1, and has a data length of 87 bytes.

15. The seventh segment data part

```
012E: 00 00 00 20 00 00 00 24 00 00 00 10 00 00 00 0F
013E: 00 01 00 00 00 08 00 00 00 09 00 00 00 00 00 00
014E: 00 00 04 00 00 00 AA AA AA AA 80 08 00 80 36 D5
015E: 55 6B 5A D4 00 40 04 2E E9 52 D2 D2 D2 8A A5 4A
016E: 00 20 02 23 E0 95 24 B4 92 8A 4A 92 54 92 D2 4A
017E: 29 2A 49 40 04 00 40
```

(a) The region segment information field

```
012E: 00 00 00 20 00 00 00 24 00 00 00 10 00 00 00 0F
013E: 00
```

This indicates that the region bitmap encoded by this segment is 32 pixels wide, 36 pixels high, and its top left corner is 16 pixels right of the page’s left edge and 15 pixels down from the page’s top edge. It should be drawn into the page using OR.

(b) The halftone region segment flags field

```
013F: 01
```

This field indicates that the halftone region is encoded using the MMR coding variant. The patterns should be combined using OR. The default pixel value is 0.

(c) The **HGW** field

```
0140: 00 00 00 08
```

This field indicates that the array of gray-scale values is 8 wide.

(d) The **HGH** field

```
0144: 00 00 00 09
```

This field indicates that the array of gray-scale values is 9 high.

(e) The **HGX** field

```
0148: 00 00 00 00
```

This field indicates that the horizontal offset of the halftone grid is 0 pixels.

(f) The **HGY** field

```
014C: 00 00 00 00
```

This field indicates that the vertical offset of the halftone grid is 0 pixels.

(g) The **HRX** field

```
0150: 04 00
```

This field indicates that the **HRX** is 1024, and thus the horizontal coordinate of the grid vector is 1024/256 pixels, or 4 pixels.

(h) The **HRY** field

```
0152: 00 00
```

This field indicates that the vertical coordinate of the grid vector is 0 pixels.

(i) The first bitplane

```
0154: AA AA AA AA 80 08 00 80
```

Decompressing this with MMR yields the bitmap shown in Figure H.9(a). Note that the last 7 bits in the last byte are skipped over after all the MMR-encoded data has been decoded (i.e., decoding the bitplane is forced to consume an integral number of bytes).




Figure H.9 — The raw bitplanes for the halftone region




Figure H.10 — The bitplanes for the halftone region

(j) The second bitplane

015C: 36 D5 55 6B 5A D4 00 40 04

Decompressing this with MMR yields the bitmap shown in Figure H.9(b).

(k) The third bitplane

0165: 2E E9 52 D2 D2 D2 8A A5 4A 00 20 02

Decompressing this with MMR yields the bitmap shown in Figure H.9(c).

(l) The fourth bitplane

0171: 23 E0 95 24 B4 92 8A 4A 92 54 92 D2 4A 29 2A 49

0181: 40 04 00 40

Decompressing this with MMR yields the bitmap shown in Figure H.9(d).

(m) These bitplanes are then Gray-decoded as described in C.5, by XORing the first into the second, then the resulting bitplane into the third, and so on. The resulting bitplanes are shown in Figure H.10.

(n) Stacking up these bitplanes, with the first being the most significant, results in the array of values

0	1	2	3	4	5	6	7
1	2	3	4	5	6	7	8
2	3	4	5	6	7	8	9
3	4	5	6	7	8	9	10
4	5	6	7	8	9	10	11
5	6	7	8	9	10	11	12
6	7	8	9	10	11	12	13
7	8	9	10	11	12	13	14
8	9	10	11	12	13	14	15

(o) The halftone grid vector and offset produces the following array of locations. Combining this with the array of values results in a list of drawing operations, indicating that the pattern whose index in the pattern dictionary in segment number 5 is that value should be drawn with its upper left pixel at the given location.




Figure H.11 — The halftone region bitmap

(0, 0)	(4, 0)	(8, 0)	(12, 0)	(16, 0)	(20, 0)	(24, 0)	(28, 0)
(0, 4)	(4, 4)	(8, 4)	(12, 4)	(16, 4)	(20, 4)	(24, 4)	(28, 4)
(0, 8)	(4, 8)	(8, 8)	(12, 8)	(16, 8)	(20, 8)	(24, 8)	(28, 8)
(0, 12)	(4, 12)	(8, 12)	(12, 12)	(16, 12)	(20, 12)	(24, 12)	(28, 12)
(0, 16)	(4, 16)	(8, 16)	(12, 16)	(16, 16)	(20, 16)	(24, 16)	(28, 16)
(0, 20)	(4, 20)	(8, 20)	(12, 20)	(16, 20)	(20, 20)	(24, 20)	(28, 20)
(0, 24)	(4, 24)	(8, 24)	(12, 24)	(16, 24)	(20, 24)	(24, 24)	(28, 24)
(0, 28)	(4, 28)	(8, 28)	(12, 28)	(16, 28)	(20, 28)	(24, 28)	(28, 28)
(0, 32)	(4, 32)	(8, 32)	(12, 32)	(16, 32)	(20, 32)	(24, 32)	(28, 32)

(p) Performing those drawing operations produces the 32-by-36 region bitmap shown in Figure H.11

16. The eighth segment header

```
0185: 00 00 00 07 31 00 01 00 00 00 00
```

This segment has a segment number of 7, a type of “End of page” (type 49), a short page association field, and does not have the deferred non-retain bit set. It refers to no other segments, and is not retained. It is associated with page 1, and has a data length of zero bytes.

17. The region segment bitmaps are combined as follows, taking into account the page default pixel value and each region segment’s combination operator. First, the page bitmap (64 pixels wide and 56 pixels high) is filled with 0, the page default pixel value. Next, the bitmap shown in Figure H.5 is drawn using OR into the page bitmap with its top left pixel at location (4, 1). Next, the bitmap shown in Figure H.6 is drawn using OR into the page bitmap with its top left pixel at location (4, 11). Finally, the bitmap shown in Figure H.11 is drawn using OR into the page bitmap with its top left pixel at location (16, 15). After all this has been done, the resulting bitmap is the one shown in Figure H.1.

18. The ninth segment header

```
0190: 00 00 00 08 30 00 02 00 00 00 13
```

This segment has a segment number of 8, a type of “Page information” (type 48), a short page association field, and does not have the deferred non-retain bit set. It refers to no other segments, and is not retained. It is associated with page 2, and has a data length of 19 bytes.

19. The ninth segment data part

```
019B: 00 00 00 40 00 00 00 38 00 00 00 00 00 00 00 00
01AB: 01 00 00
```

This contains the same information as does segment number 1.

20. The tenth segment header

```
01AE: 00 00 00 09 00 01 02 00 00 00 1B
```

This segment has a segment number of 9, a type of “Symbol dictionary” (type 0), a short page association field, and does not have the deferred non-retain bit set. It refers to no other segments, and is retained. It is associated with page 2, and has a data length of 27 bytes.

21. The tenth segment data part

```
01B9: 08 00 02 FF 00 00 00 02 00 00 00 02 4F E7 8C 20
01C9: 0E 1D C7 CF 01 11 C4 B2 6F FF AC
```

(a) The two-byte symbol dictionary flags field

```
01B9: 08 00
```

This field indicates that the segment is encoded using the arithmetic coding variant and does not use refinement/aggregate coding. **SDTEMPLATE** has the value 2. The “bitmap coding context used” and “bitmap coding context retained” bits are both 0.

(b) The symbol dictionary AT flags field

```
01BB: 02 FF
```

This field indicates that **SDATX**₁ is 2 and **SDATY**₁ is -1; thus, AT pixel A_1 is at location (2, -1), which is the nominal value for template 2.

(c) The four-byte **SDNUMEXSYMS** field.

```
01BD: 00 00 00 02
```

This field indicates that **SDNUMEXSYMS** is 2: two symbols are exported by this symbol dictionary.

(d) The four-byte **SDNUMNEWSYMS** field.

```
01C1: 00 00 00 02
```

This field indicates that **SDNUMNEWSYMS** is 2: two symbols are defined by this symbol dictionary.

(e) The encoded symbol dictionary data

```
01C5: 4F E7 8C 20 0E 1D C7 CF 01 11 C4 B2 6F FF AC
```

Decoding this gives the same two symbols shown in Figure H.4(a) and (b).

22. The eleventh segment header

```
01D4: 00 00 00 0A 07 40 00 09 02 00 00 00 1F
```

This segment has a segment number of 10, a type of “Immediate lossless text region” (type 7), a short page association field, and does not have the deferred non-retain bit set. It refers to two other segments, segments number 0 and 9; segment 0, segment 9, and this segment should not be retained. It is associated with page 2, and has a data length of 31 bytes.

23. The eleventh segment data part

```
01E1: 00 00 00 25 00 00 00 08 00 00 00 04 00 00 00 01
01F1: 00 0C 08 00 00 00 05 8D 6E 5A 12 40 85 FF AC
```

- (a) The region segment information field

01E1: 00 00 00 25 00 00 00 08 00 00 00 04 00 00 00 01

01F1: 00

This indicates that the region bitmap encoded by this segment is 37 pixels wide, 8 pixels high, and its top left corner is 4 pixels right of the page's left edge and 1 pixel down from the page's top edge. It should be drawn into the page using OR.

- (b) The two-byte text region segment flags field

01F2: 0C 08

This field indicates that the segment is encoded using the arithmetic coding variant, does not contain any refinements, has a **SBSTRIPS** value of 4, has a reference corner of **BOTTOMLEFT**, is not transposed, combines its symbols using OR, has a default pixel value of 0, and has a **SBDSOFFSET** value of 3.

- (c) The four-byte **SBNUMINSTANCES** field

01F4: 00 00 00 05

This field indicates that **SBNUMINSTANCES** is 5: five symbol instances are encoded in this text region.

- (d) The encoded text region data

01F8: 8D 6E 5A 12 40 85 FF AC

Decoding this follows the exact same sequence that was seen in decoding segment number 3 (page 1's text region segment), and results in the region bitmap shown in Figure H.5.

24. The twelfth segment header

0200: 00 00 00 0B 27 00 02 00 00 00 23

This segment has a segment number of 11, a type of "Immediate lossless generic region" (type 39), a short page association field, and does not have the deferred non-retain bit set. It refers to no other segments, and is not retained. It is associated with page 2, and has a data length of 35 bytes.

25. The twelfth segment data part

020B: 00 00 00 36 00 00 00 2C 00 00 00 04 00 00 00 0B

021B: 00 08 03 FF FD FF 02 FE FE FE 04 EE ED 87 FB CB

022B: 2B FF AC

- (a) The region segment information field

020B: 00 00 00 36 00 00 00 2C 00 00 00 04 00 00 00 0B

021B: 00

This indicates that the region bitmap encoded by this segment is 54 pixels wide, 44 pixels high, and its top left corner is 4 pixels right of the page's left edge and 11 pixels down from the page's top edge. It should be drawn into the page using OR.

- (b) The one-byte generic region flags field

021C: 08

This indicates that the region is encoded using arithmetic coding, that **GBTEMPLATE** is 0, and **TPGDON** is 1.

- (c) The generic region segment AT flags field

021D: 03 FF FD FF 02 FE FE FE

This field is eight bytes long because **GBTEMPLATE** is 0, and there are thus four AT pixels whose positions must be determined. The AT pixels are located with A_1 at (3, -1); A_2 at (-3, -1); A_3 at (2, -2); and A_4 at (-2, -2). These are the nominal positions of those pixels for this template.

(d) The region data

0225: 04 EE ED 87 FB CB 2B FF AC

Decoding this using the decoded values of **GBTEMPLATE**, **TPGDON**, and the AT pixel locations produces the 54-by-44 region bitmap shown in Figure H.6.

26. The thirteenth segment header

022E: 00 00 00 0C 10 01 02 00 00 00 1C

This segment has a segment number of 12, a type of “Pattern dictionary” (type 16), a short page association field, and does not have the deferred non-retain bit set. It refers to no other segments, and is retained. It is associated with page 2, and has a data length of 28 bytes.

27. The thirteenth segment data part

0239: 06 04 04 00 00 00 0F 90 71 6B 6D 99 A7 AA 49 7D

0249: F2 E5 48 1F DC 68 BC 6E 40 BB FF AC

(a) The one-byte pattern dictionary flags field

0239: 06

This field indicates that the segment is encoded using the arithmetic coding variant, and that **HDTEMPLATE** is 3.

(b) The one-byte **HDPW** field

023A: 04

This field indicates that **HDPW** is 4.

(c) The one-byte **HDPH** field

023B: 04

This field indicates that **HDPH** is 4.

(d) The four-byte **GRAYMAX** field

023C: 00 00 00 0F

This field indicates that **GRAYMAX** is 15, and thus there are 16 patterns in this pattern dictionary.

(e) The remaining 21 bytes in the segment

0240: 90 71 6B 6D 99 A7 AA 49 7D F2 E5 48 1F DC 68 BC

0250: 6E 40 BB FF AC

These bytes decompress, using the pattern dictionary decoding procedure, to the collective bitmap shown in Figure H.7, and thus the 16 patterns defined by this pattern dictionary are as shown in Figure H.8.

28. The fourteenth segment header

0255: 00 00 00 0D 17 20 0C 02 00 00 00 3E

This segment has a segment number of 13, a type of “Immediate lossless halftone region” (type 23), a short page association field, and does not have the deferred non-retain bit set. It refers to one other segment, segment number 12; neither segment 12 nor this segment should be retained. It is associated with page 2, and has a data length of 62 bytes.

29. The fourteenth segment data part

0261: 00 00 00 20 00 00 00 24 00 00 00 10 00 00 00 0F

0271: 00 02 00 00 00 08 00 00 00 09 00 00 00 00 00 00

0281: 00 00 04 00 00 00 87 CB 82 1E 66 A4 14 EB 3C 4A

0291: 15 FA CC D6 F3 B1 6F 4C ED BF A7 BF FF AC

- (a) The region segment information field

```
0261: 00 00 00 20 00 00 00 24 00 00 00 10 00 00 00 0F
0271: 00
```

This indicates that the region bitmap encoded by this segment is 32 pixels wide, 36 pixels high, and its top left corner is 16 pixels right of the page's left edge and 15 pixels down from the page's top edge. It should be drawn into the page using OR.

- (b) The halftone region segment flags field

```
0272: 02
```

This field indicates that the halftone region is encoded using the arithmetic coding variant, and that **HTEMPLATE** is 1. The patterns should be combined using OR. The default pixel value is **0**.

- (c) The other parameters

```
0273: 00 00 00 08 00 00 00 09 00 00 00 00 00 00 00
0283: 04 00 00 00
```

The following fields indicate that **HGW** is 8, **HGH** is 9, **HGX** is 0, **HGY** is 0, **HRX** is 1024, and **HRY** is 0.

- (d) The four bitplanes

```
0287: 87 CB 82 1E 66 A4 14 EB 3C 4A 15 FA CC D6 F3 B1
0297: 6F 4C ED BF A7 BF FF AC
```

Decoding four 8-by-9 bitplanes from this data results in the four bitplanes shown in Figure H.9. As in segment number 6, Gray-decoding these bitplanes, combining them into an array of values, and drawing the patterns from the pattern dictionary according to that array and the halftone grid parameters results in the region bitmap shown in Figure H.11.

30. The fifteenth segment header

```
029F: 00 00 00 0E 31 00 02 00 00 00 00
```

This segment has a segment number of 14, a type of "End of page" (type 49), a short page association field, and does not have the deferred non-retain bit set. It refers to no other segments, and is not retained. It is associated with page 2, and has a data length of zero bytes.

31. The page bitmap is made by combining the three region bitmaps in the identical way that they were combined in page 1, resulting in the same page bitmap.

32. The sixteenth segment header

```
02AA: 00 00 00 0F 30 00 03 00 00 00 13
```

This segment has a segment number of 15, a type of "Page information" (type 48), a short page association field, and does not have the deferred non-retain bit set. It refers to no other segments, and is not retained. It is associated with page 3, and has a data length of 19 bytes.

33. The sixteenth segment data part

```
02B5: 00 00 00 25 00 00 00 08 00 00 00 00 00 00 00
02C5: 01 00 00
```

This indicates that the page is 37 pixels wide, is 8 pixels high, has unknown X and Y resolution, is eventually lossless, does not contain any refinements, has a default pixel value of **0**, a default combination operator of OR, does not require any auxiliary buffers, and uses the page default combination operator in every region on the page.

34. The seventeenth segment header

```
02C8: 00 00 00 10 00 01 00 00 00 00 16
```

This segment has a segment number of 16, a type of "Symbol dictionary" (type 0), a short page association field, and does not have the deferred non-retain bit set. It refers to no other segments, and is retained. It is associated with no page, and has a data length of 22 bytes.

35. The seventeenth segment data part

02D3: 08 00 02 FF 00 00 00 01 00 00 00 01 4F E7 8D 68

02E3: 1B 14 2F 3F FF AC

- (a) The two-byte symbol dictionary flags field

02D3: 08 00

This field indicates that the segment is encoded using the arithmetic coding variant and does not use refinement/aggregate coding. **SDTEMPLATE** has the value 2. The “bitmap coding context used” and “bitmap coding context retained” bits are both 0.

- (b) The symbol dictionary AT flags field

02D5: 02 FF

This field indicates that **SDATX**₁ is 2 and **SDATY**₁ is -1; thus, AT pixel A_1 is at location (2, -1), which is the nominal value for template 2.

- (c) The four-byte **SDNUMEXSYMS** field.

02D7: 00 00 00 01

This field indicates that **SDNUMEXSYMS** is 1: one symbol is exported by this symbol dictionary.

- (d) The four-byte **SDNUMNEWSYMS** field.

02DB: 00 00 00 01


This field indicates that **SDNUMNEWSYMS** is 1: one symbol is defined by this symbol dictionary.

- (e) The encoded symbol dictionary data


02DF: 4F E7 8D 68 1B 14 2F 3F FF AC

This is decoded as follows.


- i. Reset all the arithmetic coding statistics to zero.
- ii. Using the IADH arithmetic integer decoding procedure, decode a height class delta height value. The value decoded is 6, indicating that the first height class is 6 pixels high.
- iii. Using the IADW arithmetic integer decoding procedure, decode a delta width value. The value decoded is 6. The first symbol thus has a width of 6 pixels.
- iv. Using the generic region decoding procedure, with **GBTEMPLATE** and the AT pixel A_1 set as described in the symbol dictionary data header, decode a 6×6 bitmap. This produces the bitmap shown in Figure H.12(a).
- v. Using the IADW arithmetic integer decoding procedure, decode a delta width value. The value decoded is OOB, indicating the end of the height class.
- vi. Since **SDNUMNEWSYMS** is 1, the last symbol has now been decoded.
- vii. Using the IAEX arithmetic integer decoding procedure, decode an export run length. The value decoded is 0, indicating that the first 0 symbols are not exported.
- viii. Using the IAEX arithmetic integer decoding procedure, decode an export run length. The value decoded is 1, indicating that the next 1 symbols are exported. Thus, this symbol dictionary defines one symbol, which is exported.



(a)



(b)



(c)

Figure H.12 — The symbols in the symbol dictionaries on the third page

36. The eighteenth segment header

02E9: 00 00 00 11 00 21 10 03 00 00 00 20

This segment has a segment number of 17, a type of “Symbol dictionary” (type 0), a short page association field, and does not have the deferred non-retain bit set. It refers to one other segment, segment 16. Segment 16 is not retained, but this segment is retained. It is associated with page 3, and has a data length of 32 bytes.

37. The eighteenth segment data part

02F5: 08 02 02 FF FF FF FF FF 00 00 00 03 00 00 00 02

0305: 4F E9 D7 D5 90 C3 B5 26 A7 FB 6D 14 98 3F FF AC

(a) The two-byte symbol dictionary flags field

02F5: 08 02

This field indicates that the segment is encoded using the arithmetic coding variant and uses refinement/aggregate coding. **SDTEMPLATE** has the value 2. **SDRTEMPLATE** has the value 0. The “bitmap coding context used” and “bitmap coding context retained” bits are both 0.

(b) The symbol dictionary AT flags field

02F7: 02 FF

This field indicates that **SDATX₁** is 2 and **SDATY₁** is -1; thus, AT pixel A_1 is at location (2, -1), which is the nominal value for template 2.

(c) The symbol dictionary refinement AT flags

02F9: FF FF FF FF

This field indicates that **SDRATX₁** is -1, **SDRATY₁** is -1, **SDRATX₂** is -1, and **SDRATY₂** is -1. Thus, AT pixel RA_1 is at location (-1, -1) and AT pixel RA_2 is at location (-1, -1), which are the nominal locations for refinement template 0.

(d) The four-byte **SDNUMEXSYMS** field.

02FD: 00 00 00 03

This field indicates that **SDNUMEXSYMS** is 3: three symbols are exported by this symbol dictionary.

(e) The four-byte **SDNUMNEWSYMS** field.

0301: 00 00 00 02

This field indicates that **SDNUMNEWSYMS** is 2: two symbols are defined by this symbol dictionary.

(f) The encoded symbol dictionary data

0305: 4F E9 D7 D5 90 C3 B5 26 A7 FB 6D 14 98 3F FF AC

This is decoded as follows.

- i. Reset all the arithmetic coding statistics to zero.
- ii. Using the IADH arithmetic integer decoding procedure, decode a height class delta height value. The value decoded is 6, indicating that the first height class is 6 pixels high.
- iii. Using the IADW arithmetic integer decoding procedure, decode a delta width value. The value decoded is 6. The first symbol thus has a width of 6 pixels.
- iv. Using the IAAI arithmetic integer decoding procedure, decode a count of symbol instances in the aggregation that forms the first symbol. The value decoded is 1.
- v. Using the IAID arithmetic integer decoding procedure, decode a symbol ID. The value decoded is 0. The first symbol is thus the one identified by symbol ID 0, which is the first (and only) symbol in the dictionary (segment 16) referenced by this segment.
- vi. Using the IARDX arithmetic integer decoding procedure, decode a symbol instance refinement delta X value. The value decoded is 0.
- vii. Using the IARDY arithmetic integer decoding procedure, decode a symbol instance refinement delta Y value. The value decoded is 0. The refinement is thus done with the refined symbol aligned with the reference symbol (i.e., **GRREFERENCEDX** and **GRREFERENCEDY** are both 0).

- viii. Using the generic refinement region decoding procedure, decode the refined symbol instance bitmap. The reference bitmap is the bitmap shown in Figure H.12(a) and the refined bitmap, which is the bitmap of the first symbol defined in this symbol dictionary, is the bitmap shown in Figure H.12(b).
- ix. Using the IADW arithmetic integer decoding procedure, decode a delta width value. The value decoded is 8. The second symbol thus has a width of 14 pixels.
- x. Using the IAAI arithmetic integer decoding procedure, decode a count of symbol instances in the aggregation that forms the second symbol. The value decoded is 2.
- xi. Using the text region decoding procedure, with parameters set as described in 6.5.8.2, decode a 14×6 pixel text region.
 - A. Using the IADT arithmetic integer decoding procedure, decode the initial STRIPT value. The value decoded is 0.
 - B. Using the IADT arithmetic integer decoding procedure, decode a delta T value. The value decoded is 0.
 - C. Using the IAFS arithmetic integer decoding procedure, decode a first S value. The value decoded is 0. The reference corner (top left corner in this case) of the first symbol instance in the aggregation is thus at (0, 0).
 - D. Using the IAID arithmetic integer decoding procedure, decode a symbol ID. The value decoded is 0. The first symbol is thus the one identified by symbol ID 0, which is the first (and only) symbol in the dictionary (segment 16) referenced by this segment.
 - E. Using the IARI arithmetic integer decoding procedure, decode a refinement flag. The value decoded is 0, indicating that the first symbol instance is not refined.
 - F. At this point CURS is 5. Using the IADS arithmetic integer decoding procedure, decode a delta S value. The value decoded is 3. The reference corner of the second symbol instance in the aggregation is thus at (8, 0).
 - G. Using the IAID arithmetic integer decoding procedure, decode a symbol ID. The value decoded is 1. The second symbol is thus the one identified by symbol ID 1, which is the first (and, thus far only) symbol defined in this symbol dictionary.
 - H. Using the IARI arithmetic integer decoding procedure, decode a refinement flag. The value decoded is 0, indicating that the first symbol instance is not refined.
 - I. Using the IADS arithmetic integer decoding procedure, decode a delta S value. The value decoded is OOB, indicating the end of the strip.
 - J. Decoding of the text region is now complete. The text region bitmap, which is the bitmap of the second symbol defined in the symbol dictionary, is shown in Figure H.12(c). This is obtained by drawing Figure H.12(a) at (0, 0) and Figure H.12(b) at (8, 0).
- xii. Using the IADW arithmetic integer decoding procedure, decode a delta width value. The value decoded is OOB, indicating the end of the height class.
- xiii. Since **SDNUMNEWSYMS** is 2, the last symbol has now been decoded.
- xiv. Using the IAEX arithmetic integer decoding procedure, decode an export run length. The value decoded is 0, indicating that the first 0 symbols are not exported.
- xv. Using the IAEX arithmetic integer decoding procedure, decode an export run length. The value decoded is 3, indicating that the next 3 symbols are exported. Thus, this symbol dictionary imports one symbol and defines two symbols, and all three are exported. Note that the symbol from segment 16 is re-exported by this dictionary. The three symbols exported by this dictionary are therefore the three symbols shown in Figure H.12. Thus, a text region may use the symbol shown in Figure H.12(a) (originally defined in segment 16) by referring to segment 17, even though segment 16 is not retained past the end of segment 17.

38. The nineteenth segment header

0315: 00 00 00 12 07 20 11 03 00 00 00 25

This segment has a segment number of 18, a type of “Immediate lossless text region” (type 7), a short page association field, and does not have the deferred non-retain bit set. It refers to one other segment, segment

17. Segment 17 and this segment should not be retained. It is associated with page 3, and has a data length of 37 bytes.

39. The nineteenth segment data part

```
0321: 00 00 00 25 00 00 00 08 00 00 00 00 00 00 00
0331: 00 8C 12 00 00 00 04 A9 5C 8B F4 C3 7D 96 6A 28
0341: E5 76 8F FF AC
```

(a)

(b) The region segment information field

```
0321: 00 00 00 25 00 00 00 08 00 00 00 00 00 00 00 00
0331: 00
```

This indicates that the region bitmap encoded by this segment is 37 pixels wide, 8 pixels high, and its top left corner is 0 pixels right of the page's left edge and 0 pixel down from the page's top edge. It should be drawn into the page using OR.

(c) The two-byte text region segment flags field

```
0332: 8C 12
```

This field indicates that the segment is encoded using the arithmetic coding variant, contains refinements, has a **SBSTRIPS** value of 1, has a reference corner of TOPLEFT, is not transposed, combines its symbols using OR, has a default pixel value of 0, has a **SBDSOFFSET** value of 3, and has a **SBRTEMPLATE** value of 1.

(d) The four-byte **SBNUMINSTANCES** field

```
0334: 00 00 00 04
```

This field indicates that **SBNUMINSTANCES** is 4: four symbol instances are encoded in this text region.

(e) The encoded text region data

```
0338: A9 5C 8B F4 C3 7D 96 6A 28 E5 76 8F FF AC
```

This is decoded as follows.

- i. Reset all the arithmetic coding statistics to zero.
- ii. Using the IADT arithmetic integer decoding procedure, decode the initial STRIPT value. The value decoded is 0.
- iii. Using the IADT arithmetic integer decoding procedure, decode a delta T value. The value decoded is 0.
- iv. Using the IAFS arithmetic integer decoding procedure, decode a first S value. The value decoded is 0. The reference corner (top left corner in this case) of the first symbol instance in the text region is thus at (0, 0).
- v. Using the IAID arithmetic integer decoding procedure, decode a symbol ID. The value decoded is 1. The first symbol instance thus uses the symbol shown in Figure H.12(b).
- vi. Using the IARI arithmetic integer decoding procedure, decode a refinement flag. The value decoded is 0, indicating that the first symbol instance is not refined.
- vii. At this point CURS is 5. Using the IADS arithmetic integer decoding procedure, decode a delta S value. The value decoded is 0. After adding in **SBDSOFFSET**, the reference corner of the second symbol instance in the aggregation is thus at (8, 0).
- viii. Using the IAID arithmetic integer decoding procedure, decode a symbol ID. The value decoded is 0. The second symbol instance thus uses the symbol shown in Figure H.12(a).
- ix. Using the IARI arithmetic integer decoding procedure, decode a refinement flag. The value decoded is 0, indicating that the first symbol instance is not refined.
- x. At this point CURS is 13. Using the IADS arithmetic integer decoding procedure, decode a delta S value. The value decoded is 0. After adding in **SBDSOFFSET**, the reference corner of the third symbol instance in the aggregation is thus at (16, 0).

- xi. Using the IAID arithmetic integer decoding procedure, decode a symbol ID. The value decoded is 1. The third symbol instance thus uses the symbol shown in Figure H.12(b).
- xii. Using the IARI arithmetic integer decoding procedure, decode a refinement flag. The value decoded is 1, indicating that the third symbol instance is refined.
- xiii. Using the IARDW arithmetic integer decoding procedure, decode a symbol instance refinement delta width value. The value decoded is -1.
- xiv. Using the IARDH arithmetic integer decoding procedure, decode a symbol instance refinement delta height value. The value decoded is 2. Since the reference symbol is 6×6 pixels, the refined symbol instance is therefore 5×8 pixels.
- xv. Using the IARDX arithmetic integer decoding procedure, decode a symbol instance refinement delta X value. The value decoded is 1.
- xvi. Using the IARDY arithmetic integer decoding procedure, decode a symbol instance refinement delta Y value. The value decoded is -2. **GRREFERENCEDX** and **GRREFERENCEDY** are therefore set as

$$\mathbf{GRREFERENCEDX} = \lfloor -1/2 \rfloor + 1 = -1 + 1 = 0$$

$$\mathbf{GRREFERENCEDY} = \lfloor 2/2 \rfloor - 2 = 1 - 2 = -1$$

so the refinement is done with the refined symbol placed so that the top left pixel of the refined symbol is aligned with pixel (0, 1) of the reference symbol.

- xvii. Using the generic refinement region decoding procedure, decode the refined symbol instance bitmap. The reference bitmap is the bitmap shown in Figure H.12(b) and the refined bitmap, which is the bitmap for the third symbol instance, is the bitmap shown in Figure H.2.
- xviii. At this point CURS is 18. Using the IADS arithmetic integer decoding procedure, decode a delta S value. The value decoded is 0. After adding in **SBDSOFFSET**, the reference corner of the third symbol instance in the aggregation is thus at (23, 0).
- xix. Using the IAID arithmetic integer decoding procedure, decode a symbol ID. The value decoded is 2. The fourth symbol instance thus uses the symbol shown in Figure H.12(c).
- xx. Using the IADS arithmetic integer decoding procedure, decode a delta S value. The value decoded is OOB, indicating the end of the strip.
- xxi. Decoding of the text region is now complete. The text region bitmap is the bitmap shown in Figure H.5. It is obtained by drawing Figure H.12(b) with its top left corner at (0, 0), Figure H.12(a) with its top left corner at (8, 0), Figure H.2 with its top left corner at (16, 0), and Figure H.12(c) with its top left corner at (23, 0).

40. The twentieth segment header

0346: 00 00 00 13 31 00 03 00 00 00 00

This segment has a segment number of 19, a type of “End of page” (type 49), a short page association field, and does not have the deferred non-retain bit set. It refers to no other segments, and is not retained. It is associated with page 3, and has a data length of zero bytes.

41. The page bitmap is formed from the page’s only region segment, segment number 18, and is equal to that region segment’s bitmap (Figure H.5).

42. The twenty-first segment header

0351: 00 00 00 14 33 00 00 00 00 00 00

This segment has a segment number of 20, a type of “End of file” (type 51), a short page association field, and does not have the deferred non-retain bit set. It refers to no other segments, and is not retained. It is associated with no page, and has a data length of zero bytes.

H.2 Test sequence for arithmetic coder

In this subclause a small data set is provided for testing the arithmetic encoder and decoder. The test is structured to test many of the encoder and decoder paths, but it is impossible in a short test sequence to check all of them so agreement with the results of this test unfortunately does not guarantee a completely correct implementation.

The decisions to be encoded, packed into 32 bytes and shown in hexadecimal, are

```
00 02 00 51 00 00 00 C0 03 52 87 2A AA AA AA AA
82 C0 20 00 FC D7 9E F6 BF 7F ED 90 4F 46 A3 BF
```

The encoded data that should be obtained by encoding that sequence, shown as 30 hexadecimal bytes, are

```
84 C7 3B FC E1 A1 43 04 02 20 00 00 41 0D BB 86
F4 31 7F FF 88 FF 37 47 1A DB 6A DF FF AC
```

Decoding those 30 bytes should produce the 32 original bytes.

Table H.1 provides a bit-by-bit list of the arithmetic encoder and decoder operation. The first line in this table corresponds to the INITENC and INITDEC operations. The value of the byte before the first byte in the output buffer is assumed to be 0x00, making the initial value of B 0x00. The last line in the table corresponds to the FLUSH operation.

For this entire test, a single value of CX is used. I(CX) is initially 0 and MPS(CX) is initially 0.

The first column is the event counter EC. The second column is the decision D to be encoded. The third and fourth columns give the values of I(CX) and MPS(CX). The fifth column shows an “X” indicates that the conditional exchange will occur when encoding (decoding) the current decision. The sixth column shows the current Qe value corresponding to I(CX) (see Table E.1). The seventh column shows the value of the register A before the decision is encoded (decoded). Note that the A register is always greater than or equal to 0x8000.

The variables up to this point were common for the encoder and decoder. The next four columns (C, CT, B, OUT) are only for the encoder. The next four columns (C, CT, B, IN) are only for the decoder. The final column (C) shows the C register for the software-conventions decoder, as it is the only value that differs for the software-conventions decoder. All the values shown for the C registers are given before the current decision is encoded (decoded).

For the encoder, CT is a counter indicating when a byte is ready for output from register C. The column under B shows the byte in variable B waiting to be sent out. This byte can sometimes change from a carry-over. Finally, for the encoder the compressed bytes are listed under column OUT. A byte is considered to be “output” when the compressed data pointer BP is advanced to point beyond it.

The decoder’s counter CT indicates when to input the next byte from the compressed data. The column under B shows the value of the B register, which is used to determine when a bit-stuffing has occurred. The column under IN shows the bytes that are consumed. A byte is considered to be “consumed” when the compressed data pointer BP is advanced to point at it. Note that the final 0xAC byte is never consumed, according to this definition, though it is read as part of BYTEIN.

Table H.1 — Encoder and decoder trace data

Common							Encoder				Decoder				Software- Conventions Decoder
EC	D	I	MPS	CE	Qe hex	A hex	C hex	CT	B hex	OUT hex	C hex	CT	B hex	IN hex	C hex
0									00		00000000			84 C7	00000000
1	0	0	0	X	5601	8000	00000000	12	00		42638000	1	C7		3D9C0000
2	0	1	0		3401	AC02	00000000	11	00		84C70000	0	C7	3B	273A0000
3	0	2	0		1801	F002	00006802	10	00		A18C7600	7	3B		4E758800
4	0	2	0		1801	D801	00008003	10	00		898B7600	7	3B		4E758800
5	0	2	0		1801	C000	00009804	10	00		718A7600	7	3B		4E758800
6	0	2	0		1801	A7FF	0000B005	10	00		59897600	7	3B		4E758800
7	0	2	0		1801	8FFE	0000C806	10	00		41887600	7	3B		4E758800
8	0	3	0		0AC1	EFFA	0001C00E	9	00		530EEC00	6	3B		9CEB1000
9	0	3	0		0AC1	E539	0001CACF	9	00		484DEC00	6	3B		9CEB1000
10	0	3	0		0AC1	DA78	0001D590	9	00		3D8CEC00	6	3B		9CEB1000
11	0	3	0		0AC1	CFB7	0001E051	9	00		32CBEC00	6	3B		9CEB1000
12	0	3	0		0AC1	C4F6	0001EB12	9	00		280AEC00	6	3B		9CEB1000
13	0	3	0		0AC1	BA35	0001F5D3	9	00		1D49EC00	6	3B		9CEB1000
14	0	3	0		0AC1	AF74	00020094	9	00		1288EC00	6	3B		9CEB1000
15	1	3	0		0AC1	A4B3	00020B55	9	00		07C7EC00	6	3B		9CEB1000
16	0	12	0		1C01	AC10	0020B550	5	00		7C7EC000	2	3B		2F910000
17	0	12	0		1C01	900F	0020D151	5	00		607DC000	2	3B		2F910000
18	0	13	0		1601	E81C	0041DAA4	4	00		88F98000	1	3B		5F220000
19	0	13	0		1601	D21B	0041F0A5	4	00		72F88000	1	3B		5F220000
20	0	13	0		1601	BC1A	004206A6	4	00		5CF78000	1	3B		5F220000
21	0	13	0		1601	A619	00421CA7	4	00		46F68000	1	3B		5F220000
22	0	13	0		1601	9018	004232A8	4	00		30F58000	1	3B		5F220000
23	0	29	0		1101	F42E	00849152	3	00		35E90000	0	3B		BE440000
24	0	29	0		1101	E32D	0084A253	3	00		24E80000	0	3B		BE440000
25	0	29	0		1101	D22C	0084B354	3	00		13E70000	0	3B		BE440000
26	1	29	0		1101	C12B	0084C455	3	84		02E60000	0	3B	FC	BE440000
27	0	27	0		1401	8808	000622A8	8	84		1737E000	5	FC		70D01800
28	1	28	0		1201	E80E	000C6D52	7	84		066DC000	4	FC		E1A03000
29	0	26	0		1601	9008	00636A90	4	84		336E0000	1	FC		5C998000
30	0	27	0		1401	F40E	00C70122	3	84		3ADA0000	0	FC		B9330000
31	0	27	0		1401	E00D	00C71523	3	84		26D90000	0	FC		B9330000
32	1	27	0		1401	CC0C	00C72924	3	C7	84	12D80000	0	FC	E1	B9330000
33	0	25	0		1801	A008	00014920	8	C7		96C70800	5	E1		0940F000
34	0	25	0		1801	8807	00016121	8	C7		7EC60800	5	E1		0940F000
35	0	26	0		1601	E00C	0002F244	7	C7		CD8A1000	4	E1		1281E000
36	0	26	0		1601	CA0B	00030845	7	C7		B7891000	4	E1		1281E000
37	0	26	0		1601	B40A	00031E46	7	C7		A1881000	4	E1		1281E000
38	0	26	0		1601	9E09	00033447	7	C7		8B871000	4	E1		1281E000
39	0	26	0		1601	8808	00034A48	7	C7		75861000	4	E1		1281E000
40	0	27	0		1401	E40E	0006C092	6	C7		BF0A2000	3	E1		2503C000
41	0	27	0		1401	D00D	0006D493	6	C7		AB092000	3	E1		2503C000
42	0	27	0		1401	BC0C	0006E894	6	C7		97082000	3	E1		2503C000
43	0	27	0		1401	A80B	0006FC95	6	C7		83072000	3	E1		2503C000
44	0	27	0		1401	940A	00071096	6	C7		6F062000	3	E1		2503C000
45	0	27	0		1401	8009	00072497	6	C7		5B052000	3	E1		2503C000
46	0	28	0		1201	D810	000E7130	5	C7		8E084000	2	E1		4A078000
47	0	28	0		1201	C60F	000E8331	5	C7		7C074000	2	E1		4A078000
48	0	28	0		1201	B40E	000E9532	5	C7		6A064000	2	E1		4A078000
49	0	28	0		1201	A20D	000EA733	5	C7		58054000	2	E1		4A078000
50	0	28	0		1201	900C	000EB934	5	C7		46044000	2	E1		4A078000
51	0	29	0		1101	FC16	001D966A	4	C7		68068000	1	E1		940F0000
52	0	29	0		1101	EB15	001DA76B	4	C7		57058000	1	E1		940F0000
53	0	29	0		1101	DA14	001DB86C	4	C7		46048000	1	E1		940F0000
54	0	29	0		1101	C913	001DC96D	4	C7		35038000	1	E1		940F0000
55	0	29	0		1101	B812	001DDA6E	4	C7		24028000	1	E1		940F0000
56	0	29	0		1101	A711	001DEB6F	4	C7		13018000	1	E1		940F0000
57	1	29	0		1101	9610	001DFC70	4	C7		02008000	1	E1	A1	940F0000
58	1	27	0		1401	8808	00EFE380	1	3B	C7	10068400	6	A1		78017800
59	0	25	0		1801	A008	001F1C00	6	3B		80342000	3	A1		1FD3C000
60	0	25	0		1801	8807	001F3401	6	3B		68332000	3	A1		1FD3C000
61	0	26	0		1601	E00C	003E9804	5	3B		A0644000	2	A1		3FA78000
62	0	26	0		1601	CA0B	003EAE05	5	3B		8A634000	2	A1		3FA78000
63	0	26	0		1601	B40A	003EAC06	5	3B		74624000	2	A1		3FA78000
64	0	26	0		1601	9E09	003EDA07	5	3B		5E614000	2	A1		3FA78000

Table H.1 (continued)

Common						Encoder				Decoder				Software- Conventions Decoder	
EC	D	I	MPS	CE	Qe hex	A hex	C hex	CT	B hex	OUT hex	C hex	CT	B hex	IN hex	C hex
65	0	26	0		1601	8808	003EF008	5	3B		48604000	2	A1		3FA78000
66	0	27	0		1401	E40E	007E0C12	4	3B		64BE8000	1	A1		7F4F0000
67	0	27	0		1401	D00D	007E2013	4	3B		50BD8000	1	A1		7F4F0000
68	0	27	0		1401	BC0C	007E3414	4	3B		3CBC8000	1	A1		7F4F0000
69	0	27	0		1401	A80B	007E4815	4	3B		28BB8000	1	A1		7F4F0000
70	0	27	0		1401	940A	007E5C16	4	3B		14BA8000	1	A1		7F4F0000
71	1	27	0		1401	8009	007E7017	4	3B		00B98000	1	A1	43	7F4F0000
72	1	25	0		1801	A008	03F380B8	1	FC	3B	05CD0C00	6	43		9A3AF000
73	0	23	0		2201	C008	001C05C0	6	FC		2E686000	3	43		919F8000
74	1	23	0		2201	9E07	001C27C1	6	FC		0C676000	3	43		919F8000
75	0	21	0		2801	8804	00709F04	4	FC		319D8000	1	43		56660000
76	1	22	0		2401	C006	00E18E0A	3	FC		13390000	0	43	04	ACCC0000
77	0	20	0		3001	9004	03863828	1	E1	FC	4CE41000	6	04		431FEC00
78	0	21	0		2801	C006	0004D052	8	E1		39C62000	5	04		863FD800
79	1	21	0		2801	9805	0004F853	8	E1		11C52000	5	04		863FD800
80	0	19	0		3401	A004	0013E14C	6	E1		47148000	3	04		58EF6000
81	1	20	0		3001	D806	00282A9A	5	E1		26270000	2	04		B1DEC000
82	0	19	0		3401	C004	00A0AA68	3	E1		989C0000	0	04		27670000
83	0	19	0		3401	8C03	00A0DE69	3	E1		649B0000	0	04	02	27670000
84	0	20	0		3001	B004	014224D4	2	E1		61340400	7	02		4ECFFA00
85	0	20	0		3001	8003	014254D5	2	E1		31330400	7	02		4ECFFA00
86	1	21	0		2801	A004	028509AC	1	A1	E1	02640800	6	02		9D9FF400
87	1	19	0		3401	A004	000426B0	7	A1		09902000	4	02		9673D000
88	1	18	0		3801	D004	00109AC0	5	A1		26408000	2	02		A9C34000
89	0	17	0		4801	E004	00426B00	3	A1		99020000	0	02		47010000
90	0	17	0		4801	9803	0042B301	3	A1		51010000	0	02	20	47010000
91	1	18	0		3801	A004	0085F604	2	42	A1	12004000	7	20		8E03BE00
92	0	17	0		4801	E004	0007D810	8	42		48010000	5	20		9802F800
93	1	17	0		4801	9803	00082011	8	42		00000000	5	20		9802F800
94	0	16	0	X	5101	9002	00104022	7	42		00000000	4	20		9001F000
95	1	17	0		4801	A202	00208044	6	42		00000000	3	20		A201E000
96	0	16	0	X	5101	9002	00410088	5	42		00000000	2	20		9001C000
97	1	17	0		4801	A202	00820110	4	42		00000000	1	20		A2018000
98	0	16	0	X	5101	9002	01040220	3	42		00000000	0	20	00	90010000
99	1	17	0		4801	A202	02080440	2	42		00000000	7	00		A201FE00
100	0	16	0	X	5101	9002	04100880	1	04	43	00000000	6	00		9001FC00
101	1	17	0		4801	A202	00001100	8	04		00000000	5	00		A201F800
102	0	16	0	X	5101	9002	00002200	7	04		00000000	4	00		9001F000
103	1	17	0		4801	A202	00004400	6	04		00000000	3	00		A201E000
104	0	16	0	X	5101	9002	00008800	5	04		00000000	2	00		9001C000
105	1	17	0		4801	A202	00011000	4	04		00000000	1	00		A2018000
106	0	16	0	X	5101	9002	00022000	3	04		00000000	0	00		90010000
107	1	17	0		4801	A202	00044000	2	04		00000000	7	00		A201FE00
108	0	16	0	X	5101	9002	00088000	1	02	04	00000000	6	00		9001FC00
109	1	17	0		4801	A202	00010000	8	02		00000000	5	00		A201F800
110	0	16	0	X	5101	9002	00020000	7	02		00000000	4	00		9001F000
111	1	17	0		4801	A202	00040000	6	02		00000000	3	00		A201E000
112	0	16	0	X	5101	9002	00080000	5	02		00000000	2	00		9001C000
113	1	17	0		4801	A202	00100000	4	02		00000000	1	00		A2018000
114	0	16	0	X	5101	9002	00200000	3	02		00000000	0	00	41	90010000
115	1	17	0		4801	A202	00400000	2	02		00008200	7	41		A2017C00
116	0	16	0	X	5101	9002	00800000	1	20	02	00010400	6	41		9000F800
117	1	17	0		4801	A202	00000000	8	20		00020800	5	41		A1FFF000
118	0	16	0	X	5101	9002	00000000	7	20		00041000	4	41		8FFDE000
119	1	17	0		4801	A202	00000000	6	20		00082000	3	41		A1F9C000
120	0	16	0	X	5101	9002	00000000	5	20		00104000	2	41		8FF18000
121	1	17	0		4801	A202	00000000	4	20		00208000	1	41		A1E10000
122	0	16	0	X	5101	9002	00000000	3	20		00410000	0	41	0D	8FC00000
123	1	17	0		4801	A202	00000000	2	20		00821A00	7	0D		A17FE400
124	0	16	0	X	5101	9002	00000000	1	00	20	01043400	6	0D		8EFDC800
125	1	17	0		4801	A202	00000000	8	00		02086800	5	0D		9FF99000
126	0	16	0	X	5101	9002	00000000	7	00		0410D000	4	0D		8BF12000
127	1	17	0		4801	A202	00000000	6	00		0821A000	3	0D		99E04000
128	0	16	0	X	5101	9002	00000000	5	00		10434000	2	0D		7FBE8000

Table H.1 (continued)

Common						Encoder				Decoder				Software- Conventions Decoder	
EC	D	I	MPS	CE	Qe hex	A hex	C hex	CT	B hex	OUT hex	C hex	CT	B hex	IN hex	C hex
129	1	17	0		4801	A202	00000000	4	00		20868000	1	0D		817B0000
130	0	16	0	X	5101	9002	00000000	3	00		410D0000	0	0D	BB	4EF40000
131	0	17	0		4801	A202	00000000	2	00		821B7600	7	BB		1FE68800
132	0	18	0		3801	B402	00009002	1	00	00	7434EC00	6	BB		3FCD1000
133	0	19	0		3401	F802	00019006	8	00		7867D800	5	BB		7F9A2000
134	0	19	0		3401	C401	0001C407	8	00		4466D800	5	BB		7F9A2000
135	1	19	0		3401	9000	0001F808	8	00		1065D800	5	BB		7F9A2000
136	0	18	0		3801	D004	0007E020	6	00		41976000	3	BB		8E6C8000
137	1	18	0		3801	9803	00081821	6	00		09966000	3	BB		8E6C8000
138	1	17	0		4801	E004	00206084	4	00		26598000	1	BB		B9AA0000
139	0	16	0	X	5101	9002	0040C108	3	00		4CB30000	0	BB	86	434E0000
140	0	17	0		4801	A202	00818210	2	00		99670C00	7	86		089AF200
141	0	18	0		3801	B402	01039422	1	40	00	A2CC1800	6	86		1135E400
142	0	19	0		3401	F802	00079846	8	40		D5963000	5	86		226BC800
143	0	19	0		3401	C401	0007CC47	8	40		A1953000	5	86		226BC800
144	0	19	0		3401	9000	00080048	8	40		6D943000	5	86		226BC800
145	0	20	0		3001	B7FE	00106892	7	40		73266000	4	86		44D79000
146	0	20	0		3001	87FD	00109893	7	40		43256000	4	86		44D79000
147	1	21	0		2801	AF8	00219128	6	40		2648C000	3	86		89AF2000
148	0	19	0		3401	A004	008644A0	4	40		99230000	1	86		06E08000
149	0	20	0		3001	D806	010CF142	3	40		CA440000	0	86		0DC10000
150	0	20	0		3001	A805	010D2143	3	40		9A430000	0	86	F4	0DC10000
151	0	21	0		2801	F008	021AA288	2	40		D485E800	7	F4		1B821600
152	0	21	0		2801	C807	021ACA89	2	40		AC84E800	7	F4		1B821600
153	0	21	0		2801	A006	021AF28A	2	40		8483E800	7	F4		1B821600
154	0	22	0		2401	F00A	04363516	1	40		B905D000	6	F4		37042C00
155	0	22	0		2401	CC09	04365917	1	40		9504D000	6	F4		37042C00
156	0	22	0		2401	A808	04367D18	1	40		7103D000	6	F4		37042C00
157	0	22	0		2401	8407	0436A119	1	0D	41	4D02D000	6	F4		37042C00
158	0	23	0		2201	C00C	00058A34	8	0D		5203A000	5	F4		6E085800
159	0	23	0		2201	9E0B	0005AC35	8	0D		3002A000	5	F4		6E085800
160	0	24	0		1C01	F814	000B9C6C	7	0D		1C034000	4	F4		DC10B000
161	1	24	0		1C01	DC13	000BB86D	7	0D		00024000	4	F4		DC10B000
162	1	22	0		2401	E008	005DC368	4	0D		00120000	1	F4	31	DFE58000
163	1	20	0		3001	9004	01770DA0	2	BB	0D	00486200	7	31		8FBB9C00
164	1	19	0		3401	C004	00043680	8	BB		01218800	5	31		BEE27000
165	1	18	0		3801	D004	0010DA00	6	BB		04862000	3	31		CB7DC000
166	1	17	0		4801	E004	00436800	4	BB		12188000	1	31		CDEB0000
167	0	16	0	X	5101	9002	0086D000	3	BB		24310000	0	31	7F	6BD00000
168	0	17	0		4801	A202	010DA000	2	BB		4862FE00	7	7F		599F0000
169	1	18	0		3801	B402	021BD002	1	86	BB	00C3FC00	6	7F		B33E0000
170	1	17	0		4801	E004	000F4008	7	86		030FF000	4	7F		DCF40000
171	0	16	0	X	5101	9002	001E8010	6	86		061FE000	3	7F		89E20000
172	1	17	0		4801	A202	003D0020	5	86		0C3FC000	2	7F		95C20000
173	0	16	0	X	5101	9002	007A0040	4	86		187F8000	1	7F		77820000
174	1	17	0		4801	A202	00F40080	3	86		30FF0000	0	7F	FF	71020000
175	1	16	0	X	5101	9002	01E80100	2	F4	86	61FFFE00	7	FF		2E020000
176	1	15	0		5401	FC04	00014804	8	F4		43FBF800	5	FF		B8080000
177	1	14	0	X	5601	A802	00029008	7	F4		877F7000	4	FF		200A0000
178	0	14	1	X	5601	A402	0005CC12	6	F4		63EDE000	3	FF		40140000
179	0	14	0	X	5601	9C02	000C4426	5	F4		1BD9C000	2	FF		80280000
180	1	15	0		5401	AC02	0018884C	4	F4		37B38000	1	FF		744E0000
181	1	14	0	X	5601	A802	00311098	3	F4		6F670000	0	FF	88	389A0000
182	1	14	1	X	5601	A402	0062CD32	2	F4		32CE2000	6	88		7133DC00
183	1	15	1		5401	AC02	00C59A64	1	31	F4	659C4000	5	88		4665B800
184	0	16	1		5101	B002	0003DCCA	8	31		23368000	4	88		8CCB7000
185	1	15	1	X	5401	A202	0007B994	7	31		466D0000	3	88		5B94E000
186	1	16	1		5101	A802	000F7328	6	31		8CDA0000	2	88		1B27C000
187	1	17	1		4801	AE02	001F8852	5	31		77B20000	1	88		364F8000
188	1	18	1		3801	CC02	003FA0A6	4	31		5F620000	0	88		6C9F0000
189	0	18	1		3801	9401	003FD8A7	4	31		27610000	0	88	FF	6C9F0000
190	1	17	1		4801	E004	00FF629C	2	31		9D87FC00	6	FF		427C0000
191	1	17	1		4801	9803	00FFAA9D	2	31		5586FC00	6	FF		427C0000
192	0	18	1		3801	A004	01FFE53C	1	7F	31	1B0BF800	5	FF		84F80000

Table H.1 (concluded)

Common							Encoder				Decoder				Software- Conventions Decoder
EC	D	I	MPS	CE	Qe hex	A hex	C hex	CT	B hex	OUT hex	C hex	CT	B hex	IN hex	C hex
193	1	17	1		4801	E004	000F94F0	7	7F		6C2FE000	3	FF		73D40000
194	0	17	1		4801	9803	000FDC1	7	7F		242EE000	3	FF		73D40000
195	1	16	1	X	5101	9002	001FB9E2	6	7F		485DC000	2	FF		47A40000
196	1	17	1		4801	A202	003F73C4	5	7F		90BB8000	1	FF		11460000
197	1	18	1		3801	B402	007F778A	4	7F		91750000	0	FF	37	228C0000
198	1	19	1		3401	F802	00FF5F16	3	7F		B2E8DC00	6	37		45192000
199	1	19	1		3401	C401	00FF9317	3	7F		7EE7DC00	6	37		45192000
200	1	19	1		3401	9000	00FFC718	3	7F		4AE6DC00	6	37		45192000
201	0	20	1		3001	B7FE	01FFF632	2	FF	7F	2DCBB800	5	37		8A324000
202	1	19	1		3401	C004	0007D8C8	8	FF		B72EE000	3	37		08D50000
203	1	19	1		3401	8C03	00080CC9	8	FF		832DE000	3	37		08D50000
204	1	20	1		3001	B004	00108194	7	FF		9E59C000	2	37		11AA0000
205	1	20	1		3001	8003	0010B195	7	FF		6E58C000	2	37		11AA0000
206	1	21	1		2801	A004	0021C32C	6	FF		7CAF8000	1	37		23540000
207	1	22	1		2401	F006	0043D65A	5	FF		A95D0000	0	37		46A80000
208	1	22	1		2401	CC05	0043FA5B	5	FF		855C0000	0	37		46A80000
209	1	22	1		2401	A804	00441E5C	5	FF		615B0000	0	37		46A80000
210	1	22	1		2401	8403	0044425D	5	FF		3D5A0000	0	37	47	46A80000
211	1	23	1		2201	C004	0088CCBC	4	FF		32B28E00	7	47		8D517000
212	0	23	1		2201	9E03	0088EEBD	4	FF		10B18E00	7	47		8D517000
213	1	21	1		2801	8804	0223BAF4	2	FF		42C63800	5	47		453DC000
214	1	22	1		2401	C006	0447C5EA	1	FF		358A7000	4	47		8A7B8000
215	0	22	1		2401	9C05	0447E9EB	1	88	FF	11897000	4	47		8A7B8000
216	1	20	1		3001	9004	001FA7AC	6	88		4625C000	2	47		49DE0000
217	1	21	1		2801	C006	003FAF5A	5	88		2C498000	1	47		93BC0000
218	0	21	1		2801	9805	003FD75B	5	88		04488000	1	47	1A	93BC0000
219	0	19	1		3401	A004	00FF5D6C	3	88		11223400	7	1A		8EE1CA00
220	1	18	1		3801	D004	03FD75B0	1	88		4488D000	5	1A		8B7B2800
221	0	18	1		3801	9803	03FDADB1	1	FF	88	0C87D000	5	1A		8B7B2800
222	0	17	1		4801	E004	0006B6C4	7	FF		321F4000	3	1A		ADE4A000
223	0	16	1	X	5101	9002	000D6D88	6	FF		643E8000	2	1A		2BC34000
224	0	15	1		5401	FC04	0036FA24	4	FF		4CF60000	0	1A	DB	AF0D0000
225	0	14	1	X	5601	A802	006DF448	3	FF		99EDB600	7	DB		0E144800
226	1	14	0	X	5601	A402	00DC9492	2	FF		87D96C00	6	DB		1C289000
227	0	14	1	X	5601	9C02	01B9D526	1	37	FF	63B0D800	5	DB		38512000
228	0	14	0	X	5601	8C02	0004564E	7	37		1B5FB000	4	DB		70A24000
229	1	15	0		5401	AC02	0008AC9C	6	37		36BF6000	3	DB		75428000
230	1	14	0	X	5601	A802	00115938	5	37		6D7EC000	2	DB		3A830000
231	1	14	1	X	5601	A402	00235E72	4	37		2EFB8000	1	DB		75060000
232	1	15	1		5401	AC02	0046BCE4	3	37		5DF70000	0	DB	6A	4E0A0000
233	0	16	1		5101	B002	008E21CA	2	37		13ECD400	7	6A		9C152A00
234	1	15	1	X	5401	A202	011C4394	1	47	37	27D9A800	6	6A		7A285400
235	0	16	1		5101	A802	00008728	8	47		4FB35000	5	6A		584EA800
236	0	15	1	X	5401	A202	00010E50	7	47		9F66A000	4	6A		029B5000
237	0	14	1	X	5601	9C02	0002C4A2	6	47		96CB4000	3	6A		0536A000
238	1	14	0	X	5601	8C02	00063546	5	47		81948000	2	6A		0A6D4000
239	1	14	1		5601	D804	001A2D1C	3	47		AE4E0000	0	6A		29B50000
240	0	14	1	X	5601	8203	001A831D	3	47		584D0000	0	6A	DF	29B50000
241	1	14	0		5601	B008	006B6478	1	1A	47	09337C00	6	DF		A6D48000
242	0	14	1		5601	AC02	0006C8F0	8	1A		1266F800	5	DF		999B0000
243	1	14	0		5601	AC02	000D91E0	7	1A		24CDF000	4	DF		87340000
244	0	14	1		5601	AC02	001B23C0	6	1A		499BE000	3	DF		62660000
245	0	14	0		5601	AC02	00364780	5	1A		9337C000	2	DF		18CA0000
246	0	15	0		5401	AC02	006D3B02	4	1A		7A6D8000	1	DF		31940000
247	1	16	0		5101	B002	00DB1E06	3	1A		4CD90000	0	DF	FF	63280000
248	1	15	0	X	5401	A202	01B63C0C	2	1A		99B3FE00	7	FF		084E0000
249	1	14	0	X	5601	9C02	036D201A	1	DB	1A	8B65FC00	6	FF		109C0000
250	0	14	1	X	5601	8C02	0002EC36	8	DB		6AC9F800	5	FF		21380000
251	1	14	0		5601	D804	000D08DC	6	DB		5323E000	3	FF		84E00000
252	1	14	1		5601	AC02	001A11B8	5	DB		A647C000	2	FF		05BA0000
253	1	15	1		5401	AC02	0034CF72	4	DB		A08D8000	1	FF		0B740000
254	1	16	1		5101	B002	006A46E6	3	DB		99190000	0	FF		16E80000
255	1	17	1		4801	BE02	00D52FCE	2	DB		9031FE00	7	FF		2DD00000
256	1	18	1		3801	EC02	01AAEF9E	1	DB		9061FC00	6	FF		5BA00000
257															

Annex I

(informative)

List of Patents

The user's attention is called to the possibility that compliance with this Specification may require use of an invention covered by patent rights.

By publication of this Specification, no position is taken with respect to the validity of the claim or of any patent rights in connection therewith.

The criteria for including patents in this annex are:

1. The patent has been identified by someone who is familiar with the technical fields relevant to this Specification, and who believes use of the invention covered by the patent is required for implementation of one or more of the coding processes specified.
2. The patent holder has filed a letter stating willingness to grant a license to an unlimited number of applicants throughout the world under reasonable terms and conditions that are demonstrably free of any unfair discrimination.

During maintenance of this Specification, the list of patents shall be updated, if necessary, upon any revisions to the Recommendation | International Standard.

Only patents in the home countries of the patent-holding corporations are listed. In many cases foreign filings have been made.

I.1 List of patents

The holders of the following patents have filed a statement of willingness to grant a license under these rights on reasonable and non-discriminatory terms and conditions to applications desiring to obtain such a license.

1. Korean Patent, 10-97-068093, 1997 (pending), Kwang Woon University, Hyung Hwa Ko et al.: LOSSY/LOSS-LESS CODING METHOD FOR BINARY IMAGE BY EFFICIENT UTILIZATION OF PATTERN CORRELATION
2. US Patent, 4 749 983, IBM, Compression of multilevel signals, June 7, 1988

It is the understanding of ISO/IEC JTC1 SC29/WG1 that the holders of the following patents have agreed to allow payment free licensing of those patents for use in connection with this Recommendation | International Standard, subject to certain conditions which are available on request from the sources listed. Prospective licensees are advised to contact the respective organisations for details.

1. Japanese Patent, 2128115, Feb. 1990, Mitsubishi Electric Corp., Ono (F.) et al.: CODING SYSTEM
2. Japanese Patent, 2128110, Jan. 1989, Mitsubishi Electric Corp., Ono (F.) et al.: CODING METHOD OF IMAGE INFORMATION
3. US Patent, 4 286 256, IBM, Method and means for arithmetic coding using a reduced number of operations, August 25, 1981.
4. US Patent, 4 295 125, IBM, A method and means for pipeline decoding of the high to low order pairwise combined digits of a decodable set of relatively shifted finite number of strings, Oct. 13, 1981.
5. US Patent, 4 463 342, IBM, A method and means for carry-over control in a high order to low order combining of digits of a decodable set of relatively shifted finite number strings, July 31, 1984.
6. US Patent, 4 467 317, IBM, High-speed arithmetic compression using concurrent value updating, August 21, 1984.
7. US Patent, 4 652 856, IBM, A multiplication-free multi-alphabet arithmetic code, Feb. 4, 1986.
8. US Patent, 4 633 490, IBM, Symmetrical adaptive data compression/decompression system, Dec. 30, 1986.

9. US Patent, 4 891 643, IBM, Arithmetic coding data compression/de compression by selectively employed, diverse arithmetic encoders and decoders, January 2, 1990.
10. US Patent, 4 905 297, IBM, Arithmetic coding encoder and decoder system, February 27, 1990.
11. US Patent, 4 935 882, IBM, Probability adaptation for arithmetic coders, June 19, 1990.
12. US Patent, 5 099 440, IBM, Probability adaptation for arithmetic coders, March 24, 1992.

I.2 Contact addresses for patent information

Mitsubishi Electric Corp.
Intellectual Property Licensing Dept.
2-2-3 Marunouchi, Choyoda-ku, Tokyo 100-8310, Japan
Tel: +81 3 3218 3465
Fax: +81 3 3218 2474

447-1 Weol-Gye Dong, No-Won Gu,
Seoul, 137-050, Korea
Kwang Woon University
Tel: +82 2 940 5131
Fax: +82 2 942 0107

Program Manager, Licensing
Intellectual Property and Licensing Services
IBM Corporation
208 Harbor Drive
P.O. Box 10501
Stamford, Connecticut 08904-2501
Tel: +1 (203) 973 7935
Fax: +1 (203) 973 7981 or +1 (203) 973 7982

Annex J
(informative)
References

- [1] R. N. Ascher and G. Nagy. A means for achieving a high degree of compaction on scan-digitized printed text. *IEEE Transactions on Computers*, C-23:1174–1179, November 1974.
- [2] A. Bilgin, P. Sementilli, and M. Marcellin. Progressive image coding using trellis coded quantization. *IEEE Transactions on Image Processing*, November 1997. (submitted).
- [3] C. Constantinescu and R. Arps. Fast residue coding for lossless textual image compression. In *Proc. of Data Compression Conference*, pages 397–406, Snowbird, Utah, USA, 1997.
- [4] S. Forchhammer and K. S. Jensen. Data compression of scanned halftone images. *IEEE Trans. Commun.*, 42:1881–1893, Feb–Apr 1994.
- [5] P. G. Howard. Lossless and lossy compression of text images by soft pattern matching. In *Proc. of Data Compression Conference*, pages 210–219, 1996.
- [6] P. G. Howard. Text image compression using soft pattern matching. *Computer Journal*, 40:2–3, 1997.
- [7] P.G. Howard, F. Kossentini, B. Martins, S. Forchhammer, and W.J. Rucklidge. The emerging JBIG2 standard. *IEEE Transactions on Circuits and Systems for Video Technology*, 8(7):838–848, November 1998.
- [8] R. Hunter and A. H. Robinson. International digital facsimile coding standards. In *Proceedings of IEEE*, volume 68, pages 854–867, July 1980.
- [9] S. Inglis and I.H. Witten. Compression-based template matching. In J. Storer and M. Cohn, editors, *Proc. IEEE Data Compression Conference*, 1994.
- [10] F. Kossentini and R. Ward. An analysis-compression technique for black and white documents. In *IEEE Southwest Symposium on Image Analysis and Interpretation*, pages 141–144, San Antonio, TX, USA, April 1996.
- [11] B. Martins and S. Forchhammer. Lossless/lossy compression of bi-level images. In *Proc. of IS&T/SPIE Symp. on Electr. Im.: Science and Technology 1997*, volume 3018, pages 38–49, 1997.
- [12] B. Martins and S. Forchhammer. Halftone Coding with JBIG2. Submitted to *Journal of Electronic Imaging*, September 1998.
- [13] B. Martins and S. Forchhammer. Tree Coding of Bi-level Images. *IEEE Trans. Image Proc.*, 7(4):517–528, 1998.
- [14] B. Martins and S. Forchhammer. Lossless, near-lossless, and refinement coding of bi-level images. *IEEE Trans. Image Processing.*, 8(5):601–613, May 1999.
- [15] K. Mohiuddin, J. J. Rissanen, and R. Arps. Lossless binary image compression based on pattern matching. In *Proceedings of International Conference on Computers, Systems, and Signal Processing*, pages 447–451, Bangalore, India, 1984.
- [16] W. K. Pratt, P. J. Capitant, W. H. Chen, E. R. Hamilton, and R. H. Walls. Combined symbol matching facsimile data compression system. In *Proceedings of the IEEE*, volume 68, pages 786–796, July 1980.
- [17] A. Said and W. A. Pearlman. A new fast and efficient image codec based on set partitioning in hierarchical trees. *IEEE Transactions on Circuits and Systems for Video Technology*, 6:243–250, June 1996.
- [18] K. Sayood. *Introduction to Data Compression*. Morgan Kaufmann Publishers, San Francisco, CA, 1996.
- [19] J. T. Tou and R. C. Gonzalez. *Pattern Recognition Principles*. Addison-Wesley Publishing Company, Reading, MA, 1974.
- [20] I.H. Witten, A. Moffat, and T.C. Bell. *Managing Gigabytes*. Van Nostrand Reinhold, New York, 1994.